

MAZDA**30C2****30C2****CATHODE RAY TUBE-ALL ELECTROSTATIC 5½" Dia.**

Indirectly heated high grade precision measurement
cathode ray tube with a polished flat face

RATING

Heater Voltage (volts)	V _h	4.0
Heater Current (amps)	I _h	0.72
Maximum 1st Anode Voltage (volts)	V _{a1} (max)	2,500
Maximum 2nd Anode Voltage (volts)	V _{a2} (max)	1,000
Maximum 3rd Anode Voltage (volts)	V _{a3} (max)	6,000
Average Sensitivity of "X" Plates (mm/V)		• 600/V
Average Sensitivity of "Y" Plates (mm/V)		• 1,100/V

- Where "v" denotes the voltage on the
3rd Anode and bulb coating.

INTER-ELECTRODE CAPACITANCES

X1 Deflecting Plate/All other electrodes (μF)	C _{x1,all}	15.0
X2 Deflecting Plate/All other electrodes (μF)	C _{x2,all}	15.0
Y1 Deflecting Plate/All other electrodes (μF)	C _{y1,all}	14.5
Y2 Deflecting Plate/All other electrodes (μF)	C _{y2,all}	14.5
X1 Deflecting Plate/Y1 Deflecting Plate (μF)	C _{x1,y1}	1.5
X1 Deflecting Plate/Y2 Deflecting Plate (μF)	C _{x1,y2}	1.0
X2 Deflecting Plate/Y1 Deflecting Plate (μF)	C _{x2,y1}	1.0
X2 Deflecting Plate/Y2 Deflecting Plate (μF)	C _{x2,y2}	1.25
Control Grid (Wehnelt)/all other electrodes (μF)	C _{g,all}	9.5

DIMENSIONS

Maximum Overall Length (mm)	430
Maximum Diameter (mm)	142 ←
Nominal Screen Diameter (inches)	5½
Approximate Nett Weight (ozs)	30
Approximate Packed Weight (lbs)	11½

NOTES

For general measurement work the 30.C.2/P1 is recommended. This has a screen with a medium persistence green phosphor. For special applications, however, the tube may be supplied with any of the standard phosphors described on the Introductory Page to this Section.

Final Anode and Bulb coating are brought out separately in order to enable a finer spot or a high writing speed to be obtained by increasing the Final Anode Voltage above the limit set for the 1st Anode Voltage.

In use the 3rd Anode and Bulb coating are normally joined.

All maximum ratings are absolute values, not design centres.

Indicates a change ←

December 1953

VALVE & CRT DIVISION


Issue 3/3

SIEMENS EDISON SWAN LIMITED

30C2

MAZDA**30C2****CATHODE RAY TUBE-ALL ELECTROSTATIC 5½" Dia.**Indirectly heated high grade precision measurement
cathode ray tube with a polished flat face**TYPICAL OPERATION**

3rd Anode Voltage (volts)	Va3	2,000	5,000
2nd Anode Voltage - approximate, for focus (volts)	Va2	440	800
1st Anode Voltage (volts)	Val	2,000	2,000
Average Bias on Control Grid for Cut-off of Beam Current (volts)	Vg	-60	-60
Average Working Bias for 20µA Beam (volts)		-33	-33
Approximate Sensitivity of "X" Plates (mm/V)		0.30	0.12
Approximate Sensitivity of "Y" Plates (mm/V)		0.57	0.23

BASE Special 12 Contact Key Base (BS448)**VIEW OF FREE END****PERMISSIBLE ANGULAR
VARIATION OF MOUNTS ± 10°****CONNECTIONS**

Pin 1	Control Grid	g
Pin 2	Cathode	k
Pin 3	Heater	h
Pin 4	Heater	h
Pin 5	Anode 1	a1
Pin 6	Anode 2	a2
Pin 7	Internal Coating	m
Pin 8	Deflecting Plate Y2	y2
Pin 9	Deflecting Plate X2	x2
Pin 10	Anode 3	a3
Pin 11	Deflecting Plate X1	x1
Pin 12	Deflecting Plate Y1	y1