

MAZDA

30.C.3

CATHODE RAY TUBE-ALL ELECTROSTATIC. 5½" Dia.

Indirectly heated-for measurement purposes, with side connexions to both pairs of plates.

RATING

Heater Voltage (Volts)	V _h	4.0
Heater Current (amps)	I _h	0.72
Maximum 1st Anode Voltage (volts)	V _{a1} (max)	2,500
Maximum 2nd Anode Voltage (volts)	V _{a2} (max)	1,000
Maximum 3rd Anode Voltage (volts)	V _{a3} (max)	6,000
Average Sensitivity of "X" Plates (mm/V)		† 600/V
Average Sensitivity of "Y" Plates (mm/V)		† 1,100/V

† Where "V" denotes the voltage on the 3rd Anode and Bulb Coating.

INTER-ELECTRODE CAPACITANCES

X1 Deflecting Plate/All other electrodes (μF)	C _{x1,all}	6.0
X2 Deflecting Plate/All other electrodes (μF)	C _{x2,all}	6.0
Y1 Deflecting Plate/All other electrodes (μF)	C _{y1,all}	8.6
Y2 Deflecting Plate/All other electrodes (μF)	C _{y2,all}	8.6
X1 Deflecting Plate/Y1 Deflecting Plate (μF)	C _{x1,y1}	0.25
X1 Deflecting Plate/Y2 Deflecting Plate (μF)	C _{x1,y2}	0.25
X2 Deflecting Plate/Y1 Deflecting Plate (μF)	C _{x2,y1}	0.25
X2 Deflecting Plate/Y2 Deflecting Plate (μF)	C _{x2,y2}	0.25
Control Grid (Wehnelt)/All other electrodes (μF)	C _{g,all}	8.2
X1 Deflecting Plate/X2 Deflecting Plate (μF)	C _{x1,x2}	2.5
Y1 Deflecting Plate/Y2 Deflecting Plate (μF)	C _{y1,y2}	3.2

DIMENSIONS

Maximum Overall Length (mm)	430
Maximum Diameter (mm)	140
Nominal Screen Diameter (inches)	5½
Approximate Nett Weight (ozs)	30
Approximate Packed Weight (lbs)	11½

NOTES

The connexions to the deflector plates are brought out to side contacts on the neck of the tube in order to reduce the inductance and capacitance of the leads, and the coupling between the X and Y plates. It is intended, particularly, for H.F. and pulse measurements.

For general measurement work the 30.C.3/P1 is recommended. This has a screen with a medium persistence green phosphor. For special applications, however, the tube may be supplied with any of the standard phosphors described on the Introductory Page to this section.

Final Anode and Bulb coating are brought out separately in order to enable a finer spot or a higher writing speed to be obtained by increasing the Final Anode voltage above the limit set for the 1st Anode Voltage.

In use the 3rd Anode and Bulb coating are normally joined.

MAZDA

30.C.3

30.C.3


CATHODE RAY TUBE - ALL ELECTROSTATIC. 5 $\frac{1}{2}$ " Dia.

Indirectly heated - for measurement purposes, with side connexions to both pairs of plates.

TYPICAL OPERATION

3rd Anode Voltage (volts)	Va3	2,000	6,000
2nd Anode Voltage - approximate for focus (volts)	Va2	440	960
1st Anode Voltage (volts)	Va1	2,000	2,000
Average Bias on Control Grid for Cut-off of Beam Current (volts)	Vg	-60	-60
Average Working Bias for 20 μ A Beam (volts)		-33	-33
Approximate Sensitivity of "X" Plates (mm/V)		0.30	0.1
Approximate Sensitivity of "Y" Plates (mm/V)		0.57	0.19

BASE 12 Contact Key Base BS.448.



CONNEXIONS

Pin 1	Control Grid	g
Pin 2	Cathode	k
Pin 3	Heater	h
Pin 4	Heater	h
Pin 5	Anode 1	a1
Pin 6	Anode 2	a2
Pin 7	-	-
Pin 8	-	-
Pin 9	-	-
Pin 10	Anode 3	a3
Pin 11	-	-
Pin 12	-	-