

31C14

CATHODE RAY TUBE

Indirectly heated—for Radio D.F. Compass

GENERAL

The 31C14 is a magnetically focused and deflected cathode ray tube. The tube is aluminised, has a 6" diameter flat face, and is available with a screen type T1 which gives a green trace of medium persistence. It has an internal compass scale uniformly graduated and its face is treated to reduce specular reflection.

RATING

Heater Voltage	V_h	6.3 V
Heater Current	I_h	0.6 A
Maximum Anode Voltage	$V_a(\text{max})$	10* kV
Minimum Anode Voltage	$V_a(\text{min})$	7.5 kV
Maximum Heater/Cathode Voltage d.c. (heater negative)	$V_{h-k}(\text{max})$	150 V

* 10 kV is a design centre rating. The absolute rating of 12.5 kV maximum must not be exceeded.

INTER-ELECTRODE CAPACITANCES

Grid/All other electrodes	$C_{g-\text{all}}$	4.7 pF
Cathode/All other electrodes	$C_{k-\text{all}}$	5.3 pF

These capacitances include an AEI wafer-type duodecal holder.

TYPICAL OPERATION

Anode Voltage	V_a	9.5 kV
Grid Bias Voltage for cut-off of 140mm focused line	V_g	-43 to -93 V
Average Peak to Peak Modulating Voltage for Modulation up to 150 μ A		30 V
Maximum Peak to Peak Modulating Voltage for Modulation of limit Cathode Ray Tube up to 150 μ A		35 V

A resistance should be inserted in the anode circuit in order to limit the discharge current to 100mA (max), in the event of a flash-over inside the tube.

31C14

CATHODE RAY TUBE


Indirectly heated—for Radio D.F. Compass

DIMENSIONS

Maximum Overall Length	458 mm
Maximum Face Diameter	160 mm
Maximum Neck Diameter	35 mm
Approximate Net Weight	2 $\frac{1}{4}$ lb.
Approximate Packed Weight	16 $\frac{1}{4}$ lb.

CAP—Cavity (CT8)

BASE—B12A (5 Pin)



Viewed from free end of pins

CONNECTIONS

Pin 1	Heater	h
Pin 2	Grid	g
Pin 3	No Pin	NP
Pin 4	No Pin	NP
Pin 5	No Pin	NP
Pin 6	No Pin	NP
Pin 7	No Pin	NP
Pin 8	No Pin	NP
Pin 9	No Pin	NP
Pin 10	No Connection	NC
Pin 11	Cathode	k
Pin 12	Heater	h
Cap	Anode	a