

ELECTRON TUBE DATA SHEET

WESTERN ELECTRIC 346B ELECTRON TUBE



DESCRIPTION

The 346B is a three-electrode, inert-gas-filled, cold cathode tube for use in relay, voltage regulator, or rectifier circuits. This tube is especially suitable for use in control circuits such as in triggering, counting, or switching apparatus.

MAXIMUM RATINGS

Peak Anode Voltage		225 volts
Average Cathode Current	10	100 milliamperes
Average Life, Approximate	10000	10 hours

MAXIMUM RATINGS, Absolute Values

Forward Peak Anode Voltage	225 volts
Forward Cathode Current ¹	
Peak	100 milliamperes
Average	35 milliamperes
Averaging Time	2 seconds
Inverse Peak Anode Current ¹	5 milliamperes
Ambient Temperature Limits	-55 to +85 centigrade

ELECTRICAL DATA

	Min.	Bogey	Max.
Starter Breakdown Voltage ²	65	70	89 volts
Starter Voltage Drop at 20 Milliamperes	52	60	74 volts
Anode Voltage Drop at 20 Milliamperes.	72	80	90 volts
Transfer Current	See curve - Fig. 3		
Ionization Time - Starter Gap ³	---	6	---
Deionization Time, Approximate			
Starter Gap	---	2	---
Main Gap	---	8	---
Inverse Current at			
-120 Volts Anode Potential ⁴	---	---	3 milliamperes

MECHANICAL DATA

Mounting Position Any
 Net Weight, Approximate 1 ounce
 Dimensions and pin connections shown in outline drawing on page 4

Note 1: Sufficient resistance must be used in series with the tube to assure that the electrode currents do not exceed their maximum rated values.

Note 2: Limits apply immediately after tube has conducted current. If the tube has been idle, these values initially may be as much as 3 volts higher or lower.

Note 3: With 15 volts starter overvoltage (15 volts above Starter Breakdown Voltage) with tube in total darkness.

Note 4: Negative anode voltage applied through 8000 ohms. Starter connected to anode through 100000 ohms.

HANDLING

Western Electric cold cathode tubes contain a minute amount of radium bromide which is a radioactive material. The amount in most types is too small to require any special care in use, handling or disposal.

A few types contain a larger quantity of radium bromide in which the radium approximates that found on a luminous watch dial. These types bear a red three-bladed propeller-shaped symbol on the tube envelope. Instructions for handling such tubes are given below and also in Bell System Practices for Central Office maintenance.

Installations ordinarily require no precautions against radiation. However, quantities of the tubes should not be so installed, or so stored outside the shipping carton, that they will be within a few inches of personnel or in proximity to photographic film for extended periods of time. For example, however, a 40-hour week exposure at about one (1) foot from a bank of 500 tubes (covering an area of 20 inches x 45 inches) is well within the accepted tolerance limits for personnel. Reasonable care should be exercised in handling and disposal of broken tubes. In general, attention should be given to the following:

- (a) Avoid breathing dust or vapors from broken tubes.
- (b) Avoid contacting broken parts with bare hands.
- (c) Use wet rag to pick up broken parts. Wrap broken parts in rag and tie securely so as to form a package. Thoroughly wash hands after disposal.
- (d) Dispose of broken or defective tubes as they are taken out of service. One or two tubes at a time may be disposed of with normal waste material. Accumulation of tubes in one concentrated area of the place of final disposition should be avoided.




FIG. 1




FIG. 2





FIG. 3



A development of Bell Telephone Laboratories, the research laboratories of the American Telephone and Telegraph Company and the Western Electric Company.