


TUNG-SOL

DOUBLE TRIODE

MINIATURE TYPE

COATED FILAMENT



GLASS BULB

SERIES FILAMENT
 E_f APPLIED BETWEEN
 PINS 1 & 7
 E_g REFERRED TO PIN 1


2.8 VOLTS
 110 MA.

PARALLEL FILAMENT
 E_f APPLIED BETWEEN
 PIN 4 AND PINS 1 &
 7 TIED TOGETHER.
 E_g REFERRED TO PIN 4

1.4 VOLTS
 220 MA.

DC

A SHUNTING RESISTOR MUST BE CONNECTED BETWEEN PINS 1 AND 4 FOR SERIES-FILAMENT OPERATION. ITS VALUE SHOULD BE SUCH THAT THE VOLTAGE ACROSS THE SHUNTED SECTION IS EQUAL TO THE VOLTAGE BETWEEN PINS 4 AND 7. AN ADDITIONAL SHUNTING RESISTOR MAY BE NECESSARY BETWEEN PINS 1 AND 7 IF OTHER TUBES USED IN SERIES-FILAMENT ARRANGEMENT CONTRIBUTE TO THE FILAMENT CURRENT OF THE 3A5.



BOTTOM VIEW
 MINIATURE BUTTON
 7 PIN BASE

ANY MOUNTING POSITION

THE 3A5 IS INTENDED FOR USE IN HIGH FREQUENCY APPLICATIONS. THE RELATIVELY LARGE FILAMENT EMPLOYED IN THE 3A5 ENABLES IT TO SUPPLY THE HIGH PEAK CURRENTS REQUIRED IN RF POWER APPLICATIONS. IN CLASS C SERVICE, A 3A5 WITH ITS UNITS IN PUSH-PULL WILL DELIVER A POWER OUTPUT OF APPROXIMATELY 2 WATTS AT 40 MEGACYCLES. IT MAY BE USED AT STILL HIGHER FREQUENCIES WITH REDUCED EFFICIENCY. EACH TRIODE MAY BE USED INDEPENDENTLY OF THE OTHER.

DIRECT INTERELECTRODE CAPACITANCES

	TRIODE UNIT 1	TRIODE UNIT 2	
GRID TO PLATE: (G TO P)	3.2	3.2	μf
INPUT: (G TO H)	0.9	0.9	μf
OUTPUT: (P TO H)	1.0	1.0	μf
PLATE TO PLATE: (P TO P)	0.32		μf

RATINGS

INTERPRETED ACCORDING TO RMA STANDARD MB-210

	AF AMPLIFIER		RF AMPLIFIER		
FILAMENT VOLTAGE	1.4	2.8	1.4	2.8	VOLTS
MAXIMUM PLATE VOLTAGE	135		135		VOLTS
MAXIMUM DC GRID VOLTAGE	---		-30		VOLTS
MAXIMUM PLATE CURRENT	5		---		MA.
MAXIMUM DC PLATE CURRENT (PER UNIT)	---		15		MA.
MAXIMUM DC GRID CURRENT (PER UNIT)	---		2.5		MA.
MAXIMUM PLATE DISSIPATION	0.5		---		WATT
MAXIMUM PLATE DISSIPATION (PER UNIT)	---		1.0		WATT
MAXIMUM PLATE INPUT (PER UNIT)	---		2.0		WATT

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

AF AMPLIFIER

HEATER VOLTAGE	1.4	2.8	VOLTS
HEATER CURRENT	220	110	MA.
PLATE VOLTAGE	90		VOLTS
GRID VOLTAGE	-2.5		VOLTS
PLATE CURRENT	3.7		MA.
PLATE RESISTANCE	8 300		OHMS
TRANSCONDUCTANCE	1 800		MMHOS
AMPLIFICATION FACTOR	15		

RF POWER AMPLIFIER AND OSCILLATOR-CLASS "C" TELEGRAPHY

AT 40 MC WITH BOTH UNITS IN PUSH-PULL
(KEY-DOWN CONDITIONS PER TUBE WITHOUT MODULATION)

FILAMENT VOLTAGE	1.4	2.8	VOLTS
FILAMENT CURRENT	220	110	MA.
DC PLATE VOLTAGE	135		VOLTS
DC GRID VOLTAGE:			
FROM A FIXED SUPPLY OF	-20		VOLTS
FROM A GRID RESISTOR OF	4 000		OHMS
FROM A CATHODE RESISTOR OF	570		OHMS
PEAK RF GRID-TO-GRID VOLTAGE	90		VOLTS
DC PLATE CURRENT	30		MA.
DC GRID CURRENT (APPROX.)	5		MA.
DRIVING POWER (APPROX.)	0.2		WATT
POWER OUTPUT (APPROX.)	2		WATTS

PLATE
1910
NOV. 1,
1947

