


TUNG-SOL


PENTODE
MINIATURE TYPE

GLASS BULB
MINIATURE BUTTON
7 PIN BASE E7-1
OUTLINE DRAWING
JEDEC 5-2

COATED UNIPOTENTIAL CATHODE

HIGH FREQUENCY INTERMEDIATE
AND RF AMPLIFIER

ANY MOUNTING POSITION



BOTTOM VIEW
BASING DIAGRAM
BASING DIAGRAM
JEDEC 7B0

THE 3BC5 IS A HIGH TRANSCONDUCTANCE PENTODE VOLTAGE AMPLIFIER IN THE 7 PIN MINIATURE CONSTRUCTION. IT IS DESIGNED FOR USE IN 600 MA. SERIES HEATER OPERATED RECEIVERS. IT IS USEFUL AS AN RF AMPLIFIER UP TO ABOUT 400 MC. AND AS A HIGH-FREQUENCY INTERMEDIATE AMPLIFIER. THERMAL CHARACTERISTICS OF THE HEATER ARE CONTROLLED SUCH THAT HEATER VOLTAGE SURGES DURING THE WARM-UP CYCLE ARE MINIMIZED PROVIDED IT IS USED WITH OTHER TYPES WHICH ARE SIMILARLY CONTROLLED.

DIRECT INTERELECTRODE CAPACITANCES

	WITH SHIELD ^A	WITHOUT SHIELD	
PENTODE CONNECTION:			
GRID TO PLATE: (G ₁ TO P) MAX.	0.020	0.030	pf
INPUT: G ₁ TO (H+K+G ₂ +G ₃ & I.S.)	6.6	6.5	pf
OUTPUT: P TO (H+K+G ₂ +G ₃ & I.S.)	3.1	1.8	pf
TRIODE CONNECTION: (G₂ TIED TO PLATE)			
GRID TO PLATE: G ₁ TO (P+G ₂)	2.5	2.5	pf
INPUT: G ₁ TO (H+K+G ₃ & I.S.)	4.0	3.9	pf
OUTPUT: (P+G ₂) TO (H+K+G ₃ & I.S.)	4.3	3.0	pf

^A

EXTERNAL SHIELD #316 CONNECTED TO PIN #7.

HEATER CHARACTERISTICS AND RATINGS

DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239

AVERAGE CHARACTERISTICS	3.15 VOLTS	600	MA.
HEATER WARM-UP TIME*		11	SECONDS
HEATER SUPPLY LIMITS:			
CURRENT OPERATION		600 ± 40	MA.
MAXIMUM HEATER-CATHODE VOLTAGE:			
HEATER NEGATIVE WITH RESPECT TO CATHODE		200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE		200 ^B	VOLTS

^B

DC COMPONENT MUST NOT EXCEED 100 VOLTS.

→ INDICATES A CHANGE.

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

→ MAXIMUM RATINGS

DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239

	TRIODE ^C	PENTODE	
PLATE VOLTAGE	330	330	VOLTS
GRID #2 VOLTAGE	PLATE	SEE RATING CHART	
GRID #2 SUPPLY VOLTAGE	PLATE	330	VOLTS
PLATE DISSIPATION	2.9 ^C	2.3	WATTS
GRID #1 VOLTAGE (POSITIVE BIAS VALUE)	0	0	VOLT
GRID #2 DISSIPATION			
FOR VOLTAGES UP TO 165 V.	---	0.55	WATTS
FOR VOLTAGES BETWEEN 165 & 330 V.	---	SEE RATING CHART	

→ TYPICAL OPERATING CHARACTERISTICS

CLASS A₁ AMPLIFIER

	TRIODE ^C			PENTODE		
PLATE VOLTAGE	250	180	100	125	250	VOLTS
GRID #2 VOLTAGE			100	125	150	VOLTS
CATHODE RESISTOR	820	330	180	100	180	OHMS
TRANSCONDUCTANCE	4400	6000	4900	6100	5700	μMHOS
PLATE RESISTANCE (APPROXIMATELY)	0.009	0.006	0.6	0.5	0.8	MEGOHM
AMPLIFICATION FACTOR	40	42	---	---	---	
PLATE CURRENT	6.0	8.0	4.7	8.0	7.5	MA.
GRID #2 CURRENT	---	---	1.4	2.4	2.1	MA.
GRID #1 VOLTAGE (APPROX.) FOR I _b = 10 μA.	---	---	-5	-6	-8	VOLTS

^C G₂ TIED TO PLATE.

→ INDICATES A CHANGE.

* HEATER WARM-UP TIME IS DEFINED AS THE TIME REQUIRED FOR THE VOLTAGE ACROSS THE HEATER TO REACH 80% OF ITS RATED VOLTAGE AFTER APPLYING 4 TIMES RATED HEATER VOLTAGE TO A CIRCUIT CONSISTING OF THE TUBE HEATER IN SERIES WITH A RESISTANCE OF VALUE 3 TIMES THE NOMINAL HEATER OPERATING RESISTANCE.

