



3D22-A

3D22-A GAS THYRATRON

NEGATIVE-CONTROL TETRODE TYPE

*Supersedes Type 3D22***GENERAL DATA****Electrical:**

Heater, for Unipotential Cathode:

	Min.	Av.	Max.	
Voltage	5.7	6.3	6.9	ac or dc volts
Current at 6.3 volts. . .	-	2.6	2.85	amp

Cathode:

Minimum heating time prior to tube conduction.	30	sec
Maximum outage time without reheating. .	3	sec

Direct Interelectrode Capacitances

(Approx.):⁰

Grid No.1 to anode*.	0.1	μf
Grid No.1 to cathode, grid No.2, base shell, and heater	8.5	μf
Anode to cathode, grid No.2, base shell, and heater	4.6	μf

Ionization Time (Approx.):

For conditions: dc anode volts = 100, grid-No.1 square-pulse volts = +100, and peak anode amperes during conduction = 8	0.5	μsec
---	-----	-----------------

Deionization Time (Approx.):

For conditions: dc anode volts = 125, dc grid-No.1 volts = -200, grid-No.1 resistor (ohms) = 1000, and dc anode amperes = 0.8.	150	μsec
For conditions: dc anode volts = 125, dc grid-No.1 volts = -14.8, grid-No.1 resistor (ohms) = 1000, and dc anode amperes = 0.8.	400	μsec

Maximum Critical Grid-No.1 Current:

For conditions: ac anode-supply volts = 460 (rms), and average anode amperes = 0.8.	0.8	μamp
---	-----	-----------------

Anode Voltage Drop (Approx.) 10 volts

Grid-No.1 Control Ratio (Approx.):

For conditions: grid-No.1 resistor (megohms) = 0 to 0.1, grid-No.2 resistor (megohms) = 0, and grid-No.2 volts = 0	150	
--	-----	--

Grid-No.2 Control Ratio (Approx.):

For conditions: grid-No.1 resistor (megohms) = 0, grid-No.2 resistor (megohms) = 0 to 0.1, and grid-No.1 volts = -3	650	
---	-----	--

⁰ Without external shield.

* With all other electrodes and base shell connected to ground.

3D22-A




3D22-A GAS THYRATRON

Mechanical:

Mounting Position.	Any
Maximum Overall Length	4-5/8"
Maximum Seated Length.	4"
Maximum Diameter	2-3/8"
Weight (Approx.)	5 oz
Bulb	T-16
Base	Medium-Metal-Shell Giant 7-Pin with Bayonet (JETEC No. A7-17)

Basing Designation for BOTTOM VIEW 7BV

Pin 1 - Heater
Pin 2 - Grid No.2
Pin 3 - Cathode
Pin 4 - Grid No.1



AA'= PLANE OF ELECTRODES

Pin 5 - Grid No.2
Pin 6 - Anode
Pin 7 - Heater

RELAY AND GRID-CONTROLLED RECTIFIER SERVICE

Maximum Ratings, Absolute Values:

PEAK ANODE VOLTAGE:

Forward.	650 max.	volts
Inverse.	1500 max.	volts

GRID-No.2 (SHIELD-GRID) VOLTAGE:

Peak, before tube conduction	-100 max.	volts
Average#, during tube conduction	-10 max.	volts

GRID-No.1 (CONTROL-GRID) VOLTAGE:

Peak or DC, before tube conduction	-200 max.	volts
Average#, during tube conduction	-10 max.	volts

CATHODE CURRENT:

Peak	8 max.	amp
Average#	0.8 max.	amp
Fault, for duration of 0.1 second max.	30 max.	amp

AVERAGE GRID-No.2 CURRENT#:

.	+0.1 max.	amp
-----------	-----------	-----

AVERAGE GRID-No.1 CURRENT#:

.	+0.05 max.	amp
-----------	------------	-----

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode.	100 max.	volts
Heater positive with respect to cathode.	25 max.	volts

AMBIENT-TEMPERATURE RANGE.	-75 to +90	°C
------------------------------------	------------	----

Maximum Circuit Values:

Grid-No.1-Circuit Resistance	2 max.	megohms
--	--------	---------

Averaged over any interval of 30 seconds maximum.



3D22-A

3D22-A

GAS THYRATRON

SPECIAL PERFORMANCE TESTS

Made in conformance with indicated sections of
MIL-E-1B Specifications dated 2 May 1952

4.9.19.2 (F-66) High-Frequency Vibration:

The tube is rigidly mounted on a table vibrating with simple harmonic motion at a frequency of 50 ± 2 cps with a fixed amplitude of $0.040" \pm 0.0025"$ (total excursion is double the amplitude). Maximum acceleration is 10g. No voltage is applied during vibration. Tube is vibrated for 10 minutes in such manner that table motion is along shortest line between anode and cathode. This test will not cause tube to be inoperative.

4.10.19 (F-64) Thyatron High-Voltage Operation:

Min. Max.

Grid-No.1 Supply Voltage (1) -4.4 -9.2 volts

This test is made after two light taps with a felt hammer (similar to type used for noise tests) in direction from cathode to anode under the following conditions: heater voltage of 6.3 volts rms, anode supply voltage of 500 volts rms, grid No.2 tied to cathode, load resistance of 2000 ohms, and grid-No.1 circuit-resistance of 2 megohms. Tube conduction is indicated by an oscilloscope connected between anode and cathode and ceases when the grid-No.1 supply voltage is increased negatively within indicated range.

Grid-No.1 Supply Voltage (2) -4.4 -9.2 volts

This test is made as for Grid-No.1 Supply Voltage (1), except that the taps are made in direction from anode to cathode.

Voltage Difference - 1 volt

The difference between the value of grid-No.1 supply voltage in the first and second grid-No.1 supply voltage tests will not exceed the specified value.

OPERATING CONSIDERATIONS

Sufficient anode-circuit resistance, including the tube load, must be used under any conditions of operation to prevent exceeding the current ratings of the tube.



3D22-A

GRID-CONTROLLED RECTIFIER CIRCUITS

DC Voltage Control




FIG. 1 HALF-WAVE SINGLE-PHASE




FIG. 2 FULL-WAVE SINGLE-PHASE




FIG. 3 SERIES SINGLE-PHASE

AC Voltage Control




FIG. 4 FULL-WAVE SINGLE-PHASE

NOTES

92CL-8596

T=PEAKING TRANSFORMER

IN FIG. 3, THE RECTIFIER TUBES MAY BE 3D22-A'S USED AS DIODES. THE 3D22-A IS USED AS A DIODE BY CONNECTING GRIDS N°2 AND N°1 TO CATHODE (PIN 3)

Devices and arrangements shown or described herein may use patents of RCA or others. Information contained herein is furnished without responsibility by RCA for its use and without prejudice to RCA's patent rights.



3D22-A

3D22-A

GRID-CONTROLLED RECTIFIER CIRCUITS

Numerical Relationships Among Electrical Quantities

E = Trans. Sec. Voltage (RMS)	I_{av} = Average DC Output Current
E_{av} = Average DC Output Voltage	I_b = Average Anode Current
E_{bmf} = Peak Forward Anode Voltage	I_p = Anode Current (RMS)
E_{bmi} = Peak Inverse Anode Voltage	I_{pm} = Peak Anode Current
E_m = Peak DC Output Voltage	P_{ac} = Load Volt-Amperes
E_r = Major Ripple Voltage (RMS)	P_{al} = Line Volt-Amperes
f = Supply Frequency	P_{ap} = Trans. Pri. Volt-Amperes
f_r = Major Ripple Frequency	P_{as} = Trans. Sec. Volt-Amperes
P_{dc} = DC Power ($E_{av} \times I_{av}$)	

Note: Conditions assumed involve sine-wave supply; zero voltage drop in tubes; no losses in transformer and circuit; no back emf in the load circuit; and no phase-back.

RATIO	Fig. 1	Fig. 2	Fig. 3	Fig. 4
Voltage Ratios				
E/E_{av}	2.22	1.11	1.11	-
E_{bmi}/E	1.41	2.83	1.41	1.41
E_{bmi}/E_{av}	3.14	3.14	1.57	-
E_m/E_{av}	3.14	1.57	1.57	-
E_r/E_{av}	1.11	0.472	0.472	-
E_{bmf}/E :				
Resistive Load	1.41	1.41	1.41	1.41
Inductive Load [■]	1.41	2.83	1.41	1.41
Frequency Ratio				
f_r/f	1	2	2	-
Current Ratios				
I_p/I_{av}	1.57	0.785	0.785	-
I_b/I_{av}	1	0.5	0.5	-
Resistive Load				
I_{pm}/I_{av}	3.14	1.57	1.57	-
I_{pm}/I_b	3.14	3.14	3.14	3.14
Inductive Load [■]				
I_{pm}/I_{av}	--	1	1	-
Power Ratios				
$P_{ac}/I_b E_{bmf}$	--	-	-	1.57
Resistive Load				
P_{as}/P_{dc}	3.49	1.74	1.24	-
P_{ap}/P_{dc}	2.69	1.23	1.24	-
P_{al}/P_{dc}	2.69	1.23	1.24	-

■: See next page.

JULY 1, 1955

TUBE DIVISION

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

DATA 3

3D22-A




3D22-A GAS THYRATRON

RATIO	Fig. 1	Fig. 2	Fig. 3	Fig. 4
Power Ratios (Cont'd)				
<i>Inductive Load</i> ■				
P_{as}/P_{dc}	—	1.57	1.11	—
P_{ap}/P_{dc}	—	1.11	1.11	—
P_{al}/P_{dc}	—	1.11	1.11	—

■ The use of a large filter-input choke is assumed, except for the circuit in Fig. 4.

CIRCUIT Single-Phase	MAX. TRANS. SEC. VOLTS (RMS) E	APPROX. DC OUTPUT VOLTS TO FILTER E _{av}	MAX. DC OUTPUT AMPERES I _{av}	MAX. DC OUTPUT WATTS TO FILTER P _{dc}	MAX. AC OUTPUT VOLT- AMPERES P _{ac}
Fig. 1 Half-Wave	460	205	0.8	165	—
Fig. 2 Full-Wave: Resistive Load	460	410	1.6	660	—
Inductive Load	230	205	1.6	330	—
Fig. 3 Series	460	410	1.6	660	—
Fig. 4 Full-Wave	460	—	—	—	800



92CM-6569R2

JULY 1, 1955

TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

DATA 3




3D22-A

3D22-A GAS THYRATRON

OPERATIONAL RANGE OF CRITICAL GRID-Nº1 VOLTAGE

GRID Nº2 (SHIELD) CONNECTED TO CATHODE. RANGES SHOWN ARE FOR TWO VALUES OF GRID-Nº1 RESISTOR, 0.1 MEG. AND 2 MEG., AND TAKE INTO ACCOUNT INITIAL DIFFERENCES BETWEEN INDIVIDUAL TUBES AND SUBSEQUENT DIFFERENCES DURING TUBE LIFE, FOR HEATER-VOLTAGE RANGE OF 5.7 TO 6.9 VOLTS, AND FOR AN AMBIENT TEMPERATURE RANGE OF -40 TO +90 °C.




3D22-A



3D22-A

AVERAGE CONTROL CHARACTERISTICS



JAN. 22, 1947

DC ANODE VOLTS

TUBE DIVISION

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY



92CM-6831



3D22-A

3D22-A

CHARACTERISTIC CURVES



JULY 1, 1955

TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEYCE-6865T1
-6830T

A 5574

U. S. DEPARTMENT OF AGRICULTURE

PLANT INDUSTRY DIVISION
WASHINGTON, D. C.

PLANT INDUSTRY DIVISION
WASHINGTON, D. C.

PLANT INDUSTRY DIVISION
WASHINGTON, D. C.

PLANT INDUSTRY DIVISION
WASHINGTON, D. C.

PLANT INDUSTRY DIVISION
WASHINGTON, D. C.

PLANT INDUSTRY DIVISION
WASHINGTON, D. C.

PLANT INDUSTRY DIVISION
WASHINGTON, D. C.

PLANT INDUSTRY DIVISION
WASHINGTON, D. C.