


TUNG-SOL

HI-MU TRIODE ←

MINIATURE TYPE

**GLASS BULB**


BASE E7-1
OUTLINE DRAWING
JEDEC 5-2

COATED UNIPOTENTIAL CATHODE

HEATER

2.8 VOLTS 0.45 AMP.

ANY MOUNTING POSITION

**BOTTOM VIEW**

BASING DIAGRAM
JEDEC 7FP

THE 3ER5 IS A HIGH TRANSCONDUCTANCE SHIELDED TRIODE IN THE 7 PIN MINIATURE CONSTRUCTION. IT IS DESIGNED ESPECIALLY FOR USE IN V.H.F. TELEVISION TUNERS. SEPARATE CATHODE LEADS PROVIDE LOW LEAD INDUCTANCE AND THE INTERNAL SHIELD REDUCES DIRECT GRID TO PLATE CAPACITANCE. EXCEPT FOR HEATER RATINGS AND HEATER WARM-UP TIME, THE 3ER5 IS IDENTICAL TO THE 2ER5 AND THE 6ER5.

DIRECT INTERELECTRODE CAPACITANCES

	WITHOUT SHIELD	WITH SHIELD	
PLATE TO GRID	0.38	0.36	μf
GRID TO ALL OTHER ELECTRODES EXCEPT PLATE	4.4	4.4	μf
PLATE TO ALL OTHER ELECTRODES EXCEPT GRID	3.0	4.0	μf
GRID TO HEATER (MAX.)	0.28	0.28	μf
PLATE TO CATHODE	0.24	0.20	μf
GRID TO CATHODE	3.1	3.1	μf
CATHODE TO HEATER	2.8	2.8	μf

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

HEATER VOLTAGE	2.8	VOLTS
MAXIMUM PLATE VOLTAGE WITHOUT CURRENT	550	VOLTS
MAXIMUM PLATE VOLTAGE	250	VOLTS
MAXIMUM PLATE DISSIPATION	2.2	WATTS
MAXIMUM CATHODE CURRENT	20	MAMPS
MAXIMUM NEGATIVE GRID VOLTAGE	50	VOLTS
MAXIMUM VOLTAGE BETWEEN CATHODE AND HEATER	100	VOLTS
MAXIMUM GRID CIRCUIT RESISTANCE	1	MEG OHM
MAXIMUM CIRCUIT RESISTANCE BETWEEN CATHODE AND HEATER	20 000	OHMS

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

HEATER VOLTAGE	2.8	2.8	VOLTS
HEATER CURRENT	0.45	0.45	AMP.
PLATE VOLTAGE	200		VOLTS
GRID VOLTAGE	-1.2	-3.8	-5.6
PLATE CURRENT	10		MAMPS
TRANSCONDUCTANCE	500	500	100 μ MHOS
AMPLIFICATION FACTOR	80		
GRID VOLTAGE FOR A CROSS-MODULATION FACTOR OF 1% (RMS)	100	100	100 MV.