

Sharp-Cutoff Twin Pentode With Common Cathode, Grid No.1, and Grid No.2

The 3GS8 is the same as the 4GS8/4BU8 except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A	E_h	3.15	V

3HM5/3HA5

High-Mu Triode

The 3HM5/3HA5 is the same as the 6HM5/6HA5 except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A	E_h	2.7	V
Warm-up time (Average).		11	s

3HS8

Sharp-Cutoff Twin Pentode

The 3HS8 is the same as the 6HS8 except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A	E_h	3.15	V
Warm-up time (Average).		11	s



3JC6, 3JC6A

Sharp-Cutoff Pentodes

The 3JC6 and 3JC6A are the same as the 6JC6 and 6JC6A, respectively, except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A	E_h	3.5	V
Warm-up time (Average).		11	s

3JD6

Sharp-Cutoff Pentode

The 3JD6 is the same as the 6JD6 except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A	E_h	3.5	V
Warm-up time (Average).		11	s

3KT6

Semiremote-Cutoff Pentode

The 3KT6 is the same as the 6KT6 except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A	E_h	3.5	V
Warm-up time (Average).		11	s

