

CHARACTERISTICS

GENERAL DATA

Focusing Method	Electrostatic
Deflection Method	Electrostatic
Phosphor	P1
Fluorescence	Green
Persistence	Medium
Faceplate	Clear

ELECTRICAL DATA

Heater Voltage	6.3 Volts
Heater Current	$0.6 \pm 10\%$ Ampere
Direct Interelectrode Capacitances (approx.)	
Grid to All Other Electrodes	$8.5 \mu\mu\text{f}$
Between Deflecting Plates 1-2	$2.0 \mu\mu\text{f}$
Between Deflecting Plates 3-4	$2.0 \mu\mu\text{f}$
Deflecting Plate 1 ¹ to All Other Electrodes	$11.0 \mu\mu\text{f}$
Deflecting Plate 2 ¹ to All Other Electrodes	$8.0 \mu\mu\text{f}$
Deflecting Plate 3 ¹ to All Other Electrodes	$7.0 \mu\mu\text{f}$
Deflecting Plate 4 ¹ to All Other Electrodes	$8.0 \mu\mu\text{f}$

MECHANICAL DATA

Minimum Useful Screen Diameter	$2\frac{3}{4}$ Inches
Base (Small-Shell Duodecal 10-Pin)	B10-75
or (Small-Shell Duodecal 12-Pin)	B12-43
Basing	12E

RATINGS

MAXIMUM RATINGS (Absolute Maximum Values)

Anode No. 2 Voltage	2750 Volts dc
Anode No. 1 Voltage	1100 Volts dc
Grid Voltage	
Negative Bias Value	220 Volts dc
Positive Bias Value	0 Volts dc
Positive Peak Value	2 Volts
Peak Heater-Cathode Voltage	
Heater Negative with Respect to Cathode	140 Volts
Heater Positive with Respect to Cathode	140 Volts
Peak Voltage Between Anode No. 2 and Any Deflection Plate	
	550 Volts

TYPICAL OPERATING CONDITIONS



Anode No. 2 Voltage ²	2000 Volts dc
Anode No. 1 Voltage for Focus	330 to 620 Volts dc
Maximum Grid Voltage Required for Cutoff ³	-135 Volts dc
Deflection Factor ^{4, 5}	
Deflecting Plates 1-2 ⁶	146 to 198 Volts dc/Inch
Deflecting Plates 3-4 ⁷	104 to 140 Volts dc/Inch

CIRCUIT VALUES

Grid Circuit Resistance	1.5 Megohms Max.
Deflection Circuit Resistance	5.0 Megohms Max.

QUICK REFERENCE DATA

Special Purpose Tube
3" Direct Viewed
Round Glass Type
Electrostatic Deflection
Electrostatic Focus



SYLVANIA ELECTRIC
PRODUCTS INC.

TELEVISION PICTURE TUBE
DIVISION

SENECA FALLS, NEW YORK


Prepared and Released By The
TECHNICAL PUBLICATIONS SECTION
EMPORIUM, PENNSYLVANIA

JULY, 1957

PAGE 1 OF 2

NOTES:

1. Positive voltage on Pin No. 10 will move spot approximately in direction of Pin No. 4.
Positive voltage on Pin No. 6 will move spot approximately in direction of Pin No. 1.
2. Brilliance and definition decrease with decreasing Anode No. 2 Voltage. In general, Anode No. 2 Voltage should not be less than 1500 volts.
3. Visual extinction of undeflected focused spot.
4. Angle between trace produced by plates D1-D2 and the plane through the tube axis and Pin No. 4 does not exceed 10° .
5. Angle between D1-D2 trace and D3-D4 trace is $90^{\circ} \pm 30$.
6. Deflecting Plates 1-2 are nearer the screen.
7. Deflecting Plates 3-4 are nearer the base.



3RP4

The Sylvania Type 3RP4 is identical to the Type 3RP1 except it has a white phosphor of short to medium persistence.