


TUNG-SOL

TWIN TRIODE
MINIATURE TYPE


GLASS BULB

HEATER

SERIES
 $40 \pm 5\%$ VOLTS
 .05 AMP.

PARALLEL
 $20 \pm 5\%$ VOLTS
 0.1 AMP.

ANY MOUNTING POSITION



BOTTOM VIEW
 MINIATURE BUTTON
 9 PIN BASE

THE TYPE 407A IS A NINE PIN MINIATURE, MEDIUM MU, TWIN TRIODE, FEATURING SEPARATE CATHODES. THE HEATER IS DESIGNED FOR PARALLEL OPERATION AT 20 VOLTS OR FOR SERIES OPERATION AT 40 VOLTS. OTHER CHARACTERISTICS ARE SIMILAR TO THOSE OF THE 2C51 AND THE 5670. A SHIELD IS ATTACHED TO THE CENTER OF THE HEATER TO DECREASE POSSIBLE INTERACTION BETWEEN TRIODE SECTIONS. THE USEFUL FREQUENCY RANGE AS AN AMPLIFIER, MIXER, OSCILLATOR, OR MULTIVIBRATOR EXTENDS FROM LOW FREQUENCY TO VHF.

BECAUSE OF THE INHERENT LOW NOISE AND CHOICE OF EITHER 20 VOLT OR 40 VOLT HEATER OPERATION, THE 407A HAS FOUND WIDE USE IN CARRIER TELEPHONY CIRCUITS.

ELECTRICAL DATA

HEATER VOLTAGE SERIES CONNECTION

(USE PINS 1 & 9)

 $40 \pm 5\%$ VOLTS

PARALLEL CONNECTION (TIE PIN 1 TO PIN 9:

USE PIN 5, 1 & 9)

 $20 \pm 5\%$ VOLTS

HEATER CURRENT SERIES CONNECTION

(USE PINS 1 & 9)

.05 AMP.

PARALLEL CONNECTION (TIE PIN 1 TO PIN 9:

USE PIN 5, 1, & 9)

0.1 AMP.

CHARACTERISTICS PER SECTION UNDER CONDITIONS

$$E_b = 150 \text{ Vdc}, E_c = 0, R_k/x = 240 \text{ OHMS}$$

PLATE CURRENT

8.2

MADC

TRANSCONDUCTANCE

5 500

 μMHOS

AMPLIFICATION FACTOR

35

PLATE RESISTANCE (APPROX.)

6 400

OHMS

INTERELECTRODE CAPACITANCES (MEASURED WITH NO SHIELD

AND WITH HEATER TIED TO CATHODE OF UNIT UNDER TEST.

EACH SECTION TESTED SEPARATELY.)

GRID TO PLATE

1.3

 μfd

GRID TO CATHODE

2.25

 μfd

PLATE TO CATHODE

1.0

 μfd

HEATER TO CATHODE

2.4

 μfd

INTERELECTRODE CAPACITIES BETWEEN TRIODE SECTIONS

PLATE TO PLATE

0.1

 μfd

NOISE AND MICROPHONICS (USING WESTERN ELECTRIC 2B NOISE
 MEASURING TEST SET WITH WEIGHTING FILTER (#F1A)

8

db

CONTINUED ON FOLLOWING PAGE

TUNO-80L

CONTINUED FROM PRECEDING PAGE

MECHANICAL DATA

MOUNTING POSITION	ANY	
BULB	T-6 1/2	
BASE	MINIATURE BUTTON PIN	
NET WEIGHT, AVERAGE	0.3	OUNCES
MAXIMUM VIBRATION RATING ($D=0.08"$ @ 25 CPS)	2.5	G

RATINGS
ABSOLUTE VALUES

	MINIMUM	MAXIMUM	
HEATER VOLTAGE (20VOLTS NOMINAL)	19	21	VOLTS
(40VOLTS NOMINAL)	38	42	VOLTS
PLATE VOLTAGE DC	---	330	VOLTS
GRID VOLTAGE DC	-55	0	VOLTS
HEATER-CATHODE VOLTAGE	-130	+130	VOLTS
GRID CURRENT PER GRID	---	3.0	MA.
PLATE CURRENT PER PLATE DC	---	18	MA.
POWER DISSIPATION PER PLATE	---	1.6	WATTS
ENVELOPE TEMPERATURE	---	165°	C
ALTITUDE FOR FULL RATINGS	---	60 000	FEET
CIRCUIT VALUES:			
GRID CIRCUIT RESISTANCE PER GRID	---	0.5	MEGOHM

TYPICAL OPERATIONCLASS AB₁ AMPLIFIER

PLATE VOLTAGE	300	VOLTS
CATHODE RESISTOR	800	OHMS
AF GRID TO GRID VOLTAGE (RMS)	14	VOLTS
ZERO-SIGNAL PLATE CURRENT PER SECTION	4.9	MA.
MAXIMUM SIGNAL PLATE CURRENT PER SECTION	6.3	MA.
LOAD IMPEDANCE (PLATE TO PLATE)	27 000	OHMS
TOTAL HARMONIC DISTORTION	10	PERCENT
MAXIMUM SIGNAL POWER OUTPUT	1.0	WATT

