




OUTPUT TRIODE
TRIODE DE SORTIE
ENDTRIODE

Heating : direct by A.C.;
parallel supply
Chauffage : direct par C.A.; $V_f = 4 \text{ V}$
alimentation en parallèle $I_f = 0,95 \text{ A}$
Heizung : direkt durch Wechselstrom;
Parallelspeisung



Capacities
Capacités
Kapazitäten

$C_{ag} < 20 \text{ pF}$

Operating conditions class B
Caractéristiques d'utilisation classe B
Betriebsdaten Klasse B

V_a	=	350	V
V_E	=	-75	V
$R_{aa'}$	=	5	k Ω
V_i	=	0 — 49	V_{eff}
I_a	=	2x35 — 2x70	mA
W_o	=	0 — 20	W
d	=	— 2,1	%

Operating conditions class AB
 Caractéristiques d'utilisation classe AB
 Betriebsdaten Klasse AB

V_a	=	350	V
R_k	=	850	Ω
$R_{aa'}$	=	8	k Ω
V_i	=	0	51
I_a	=	2x43	2x46
W_o	=	0	15,6
d	=	-	2,3
			%

Limiting values
 Caractéristiques limites
 Grenzdaten

V_{a_o}	= max.	600 V
V_a	= max.	350 V
W_a	= max.	15 W
I_k	= max.	90 mA
$V_g (I_g = +0,3 \mu A)$	= max.	-2 V
$R_g (B)$	= max.	0,3 M Ω
$R_g (AB)$	= max.	0,7 M Ω



	4683	
page	sheet	date
1	1	1948.08.25
2	2	1948.08.25
3	FP	1999.06.07