


TUNG-SOL

PENTODE

MINIATURE TYPE



GLASS BULB


COATED UNIPOTENTIAL CATHODE

HEATER

4.2 VOLTS 0.45 AMP.

AC OR DC

ANY MOUNTING POSITION



BOTTOM VIEW

MINIATURE BUTTON
7 PIN BASE

7BK

THE 4AU6 IS A PENTODE AMPLIFIER HAVING A SHARP CUT-OFF CONTROL CHARACTERISTIC USING THE MINIATURE CONSTRUCTION. WITH HIGH TRANSCONDUCTANCE, LOW GRID-PLATE CAPACITANCE, IT IS INTENDED FOR SERVICE AS EITHER AN RF OR AF AMPLIFIER. THERMAL CHARACTERISTICS OF THE HEATER ARE CONTROLLED SUCH THAT HEATER VOLTAGE SURGES DURING THE WARM-UP CYCLE ARE MINIMIZED PROVIDED IT IS USED WITH OTHER TYPES WHICH ARE SIMILARLY CONTROLLED. EXCEPT FOR THE CONTROLLED HEATER WARM-UP TIME AND HEATER RATINGS THE 4AU6 IS IDENTICAL TO THE 6AU6.

DIRECT INTERELECTRODE CAPACITANCES

PENTODE CONNECTION:

GRID TO PLATE: (G_1 TO P) MAX.INPUT: G_1 TO (H+K+ G_2 + G_3 &1S)OUTPUT: P TO (H+K+ G_2 + G_3 &1S)WITH
SHIELD^A

0.003

5.5

5

WITHOUT
SHIELD

0.003

5.5

5

 μf μf μf

TRIODE CONNECTION:

GRID TO PLATE: G_1 TO (P+ G_2 + G_3 &1S)INPUT: G_1 TO (H+K)OUTPUT: (P+ G_2 + G_3 &1S) TO (H+K)

2.6

3.2

8.5

2.6

3.2

1.2

 μf μf μf ^A SHIELD #316 CONNECTED TO PIN #7.

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

	TRIODE CONNECTION ^B	PENTODE CONNECTION	
HEATER VOLTAGE	4.2	4.2	VOLTS
MAXIMUM HEATER-CATHODE VOLTAGE:			
HEATER NEGATIVE WITH RESPECT TO CATHODE	180	180	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	100	100	VOLTS
MAXIMUM PLATE VOLTAGE	250	300	VOLTS
MAXIMUM GRID #2 SUPPLY VOLTAGE	PLATE	300	VOLTS
MAXIMUM GRID #2 VOLTAGE	PLATE	SEE J5-C4	
MAXIMUM GRID #3 VOLTAGE PIN #2 CONNECTED TO:	PLATE	CATHODE	
MAXIMUM PLATE DISSIPATION	3.2	3	WATTS
MAXIMUM GRID #2 DISSIPATION	---	0.65	WATTS
MAXIMUM POSITIVE DC GRID #4 VOLTAGE	0	0	VOLTS
HEATER WARM-UP TIME (APPROX.)*		11.0	SECONDS

^B TRIODE CONNECTION: G_2 AND G_3 CONNECTED TO PLATE.

* HEATER WARM-UP TIME IS DEFINED AS THE TIME REQUIRED FOR THE VOLTAGE ACROSS THE HEATER TO REACH 80% OF ITS RATED VOLTAGE AFTER APPLYING 4 TIMES RATED HEATER VOLTAGE TO A CIRCUIT CONSISTING OF THE TUBE HEATER IN SERIES WITH A RESISTANCE OF VALUE 3 TIMES THE NOMINAL HEATER OPERATING RESISTANCE.

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

CLASS A₁ AMPLIFIER - PENTODE CONNECTION

HEATER VOLTAGE	4.2	4.2	4.2	VOLTS
HEATER CURRENT	0.45	0.45	0.45	AMP.
PLATE VOLTAGE	100	250	250	VOLTS
GRID #2 VOLTAGE	100	125	150	VOLTS
CATHODE BIAS RESISTOR	150	100	68	OHMS
GRID #3 VOLTAGE	PIN #2 CONNECTED TO PIN #7 AT SOCKET			
TRANSCONDUCTANCE	3 900	4 500	5 200	μMHOS
PLATE CURRENT	5	7.6	10.6	MA.
GRID #2 CURRENT	2.1	3	4.3	MA.
PLATE RESISTANCE (APPROX.)	0.5	1.5	1	MEGOHMS
GRID #4 VOLTAGE (APPROX.) FOR $I_b = 10 \mu A$.	-4.2	-5.5	-6.5	VOLTS

CLASS A₁ AMPLIFIER - TRIODE CONNECTION^C

HEATER VOLTAGE	4.2	VOLTS
HEATER CURRENT	0.45	AMP.
PLATE VOLTAGE	250	VOLTS
GRID #2 VOLTAGE	PLATE	
CATHODE RESISTOR	330	OHMS
GRID #3 VOLTAGE	PLATE	
TRANSCONDUCTANCE	4 800	μMHOS
PLATE CURRENT	12.2	MA.
AMPLIFICATION FACTOR	36	

^C TRIODE CONNECTION: GRID #2 AND GRID #3 CONNECTED TO PLATE.

