



50B5

50B5

BEAM POWER AMPLIFIER

MINIATURE TYPE

GENERAL DATA**Electrical:**

Heater, for Unipotential Cathode:

Voltage. 50 ac or dc volts

Current. 0.15 amp.

Direct Interelectrode Capacitances (Approx.):⁰Grid-No.1 to Plate 0.5 μmf Input. 13 μmf Output 6.5 μmf **Mechanical:**

Mounting Position. Any

Maximum Overall Length 2-5/8"

Maximum Seated Length. 2-3/8"

Length from Base Seat
to Bulb Top (excluding tip). 2" $\pm$ 3/32"

Maximum Diameter 3/4"

Bulb T-5-1/2

Base Miniature Button 7-Pin


Basing Designation for BOTTOM VIEW 7BZ

Pin 1-Grid No.1

Pin 2-Cathode,

Grid No.3

Pin 3-Heater



Pin 4-Heater

Pin 5-Plate

Pin 6-Grid No.2

Pin 7-Grid No.1

CLASS A₁ AMPLIFIER**Maximum Ratings, Design-Center Values:**

PLATE VOLTAGE. 117 max. volts

GRID-No.2 (SCREEN) VOLTAGE 117 max. volts

PLATE DISSIPATION. 5.5 max. watts

GRID-No.2 DISSIPATION. 1.25 max. watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode. 90 max. volts

Heater positive with respect to cathode. 90 max. volts

Typical Operation and Characteristics:

Plate Voltage. 110 . . . volts

Grid-No.2 Voltage. 110 . . . volts

Grid-No.1 Voltage. -7.5 . . . volts

Peak A-F Grid-No.1 Voltage 7.5 . . . volts

Zero-Signal Plate Current. 49 . . . ma.

Max.-Signal Plate Current. 50 . . . ma.

⁰With no external shield.

JAN. 2, 1946

RCA VICTOR DIVISION

TENTATIVE DATA

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

50B5



50B5

BEAM POWER AMPLIFIER

Zéro-Signal Grid-No.2 Current (Approx.) . .	4	. . .	ma.
Max.-Signal Grid-No.2 Current (Approx.) . .	8.5	. . .	ma.
Plate Resistance (Approx.)	14000	. .	ohms
Transconductance	7500	. .	μmhos
Load Resistance.	2500	. .	ohms
Total Harmonic Distortion.	9	. . .	%
Max.-Sig. Power Output	1.9	. .	watts

Maximum Circuit Values (for maximum rated conditions):

Grid-No.1-Circuit Res. . .	fixed bias .	0.1	. megohm
	cathode bias .	0.5	. megohm

JAN. 2, 1946

RCA VICTOR DIVISION


TENTATIVE DATA

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY



50B5

AVERAGE PLATE CHARACTERISTICS PENTODE CONNECTION



OCT. 8, 1945


RCA VICTOR DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-6603

50B5



50B5

OPERATION CHARACTERISTICS
PENTODE CONNECTION

OCT. 24, 1945

RCA VICTOR DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-5812