


TUNG-SOL

PENTODE


SUBMINIATURE TYPE
COATED UNIPOTENTIAL CATHODEHEATER
6.3 VOLTS 0.45 AMP.

AC OR DC

ANY MOUNTING POSITION



GLASS BULB

BOTTOM VIEW
SUBMINIATURE BUTTON
8 FLEXIBLE LEADS
8DL

THE 5639 IS A RUGGEDIZED PENTODE IN THE 8 LEAD BUTTON SUBMINIATURE CONSTRUCTION. IT IS DESIGNED FOR USE IN BROAD BAND AMPLIFIER APPLICATIONS SUCH AS IN RADAR AND VIDEO AMPLIFIER SERVICE. CONTROLS ON THE PRODUCT AVERAGE FOR HEATER CURRENT ASSURE THAT THIS CHARACTERISTIC WILL REMAIN WELL CENTERED. SINCE IT MUST BE ABLE TO WITHSTAND SEVERE MECHANICAL TESTS TO MEET TEST SPECIFICATIONS, THE 5639 IS ESPECIALLY SUITED FOR USE IN INDUSTRIAL AND MILITARY AIRBORNE EQUIPMENT WHICH MAY BE SUBJECTED TO SEVERE SHOCK AND VIBRATION.

DIRECT INTERELECTRODE CAPACITANCES

	WITHOUT SHIELD	WITH SHIELD ^A	
MAXIMUM GRID #1 TO PLATE (RATED)	0.18	0.13	μmf
INPUT: (RATED)	9.0	9.0	μmf
MAXIMUM	---	10.0	μmf
MINIMUM	---	8.0	μmf
OUTPUT: (RATED)	4.6	8.0	μmf
MAXIMUM	---	9.0	μmf
MINIMUM	---	7.0	μmf

RATINGS

ABSOLUTE MAXIMUM VALUES

HEATER VOLTAGE	6.3 $\pm$ 5%	VOLTS
MAXIMUM DC PLATE VOLTAGE	165	VOLTS
MAXIMUM DC GRID #1 VOLTAGE	0	VOLTS
MAXIMUM DC GRID #2 VOLTAGE	155	VOLTS
MAXIMUM HEATER-CATHODE VOLTAGE	$\pm$ 200	VOLTS
MAXIMUM GRID #1 RESISTANCE	0.5	MEG
MAXIMUM DC CATHODE CURRENT	40	mA
MAXIMUM PLATE DISSIPATION	3.5	WATTS
MAXIMUM GRID #2 DISSIPATION	1.0	WATT
MAXIMUM BULB TEMPERATURE	+220	$^{\circ}\text{C}$
MAXIMUM ALTITUDE	60 000	FEET
LIFE EXPECTANCY (30 $^{\circ}\text{C}$ AMBIENT TEMPERATURE)	5 000	HOURS

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

HEATER VOLTAGE	6.3	VOLTS
DC PLATE VOLTAGE	150	VOLTS
DC GRID #2 VOLTAGE	100	VOLTS
CATHODE BIAS RESISTOR	100	OHMS
PLATE CURRENT	21	mA
GRID #2 CURRENT	4.0	mA
TRANSCONDUCTANCE	9 000	μ MHOS
PLATE RESISTANCE	50 000	OHMS
GRID #1 VOLTAGE FOR 10mA PLATE CURRENT	-14	VOLTS
NOISE OUTPUT VOLTAGE (MAXIMUM) ^B	200	mV

CHARACTERISTICS RANGE VALUES FOR EQUIPMENT DESIGN

 $R_k = 100 \text{ OHMS}$, $E_f = 6.3\text{V}$, $E_b = 150\text{Vdc}$, $E_{c1} = 0\text{Vdc}$, $E_{c2} = 100\text{Vdc}$, $E_{hk} = 0\text{V}$
EXCEPT AS MODIFIED BELOW

	INITIAL		PROD. MIN.	AVG. MAX.	500 HOUR LIFE TEST		
	INDIVIDUAL MIN.	MAX.			INDIVIDUAL MIN.	MAX.	
HEATER CURRENT	420	480	432	468	414	492	mA
HEATER-CATHODE LEAKAGE ($E_{hk} = \pm 100\text{Vdc}$)	---	15	---	---	---	60	μ Adc
GRID #1 CURRENT ($R_{g1} = 1.0 \text{ MEG.}$)	0	-1.0	---	---	0	-2.0	μ Adc
PLATE CURRENT (1)	14.0	28.0	---	---	---	---	mA
PLATE CURRENT (2) ($E_{c1} = -14.0\text{Vdc}$, $R_k = 0$)	---	75	---	---	---	---	μ Adc
TRANSCONDUCTANCE (1)	7500	10 500	---	---	μ MHOS	20 ^C	PERCENT
Δ AVG. TRANSCONDUCTANCE (1)	---	---	---	---	---	15	PERCENT
INSULATION OF ELECTRODES ^E							
$R(g1-a11)$	100	---	---	---	50	---	MEGOHMS
$R(p-a11)$	100	---	---	---	50	---	MEGOHMS
POWER OUTPUT ^F ($E_{sig} = 2.0\text{Vac}$, $R_p = 9000$)	0.75	---	---	---	---	---	WATT
SCREEN GRID CURRENT	2.0	6.0	---	---	---	---	mA
TRANSCONDUCTANCE (2) ($E_f = 5.7\text{V}$)	---	10	---	---	---	15	PERCENT
GRID EMISSION ^H ($E_f = 7.5\text{V}$, $E_{c1} = 14\text{Vdc}$, $R_{g1} = 1.0 \text{ meg.}$, $R_k = 0$)	0	-2.0	---	---	---	---	μ Adc
PLATE RESISTANCE	0.040	---	---	---	---	---	MEGOHM

SPECIAL REQUIREMENTS

	MIN.	MAX.	
CONTINUITY AND SHORTS ^J	---	---	
AF NOISE ^K ($E_{sig} = 200\text{mVac}$, $E_{c2} = 100\text{Vdc}$, $E_{c1} = -2.5\text{Vdc}$, $R_{g1} = 0.5 \text{ meg.}$, $R_{g2} = 0.01 \text{ meg.}$, $R_p = 2000$, $R_k = 0$, $C_{g2} = 4\mu\text{f}$)	---	17	VU
LOW PRESSURE VOLTAGE BREAKDOWN (PRESSURE = $55 \pm 5\text{mm mercury}$, VOLTAGE = 300Vac)	---	---	
VARIABLE FREQUENCY VIBRATION ^M (NO VOLTAGES: POST SHOCK AND VIBRATIONAL FATIGUE TEST END POINTS APPLY)	---	---	
LOW FREQUENCY VIBRATION ^{NP} ($R_p = 2000$, $C_k = 1000\mu\text{f}$, $G = 15$, $F = 40 \text{ cps}$)	---	100	mVac
SUBMINIATURE LEAD FATIGUE ^Q	4	---	ARCS
SHOCK ^R (HAMMER ANGLE = 30° , $E_{hk} = 100\text{Vdc}$, $R_{g1} = 0.1 \text{ meg.}$)	---	---	
VIBRATIONAL FATIGUE ^S ($G = 2.5$; FIXED FREQUENCY; $F = 25 \text{ min.}$, 60 max.)	---	---	

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

SPECIAL REQUIREMENTS - CONT'D.

	MIN.	MAX.
POST SHOCK AND VIBRATIONAL FATIGUE TEST END POINTS		
LOW FREQUENCY VIBRATION	----	350
HEATER CATHODE LEAKAGE ($E_{hk} = \pm 100Vdc$)	----	± 40
Δ TRANSCONDUCTANCE (1) OF INDIVIDUAL TUBES	----	20
1 HOUR STABILITY LIFE TEST		
($E_{hk} = 200Vdc$, $R_{g1} = 0.5$ meg., $T_A = \text{Room}$)	----	----
STABILITY LIFE TEST END POINTS		
Δ TRANSCONDUCTANCE (1) INDIVIDUAL TUBES	----	10
100 HOUR SURVIVAL RATE LIFE TEST		
STABILITY LIFE TEST CONDITIONS OR EQUIVALENT	----	----
SURVIVAL RATE LIFE TEST END POINTS		
CONTINUITY AND SHORTS		
TRANSCONDUCTANCE (1)	6750	----
HEATER CYCLING LIFE TEST		
($E_f = 7.0V$, 1 min. on, 4 min. off, $E_{hk} = 140Vdc$, $E_{c1} = E_{c2} = E_b = 0$)	----	----
INTERMITTENT LIFE TEST		
STABILITY LIFE TEST CONDITIONS	----	----
($T-BULB = +220^\circ C$ min.)		

NOTES

A WITH SHIELD OF 0.405" INSIDE DIAMETER CONNECTED TO CATHODE.

B ACROSS A PLATE RESISTOR OF 2,000 OHMS WITH APPLIED VIBRATIONAL ACCELERATION OF 15g AT 40 CYCLES PER SECOND.

C CHANGE IN TRANSCONDUCTANCE (1) OF INDIVIDUAL TUBES.

E SEE MIL-E-1C 4.8.2

F SEE MIL-E-1C 4.10.16.1

G TRANSCONDUCTANCE (2) IS THE PERCENT CHANGE IN TRANSCONDUCTANCE (1) OF AN INDIVIDUAL TUBE TYPE RESULTING FROM THE CHANGE IN E_f .

H PRIOR TO THIS TEST TUBES SHALL BE PREHEATED 5 MINUTES AT CONDITIONS INDICATED. TEST WITHIN 3 SECONDS AFTER PREHEATING. THREE MINUTE TEST IS NOT PERMITTED. GRID EMISSION SHALL BE THE LAST TEST PERFORMED ON THE SAMPLE SELECTED FOR THE GRID EMISSION TEST. CONDITIONS FOR TEST ARE AS FOLLOWS: $E_f = 7.5V$, $E_{c1} = 0Vdc$, $E_{c2} = 100Vdc$, $E_{c3} = 0Vdc$, $E_b = 150Vdc$, $R_{k1} = 100$ OHMS, $R_{g1} = 0.5$ MEG.

J SEE MIL-E-1C 4.7.5

K SEE MIL-E-1C 4.10.3.2

L THERE SHALL BE NO EVIDENCE OF ARCING OR CORONA BETWEEN ANODE PINS AND ADJACENT PINS WITH NO OTHER VOLTAGE APPLIED.

M SEE MIL-E-1C 4.9.20.3

N SEE MIL-E-1C 4.9.19.1

P FOR VIBRATION TESTS, THE IMPEDANCE OF THE PLATE VOLTAGE SUPPLY (AND SCREEN VOLTAGE SUPPLY IF ONE IS INDICATED) SHALL NOT EXCEED THAT OF A 40 μ f CAPACITOR AT 10 CPS.

Q SEE MIL-E-1C 4.9.5.3

R SEE MIL-E-1C 4.9.20.5

S SEE MIL-E-1C 4.9.20.6

5639
PREMIUM TUBE

