


TUNG-SOL

DOUBLE TRIODE

MINIATURE TYPE



GLASS BULB
SMALL BUTTON
9 PIN BASE E9-1
OUTLINE DRAWING
JEDEC 6-1


COATED UNIPOTENTIAL CATHODE

HEATER

6.3 VOLTS 350 MA.

AC OR DC

ANY MOUNTING POSITION



THE 5670 IS A HIGH-FREQUENCY DOUBLE TRIODE USING THE 9 PIN MINIATURE CONSTRUCTION. IT IS DESIGNED FOR RELIABLE LIFE UNDER CONDITIONS OF INTERMITTENT OPERATION.

DIRECT INTERELECTRODE CAPACITANCES

WITH NO EXTERNAL SHIELD

PLATE TO GRID (EACH SECTION) ^A	→	1.1	pf
PLATE TO CATHODE (EACH SECTION) ^A		1.0	pf
GRID TO CATHODE (EACH SECTION) ^A		2.2	pf
PLATE TO PLATE (NOMINAL)		0.05	pf
PLATE TO PLATE (MAXIMUM)		0.10	pf

^A INTERNAL SHIELD AND HEATER CONNECTED TO CATHODE.

RATINGS

EACH TRIODE SECTION - DESIGN CENTER VALUES

MAXIMUM HEATER CATHODE VOLTAGE	90	VOLTS
MAXIMUM PLATE VOLTAGE	300	VOLTS
MAXIMUM PLATE DISSIPATION	1.5	WATTS
MAXIMUM DC CATHODE CURRENT	16.5 *	MA.
BULB TEMPERATURE AT HOTTEST POINT (ABSOLUTE MAXIMUM)	165 *	°C

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

CLASS A₁ AMPLIFIER

PLATE VOLTAGE	150	VOLTS
CATHODE RESISTOR (EACH SECTION)	240	OHMS
PLATE CURRENT (EACH SECTION)	8.2	MA.
TRANSCONDUCTANCE (EACH SECTION)	5 500	μMHOS
AMPLIFICATION FACTOR	35	
GRID VOLTAGE (APPROX.) FOR $I_b = 10 \mu A$.	→ -8	VOLTS

CLASS AB₁ AMPLIFIER

PLATE VOLTAGE	300	VOLTS
CATHODE RESISTOR	800	OHMS
AF GRID TO GRID VOLTAGE (RMS)	14	VOLTS
ZERO-SIGNAL PLATE CURRENT (EACH SECTION)	4.9	MA.
MAXIMUM SIGNAL PLATE CURRENT (EACH SECTION)	6.3	MA.
LOAD IMPEDANCE (PLATE-TO-PLATE)	27 000	OHMS
TOTAL HARMONIC DISTORTION	10	PERCENT
MAXIMUM SIGNAL POWER OUTPUT	1.0	WATT

SPECIAL TESTS AND RATINGS *

HEATER-CYCLING RATINGS		
CYCLES OF INTERMITTENT OPERATION, MINIMUM $E_f = 7.5$ VOLTS CYCLED FOR ONE MINUTE ON AND ONE MINUTE OFF. $E_b = E_c = 0$ VOLTS. $E_{hk} = 435$ VOLTS WITH HEATER POSITIVE WITH RESPECT TO CATHODE.	2 000	CYCLES
SHOCK RATING		
IMPACT ACCELERATION IN ANY DIRECTION FORCES AS APPLIED BY THE NAVY-TYPE, HIGH IMPACT (FLYWEIGHT) SHOCK MACHINE FOR ELECTRONIC DEVICES OR ITS EQUIVALENT.	600	G
FATIGUE RATINGS		
VIBRATIONAL ACCELERATION IN ANY DIRECTION VIBRATIONAL FORCES FOR A PERIOD OF AT LEAST 100 HOURS AT A FREQUENCY OF 25 CYCLES PER SECOND	2.5	G

→ INDICATES A CHANGE.

* INDICATES AN ADDITION.

