



5726

TWIN DIODE

MINIATURE TYPE

5726
PREMIUM TYPE

Intended for applications where dependable performance under shock and vibration is paramount.

The 5726 is a "premium" version of the 6AL5W.

GENERAL DATA**Electrical:**

Heater, for Unipotential Cathodes:

Voltage	6.3 ± 10%	ac or dc volts
Current	0.3	amp
Resonant Frequency (Each unit, approx.) . .	700	Mc
Direct Interelectrode Capacitances (With external shield JETEC No.316):		

Unit No.1:

Plate to Cathode + External Shield, Heater, and Internal Shield	3.2	μμf
Cathode to Plate + External Shield, Heater, and Internal Shield	3.9	μμf

Unit No.2:

Plate to Cathode + External Shield, Heater, and Internal Shield	3.2	μμf
Cathode to Plate + External Shield, Heater, and Internal Shield	3.9	μμf

Plate of Unit No.1 to Plate of Unit No.2*	0.026 max.	μμf
---	------------	-----

Mechanical:

Mounting Position	Any
Maximum Overall Length	1-3/4"
Maximum Seated Length	1-1/2"
Length, Base Seat to Bulb Top (Excluding tip)	1-1/8" ± 3/32"
Maximum Diameter	3/4"
Bulb	T-5-1/2
Base	Small-Button Miniature 7-Pin (JETEC No.E7-1)


BOTTOM VIEW

Pin 1 - Cathode of
Diode Unit
No.1

Pin 2 - Plate of
Diode Unit
No.2

Pin 3 - Heater

Pin 4 - Heater



Pin 5 - Cathode of
Diode Unit
No.2

Pin 6 - Internal
Shield

Pin 7 - Plate of
Diode Unit
No.1

HALF-WAVE RECTIFIER**Maximum Ratings, Absolute Values:**

PEAK INVERSE PLATE VOLTAGE	360 max.	volts
PEAK PLATE CURRENT PER PLATE	60 max.	ma

* With external and internal shield connected to ground.

SEPT. 1, 1952

TUBE DEPARTMENT

TENTATIVE DATA 1

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY



TWIN DIODE

HOT-SWITCHING TRANSIENT PLATE CURRENT

For duration of 0.2 second maximum . . . 350 max. ma

DC OUTPUT CURRENT PER PLATE 10 max. ma

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode 360 max. volts

Heater positive with respect to cathode 360 max. volts

Typical Operation:

The two units may be used separately or in parallel

AC Plate-Supply Voltage

Per Plate (RMS) 117 volts

Minimum Total Effective Plate-Supply

Impedance Per Plate 300 ohms

DC Output Current Per Plate 9 ma

Shock and Vibration Tests:

These tests are made as indicated in the JAN Specifications: JAN 1-A for Electron Tubes, May 1946 under the section as follows:

Section F6b (9e) Shock Test:

Instantaneous Impact Acceleration . . 700 max. g

Section F6b (9f) Vibration Test:

Vibrational Acceleration 2.5 max. g

Heater Cycling Life Test:

This test is made as indicated in the JAN Specifications JAN 1-A for Electron Tubes for type 5726/6AL5W.

Cycles of Intermittent Operation:

At a heater voltage of 7.5 volts . . . 2000 min. cycles

CHARACTERISTICS RANGE VALUES FOR EQUIPMENT DESIGN

	Note	Min.	Max.	
Heater Current	1	0.275	0.325	amp
Direct Interelectrode Capacitances (With external shield JETEC No.316):				
Unit No.1:				
Plate to Cathode+ External Shield, Heater, and Internal Shield	-	2.4	4.0	$\mu\mu\text{f}$
Cathode to Plate+ External Shield, Heater, and Internal Shield	-	2.8	4.4	$\mu\mu\text{f}$
Unit No.2:				
Plate to Cathode+ External Shield, Heater, and Internal Shield	-	2.4	4.0	$\mu\mu\text{f}$
Cathode to Plate+ External Shield, Heater, and Internal Shield	-	2.8	4.4	$\mu\mu\text{f}$




5726

5726

TWIN DIODE

	Note	Min.	Max.	
Plate of Unit No.1 to Plate of Unit No.2	2	-	0.026	$\mu\mu\text{f}$
Plate Current (Per Plate) . . .	1,3	40	-	ma

Note 1: With 6.3 volts ac on heater.
Note 2: With external and internal shield connected to ground.
Note 3: With dc plate voltage=10 volts. Each unit tested separately with electrodes of opposite unit grounded.




5726



5726

AVERAGE CHARACTERISTICS
HALF-WAVE RECTIFICATION-SINGLE DIODE

$E_f = 6.3$ VOLTS



JUNE 7, 1944

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-6561