

Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

For Audio-Amplifier Applications Critical
as to Microphonism, Leakage Noise, and Hum

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	6.3 ± 10%	volts
Current at 6.3 volts.	0.15	amp

Direct Interelectrode Capacitances:^a

Pentode Connection:

Grid No.1 to plate.	0.11 max.	μf
Grid No.1 to cathode, grid No.3, grid No.2, heater, and pins 2 and 6.	2.7	μf
Plate to cathode, grid No.3, grid No.2, heater, and pins 2 and 6.	2.4	μf

Triode Connection:^b

Grid No.1 to plate.	1.4	μf
Grid No.1 to cathode.	1.4	μf
Plate to cathode.	0.85	μf

Characteristics, Class A₁ Amplifier:

	Triode Connection ^b		Pentode Connection	
Plate Voltage	100	250	250	volts
Grid No.3	-	-	Connected to cathode at socket	
Grid-No.2 Voltage	-	-	100	volts
Grid-No.1 Voltage	-3	-8	-3	volts
Amplification Factor.	21	21	-	
Plate Resistance (Approx.)	0.017	0.0137	2	megohms
Transconductance.	1240	1530	1000	μmhos
Plate Current	2.2	5.5	1.8	ma
Grid-No.2 Current	-	-	0.4	ma
Grid-No.1 Voltage (Approx.) for plate . . .				
μa = 10	-	-	-8	volts

Mechanical:

Operating Position.	Any
Maximum Overall Length.	2-3/16"
Maximum Seated Length	1-15/16"
Length, Base Seat to Bulb Top (Excluding tip)	1-9/16" ± 3/32"
Diameter.	0.750" to 0.875"
Dimensional Outline	See General Section
Bulb.	T6-1/2
Base.	Small-Button Noval 9-Pin (JEDEC No.E9-1)

← Indicates a change.



Basing Designation for BOTTOM VIEW. 9AD

Pin 1—Grid No.1
Pin 2—No Con-
nection
Pin 3—Cathode
Pin 4—Heater
Pin 5—Heater



Pin 6—No Con-
nection
Pin 7—Grid No.2
Pin 8—Plate
Pin 9—Grid No.3

AMPLIFIER — Class A₁

→ **Maximum Ratings, Design-Maximum Values:**

	Triode Connection ^b	Pentode Connection	
PLATE VOLTAGE.	275 max.	330 max.	volts
GRID No.3 (SUPPRESSOR GRID).	—	Connect to cathode at socket	

GRID-No.2 (SCREEN-GRID)

SUPPLY VOLTAGE.	—	330 max.	volts
GRID-No.2 VOLTAGE.	—	See Grid-No.2 Input	

Rating Chart at front of Receiving Tube Section

GRID-No.1 (CONTROL-GRID)

VOLTAGE:

Negative-bias value.	55 max.	55 max.	volts
Positive-bias value.	0 max.	0 max.	volts

GRID-No.2 INPUT:

For grid-No.2 voltages up to 165 volts.	—	0.25 max.	watt
--	---	-----------	------

For grid-No.2 voltages
between 165 and
330 volts.

— See Grid-No.2 Input

Rating Chart at front of Receiving Tube Section

PLATE DISSIPATION.	1.7 max.	1.25 max.	watts
----------------------------	----------	-----------	-------

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode.	100 max.	100 max.	volts
Heater positive with respect to cathode.	100 max.	100 max.	volts

Typical Operation as Resistance-Coupled Amplifier:

See *RESISTANCE-COUPLED-AMPLIFIER CHARTS No.26 & No.27*
at front of this Section

Maximum Circuit Values:

	Triode Connection ^b	Pentode Connection	
Grid-No.1—Circuit Resistance	2.2 max.	2.2 max.	megohms

^a Without external shield.

^b Grid No.3 and grid No.2 connected to plate.

→ Indicates a change.



OPERATING CONSIDERATIONS




It is recommended that pins 2 and 6 be grounded in all applications. Grounding of these pins will effectively shield grid No. 1 and plate from heater and help to reduce hum level when an ac heater supply is used.

← Indicates a change.



AVERAGE CHARACTERISTICS


Pentode Connection




92CM-7439RI

AVERAGE CHARACTERISTICS

Pentode Connection



92CS-11053




92CS-11052



AVERAGE PLATE CHARACTERISTICS

Triode Connection



92CM-7446

