



5890

5890

REMOTE-CUTOFF BEAM PENTODE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage.	6.3	ac or dc	volts
Current.	0.6		amp

Mu-Factor, Grid No.2 to

Grid No.1 5

Direct Interelectrode Capacitances:

Grid No.1 to Plate	0.018	μf
Input.	7.5	μf
Output	1.6	μf

Mechanical:

Mounting Position. Any

Overall Length 6-1/2" $\pm$ 1/4"Seated Length. 6" $\pm$ 1/4"

Maximum Diameter 1-1/2"

Cap. Small

Base Small-Shell Duodecal 7-Pin

Basing Designation for BOTTOM VIEW 12J


Pin 1 - Heater

Pin 2 - Grid No.1

Pin 6 - Grid No.3

Pin 7 - Internal Con.-

Do Not Use



Pin 10 - Grid No.2

Pin 11 - Cathode

Pin 12 - Heater

Cap - Plate

Bulb Temperature 220 max. °C

VOLTAGE-CONTROL SERVICE

Maximum CCS* Ratings, Absolute Values:

DC PLATE VOLTAGE 30000 max. volts

DC GRID-No.3 VOLTAGE 6600 max. volts

DC GRID-No.2 VOLTAGE 450 max. volts

DC GRID-No.1 VOLTAGE:

Negative bias value. -200 max. volts

Positive bias value. 0 max. volts

Positive peak value. 2 max. volts

MAX.-SIGNAL DC PLATE VOLTAGE 500 max. volts

MAX.-SIGNAL GRID-No.3 INPUT. 1 max. watt

MAX.-SIGNAL GRID-No.2 INPUT. 0.1 max. watt

PLATE DISSIPATION. 10 max. watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode:

During equipment warm-up period

not exceeding 15 seconds 450 max. volts

After equipment warm-up period 165 max. volts

Heater positive with respect to cathode. 165 max. volts

* : See next page.



REMOTE-CUTOFF BEAM PENTODE

Typical Operation as Shunt Voltage-

Regulator Tube in Accompanying Circuit


DC Plate Voltage.	20000	30000	volts
DC Grid-No.3 Voltage.	5500	5500	volts
DC Grid-No.2 Voltage*.	200	200	volts
DC Grid-No.1 Voltage**.	-60	-60	volts
Peak Grid-No.1 Voltage.	45	20	volts
Zero-Sig. DC Plate Cur.	0	0	μ amp
Max.-Sig. DC Plate Cur.	500	60	μ amp
Zero-Sig. DC Grid-No.3 Cur.	0	0	μ amp
Max.-Sig. DC Grid-No.3 Cur.	0	0	μ amp
Zero-Sig. DC Grid-No.2 Cur.	0	0	μ amp
Max.-Sig. DC Grid-No.2 Cur.	0	0	μ amp
Grid-No.1 Bias (Approx.) for plate current of 10 μ amp.			
	-52	-52	volts
Grid-No.1—Plate Transconductance	11	3	μ hos

• Continuous commercial service.

* Subject to variation of $\pm 40\%$ if grid-No.1 voltage is desired at indicated value.

** Subject to variation of $\pm 40\%$ if grid-No.2 voltage is desired at indicated value.

Shunt Voltage-Regulator Circuit



NOTE: THE CONTROL VOLTAGE MAY BE TAKEN FROM THE LOAD CIRCUIT OR FROM A CIRCUIT SUPPLYING SIGNAL TO THE LOAD CIRCUIT, DEPENDING ON THE TYPE OF LOAD INVOLVED.

OPERATING NOTES

Operation of the 5890 with a plate voltage above approximately 16000 volts results in the production of soft x-rays which can constitute a health hazard on prolonged exposure unless the tube is adequately shielded. Relatively simple shielding should prove adequate, but the need for this precaution should be considered in equipment design.


Devices and arrangements shown or described herein may use patents of RCA or others. Information contained herein is furnished without responsibility by RCA for its use and without prejudice to RCA's patent rights.



5890

5890

REMOTE-CUTOFF BEAM PENTODE




5890



5890

AVERAGE CHARACTERISTIC



FEB. 9, 1950

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-7445