



5964

5964

MEDIUM-MU TWIN TRIODEFOR "ON-OFF" CONTROL APPLICATIONS INVOLVING
LONG PERIODS OF OPERATION UNDER CUTOFF CONDITIONS**GENERAL DATA****Electrical:**

Heater, for Unipotential Cathode:

Voltage. 6.3 $\pm$ 10% ac or dc volts

Current. 0.45 amp

Microphonism , Not Tested

Direct Interelectrode Capacitances (Approx.):^o

Each Unit:

Grid to Plate. 1.3 μ fGrid to Cathode and Heater 2.1 μ fPlate to Cathode and Heater. 0.4 μ f

Grid of Unit No.1 to

Grid of Unit No.2 0.4 max. μ f^o With no external shielding.**Characteristics, Class A Amplifier (Each Unit, with
both units operating):**

Plate Voltage. 100 volts

Cathode-Bias Resistor[•] 50 ohms

Amplification Factor 39

Plate Resistance 6500 ohms

Transconductance 6000 μ hos

Plate Current. 9.5 ma

Mechanical:

Mounting Position. Any

Maximum Overall Length 2-1/8"

Maximum Seated Length. 1-7/8"

Length, Base Seat to Bulb Top (Excluding tip). 1-1/2" $\pm$ 3/32"

Maximum Diameter 3/4"

Bulb T-5-1/2


Base Small-Button Miniature 7-Pin

Basing Designation for BOTTOM VIEW 7BF

Pin 1-Plate of
Triode No.2Pin 2-Plate of
Triode No.1

Pin 3-Heater

Pin 4-Heater

Pin 5-Grid of
Triode No.1Pin 6-Grid of
Triode No.2

Pin 7-Cathode

**FREQUENCY DIVIDER IN COMPUTER SERVICE
& "ON-OFF" CONTROL SERVICE**

Values are for each unit

Maximum Ratings, Absolute Values:

PLATE VOLTAGE. 250 max. volts

[•] Common to both units.

SEPT. 1, 1950

TUBE DEPARTMENT

TENTATIVE DATA

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY



MEDIUM-MU TWIN TRIODE

GRID VOLTAGE:

Negative bias value.	100 max.	volts
Positive bias value.	0 max.	volts
Peak negative value.	200 max.	volts
PLATE DISSIPATION.	1.5 max.	watts
GRID INPUT	0.1 max.	watt
DC CATHODE CURRENT*.	15 max.	ma
PEAK CATHODE CURRENT*.	75 max.	ma

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode.	90 max.	volts
Heater positive with respect to cathode.	90 max.	volts
BULB TEMPERATURE (At hottest point on bulb surface)	150 max.	°C

Typical Operation as Frequency Halfer (Each Unit):

	Cutoff Condition	Zero-Bias Condition	
Plate-Supply Voltage	150	150	volts
Plate-Circuit Resistance	20000	20000	ohms
Grid-Supply Voltage.	-10	0	volts
Grid-Circuit Resistance.	47000	47000	ohms
Plate Current.	0	5	ma

Maximum Circuit Values:

Grid-Circuit Resistance:

For fixed-bias operation	0.5 max.	megohm
For cathode-bias operation	1.0 max.	megohm

RANGE VALUES FOR EQUIPMENT DESIGN

Cutoff Condition	Note	Min.	Max.	
Plate Current (Each Unit). 1	-	-	0.2	ma
Difference in Plate Current Between Units. . -	-	-	0.2	ma
Zero-Bias Condition				
Plate Current (Each Unit). 2	-	4.3	5.7	ma
Difference in Plate Current Between Units. . -	-	-	1.4	ma

Note 1: For conditions with 6.3 volts on heater, plate-supply volts = 150, plate-circuit resistance (ohms) = 20000, grid-supply volts = -10, and grid-circuit resistance (ohms) = 47000.

Note 2: Conditions are same as for Note 1 except that grid-supply volts = 0.

* With both units operating, the dc cathode current should not exceed 30 milliamperes, and the peak cathode current should not exceed 150 milliamperes.




5964

5964

AVERAGE OPERATION CHARACTERISTICS
FOR EACH UNIT $E_f = 6.3$ VOLTS

GRID-CIRCUIT RESISTANCE (OHMS) = 47000



MAY 31, 1950

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-7495

