


TUNG-SOL

TRIODE PENTODE

MINIATURE TYPE



GLASS BULB


COATED UNIPOTENTIAL CATHODE

HEATER

4.7 VOLTS 0.6 AMP.

AC OR DC

ANY MOUNTING POSITION



BOTTOM VIEW

MINIATURE BUTTON
9 PIN BASE

9EC

THE 588 IS A MEDIUM-MU TRIODE AND A SHARP CUTOFF PENTODE USING THE 9 PIN MINIATURE CONSTRUCTION. IT IS DESIGNED FOR USE AS A VHF OSCILLATOR AND MIXER IN 600 MA. SERIES HEATER OPERATED TELEVISION RECEIVERS. THERMAL CHARACTERISTICS OF THE HEATER ARE CONTROLLED SUCH THAT HEATER VOLTAGE SURGES DURING THE WARM-UP CYCLE ARE MINIMIZED PROVIDED IT IS USED WITH OTHER TYPES WHICH ARE SIMILARLY CONTROLLED.

DIRECT INTERELECTRODE CAPACITANCES - APPROX.

WITH NO EXTERNAL SHIELD

TRIODE GRID TO TRIODE PLATE	1.7	$\mu\mu f$
PENTODE GRID #1 TO PENTODE PLATE (MAX.)	0.032 ←	$\mu\mu f$
TRIODE GRID TO (TRIODE CATHODE, PENTODE GRID #3, I.S., HEATER)	1.9	$\mu\mu f$
TRIODE PLATE TO (TRIODE CATHODE, PENTODE GRID #3, I.S., HEATER)	1.4	$\mu\mu f$
PENTODE GRID #1 TO (PENTODE CATHODE, GRID #2, HEATER)	6.0	$\mu\mu f$
PENTODE PLATE TO (PENTODE CATHODE, GRID #2, GRID #3, TRIODE CATHODE, I.S., HEATER)	2.6	$\mu\mu f$
PENTODE PLATE TO (PENTODE CATHODE, GRID #2, HEATER)	0.15	$\mu\mu f$
TRIODE GRID TO PENTODE PLATE	0.0078	$\mu\mu f$
PENTODE GRID #1 TO TRIODE PLATE	0.0033	$\mu\mu f$
TRIODE PLATE TO PENTODE PLATE	0.060	$\mu\mu f$

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

	TRIODE	PENTODE	VOLTS
HEATER VOLTAGE	4.7		
MAXIMUM HEATER-CATHODE VOLTAGE:			
HEATER POSITIVE WITH RESPECT TO CATHODE			
TOTAL DC AND PEAK	200		VOLTS
DC	100		VOLTS
HEATER NEGATIVE WITH RESPECT TO CATHODE			
TOTAL DC AND PEAK	200		VOLTS
MAXIMUM PLATE VOLTAGE	300	300	VOLTS
MAXIMUM GRID #2 SUPPLY VOLTAGE	---	300	VOLTS
MAXIMUM GRID #2 VOLTAGE		SEE RATING CHART	
MAXIMUM POSITIVE GRID #1 VOLTAGE	0	0	VOLTS
MAXIMUM PLATE DISSIPATION	2.5	2.0	WATTS
MAXIMUM GRID #2 DISSIPATION	---	0.5	WATT
MAXIMUM GRID #1 CIRCUIT RESISTANCE ^A :			
FIXED BIAS	0.5	0.25	MEGOHM
SELF BIAS	1.0	1.0	MEGOHM
HEATER WARM-UP TIME (APPROX.) [*]		11.0	SECONDS

^A IF EITHER UNIT IS OPERATING AT MAXIMUM RATED CONDITIONS, GRID #1 CIRCUIT RESISTANCES FOR BOTH UNITS SHALL NOT EXCEED THE STATED VALUES.

^{*} HEATER WARM-UP TIME IS DEFINED AS THE TIME REQUIRED FOR THE VOLTAGE ACROSS THE HEATER TO REACH 80% OF ITS RATED VOLTAGE AFTER APPLYING 4 TIMES RATED HEATER VOLTAGE TO A CIRCUIT CONSISTING OF THE TUBE HEATER IN SERIES WITH A RESISTANCE OF VALUE 3 TIMES THE NOMINAL HEATER OPERATING RESISTANCE.

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

CLASS A₁ AMPLIFIER

	TRIODE	PENTODE ^B	
HEATER VOLTAGE	4.7		VOLTS
HEATER CURRENT	0.6		AMP.
PLATE VOLTAGE	200	200	VOLTS
GRID #2 VOLTAGE	---	150	VOLTS
GRID #1 VOLTAGE	-6	0	VOLTS
CATHODE BIAS RESISTOR	---	180	OHMS
PLATE CURRENT	13	9.5	MA.
GRID #2 CURRENT	---	2.8	MA.
AMPLIFICATION FACTOR	19	---	
TRANSCONDUCTANCE	3 300	6 200	μMHOS
PLATE RESISTANCE (APPROX.)	5 750	300 000	OHMS
GRID #1 VOLTAGE (APPROX.) FOR $I_b = 10 \mu\text{AMP.}$	-19	-8	VOLTS

^B WHEN READING CHARACTERISTICS OF THE PENTODE SECTION, ALL TRIODE ELEMENTS SHALL BE AT GROUND POTENTIAL. THUS, BECAUSE OF INTERNAL CONNECTIONS TO PIN #1, THE PENTODE SUPPRESSOR WILL ALSO BE AT GROUND.

