

CHARACTERISTICS

GENERAL DATA

Focusing Method		Magnetic
Deflecting Method		Magnetic
Deflection Angles (Approx.)		53 Degrees
Types*	Fluorescence	Persistence
5DKP4	White	Medium Short
5DKP11	Blue	Medium Short
5DKP15	Green	Visible: Short
		U.V.: Very Short
5DKP16	Bluish Purple (U.V.)	Very Short
5DKP24	Green	Short

*In addition to the types shown, the 5DKP- can be supplied with several other screen phosphors. All screens are aluminized.

ELECTRICAL DATA

Heater Voltage		6.3 Volts
Heater Current		0.6 ± 10 % Ampere
Direct Interelectrode Capacitances (Approx.)		
Cathode to All Other Electrodes		5 μf
Grid No. 1 to All Other Electrodes		8 μf

MECHANICAL DATA

Minimum Useful Screen Diameter		4 ¹ / ₄ Inches
Nominal Overall Length		11 ¹ / ₈ Inches
Bulb Contact (Recessed Small Ball Cap)		J1-22
Base (Medium Shell Octal 5-pin or 8-pin)		B8-11, B8-65 or B5-80
Basing		5AN
Bulb		J39 ¹ / ₂ L

RATINGS

MAXIMUM RATINGS (Absolute Maximum Values)

Anode Voltage ¹		8800 Volts	dc
Grid No. 2 Voltage		770 Volts	dc
Grid No. 1 Voltage			
Negative Bias Value		180 Volts	dc
Positive Bias Value		0 Volts	dc
Positive Peak Value		2 Volts	
Peak Heater-Cathode Voltage			
Heater Negative with Respect to Cathode		180 Volts	
Heater Positive with Respect to Cathode		180 Volts	

TYPICAL OPERATING CONDITIONS



Anode Voltage ²		8000 Volts	dc
Grid No. 2 Voltage		250 Volts	dc
Grid No. 1 Voltage ³		-30 to -75 Volts	dc
Focusing Coil Current ⁴		136 ± 15 % Ma	dc
Spot Position (Undelected) ⁵		9 mm	
Line Width A ⁶		.16 mm	Max.

CIRCUIT VALUES

Grid No. 1 Circuit Resistance		1.5 Megohms Max.
-------------------------------	-------	------------------

QUICK REFERENCE DATA

5DKP4 —Monitor Tube
 5DKP11 —Photo Recorder
 5DKP15 }
 5DKP16 } —Flying Spot Scanners
 5DKP24 }
 5" Round Glass Type
 Aluminized Screen
 Magnetic Deflection
 Magnetic Focus
 High Resolution



SYLVANIA ELECTRONIC TUBES

A Division of
Sylvania Electric Products Inc.

PICTURE TUBE OPERATIONS
SENECA FALLS, NEW YORK

Prepared and Released By The
TECHNICAL PUBLICATIONS SECTION
EMPORIUM, PENNSYLVANIA

MARCH, 1962

PAGE 1 OF 2

File Under

SPECIAL AND GENERAL
PURPOSE CATHODE RAY TUBES

NOTES:

1. The product of the anode voltage and the average anode current should be limited to 6 watts.
2. Brilliance and definition decrease with decreasing anode voltage. In general, the anode voltage should not be less than 6000 volts.
3. Visual extinction of undeflected focused spot.
4. For JEDEC focus coil No. 106 or equivalent, with the Grid No. 1 voltage adjusted to produce an accelerator current of 200 μ amps and with distance from reference line to center of air gap equal to $2\frac{3}{4}$ inches.
5. The center of the undeflected unfocused spot will fall within a circle of 9 mm radius centered on the tube face.
6. Measured in accordance with MIL-E-1 specification, at anode current of 200 μ a.

OUTLINE




DIAGRAM NOTES:

1. Reference line is determined by position where JEDEC Gauge No. 124 (a cylinder $1.430'' + .003'' - .000''$ ID and 2'' long) will seat against cone of bulb.
2. The plane through the tube axis and Pin No. 5 may vary from the plane through the tube axis and anode terminal by an angular tolerance (measured about the tube axis) of 10° . Anode terminal is on same side of tube as Pin No. 5.