TUNG-SOL

PENTODE

MINIATURE TYPE



GLASS BULB

UNIPOTENTIAL CATHODE

HEATER

5.6 VOLTS 0.45±6% AMP.

AC OR DC

ANY MOUNTING POSITION



BOTTOM VIEW

SMALL-BUTTON MINIATURE
7 PIN BASE

7CM

THE 5GM6 IS A SEMIREMOTE-CUTOFF PENTODE IN THE 7 PIN MINIATURE CONSTRUCTION. IT IS ESPECIALLY DESIGNED FOR USE IN GAIN-CONTROLLED PICTURE-IF STAGES OF TELEVISION RECEIVERS OPERATING AT INTERMEDIATE FREQUENCIES OF THE ORDER OF 40 MEGACYCLES.

DIRECT INTERELECTRODE CAPACITANCES

WITHOUT EXTERNAL SHIELD

GRID #1 TO PLATE (MAX.)	0.036	μμf
GRID #1 TO CATHODE, INTERNAL SHIELD & G3,G2 & H.	10	μμf
PLATE TO CATHODE, INTERNAL SHIELD & G3, G2 & H.	2.4	μμf

RATINGS

INTERPRETED ACCORDING TO DESIGN MAXIMUM SYSTEM

CLASS A_1 AMPLIFIER

HEATER VOLTAGE	5.6	VOLTS
MAXIMUM PLATE VOLTAGE	330	VOLTS
MAXIMUM GRID #3 (SUPPRESSOR) VOLTAGE	0	VOLTS
MAXIMUM GRID #2 SUPPLY VOLTAGE	330	VOLTS
MAXIMUM GRID #2 (SCREEN-GRID) VOLTAGE (SEE JEDEC INPUT RATING CHART J5-C4-2)		
MAXIMUM GRID #1 (CONTROL-GRID) VOLTAGE:		
POSITIVE BIAS VALUE	0	VOLTS
MAXIMUM PLATE DISSIPATION	3.1	WATTS
MAXIMUM GRID #2 INPUT:		
FOR GRID #2 VOLTAGES UP TO 165 VOLTS	0.65	WATT
FOR GRID #2 VOLTAGES BETWEEN 165 AND 330 VOLTS (SEE JEDEC INPUT RATING CHART J5-C4-2)		
MAXIMUM PEAK HEATER-CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE	200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	200[A]	VOLTS
HEATER WARM-UP TIME (APPROX.)*	11.0	SECONDS

[A] THE DC COMPONENT MUST NOT EXCEED 100 VOLTS.

CONTINUED ON FOLLOWING PAGE

PRINTED IN U.S.A.

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

CLASS A_1 AMPLIFIER

HEATER VOLTAGE	5.6	VOLTS
HEATER CURRENT	0.45±6%	AMP.
PLATE SUPPLY VOLTAGE	125	VOLTS
GRID #3	CONNECTED TO CATHODE AT SOCKET	
GRID #2 SUPPLY VOLTAGE	125	VOLTS
CATHODE RESISTOR	56	OHMS
PLATE RESISTANCE (APPROX.)	0.2	MEGOHMS
TRANSCONDUCTANCE	13 000	μMHOS
PLATE CURRENT	14	MA.
GRID #2 CURRENT	3.4	MA.
GRID #1 VOLTAGE (APPROX.) FOR TRANCONDUCTANCE = 60 μMHOS	-15	VOLTS

DESIGN-MAXIMUM RATINGS ARE LIMITING VALUES OF OPERATING AND ENVIRONMENTAL CONDITIONS APPLICABLE TO A BOGEY ELECTRON DEVICE OF A SPECIFIED TYPE AS DEFINED BY ITS PUBLISHED DATA, AND SHOULD NOT BE EXCEEDED UNDER THE WORST PROBABLE CONDITIONS. THE DEVICE MANUFACTURER CHOOSES THESE VALUES TO PROVIDE ACCEPTABLE SERVICEABILITY OF THE DEVICE, TAKING RESPONSIBILITY FOR THE EFFECTS OF CHANGES IN OPERATING CONDITIONS DUE TO VARIATIONS IN DEVICE CHARACTERISTICS. THE EQUIPMENT MANUFACTURER SHOULD DESIGN SO THAT INITIALLY AND THROUGHOUT LIFE NO DESIGN-MAXIMUM VALUE FOR THE INTENDED SER ICE IS EXCEEDED WITH A BOGEY DEVICE UNDER THE WROST PROBABLE OPERATING CONDITIONS WITH RESPECT TO SUPPLY-VOLTAGE VARIATION, EQUIPMENT COMPONENT VARIATION, EQUIPMENT CONTROL ADJUSTMENT, LOAD VARIATION, SIGNAL VARIATION, AND ENVIRONMENTAL CONDITIONS.

SIMILAR TYPE REFERENCE: *Except for heater ratings and heater warm-up time, the 5GM6 is identical to the 4GM6 and the 6GM6.*

*HEATER WARM-UP TIME IS DEFINED AS THE TIME REQUIRED FOR THE VOLTAGE ACROSS THE HEATER TO REACH 80% OF ITS RATED VOLTAGE AFTER APPLYING 4 TIMES RATED HEATER VOLTAGE TO A CIRCUIT CONSISTING OF THE TUBE HEATER IN SERIES WITH A RESISTANCE OF VALUE 3 TIMES THE NOMINAL HEATER OPERATING RESISTANCE.