

DIAMETER 5" NOMINAL

5TD3**Radar Tube**


MAGNETIC FOCUS. MAGNETIC DEFLECTION

DATA

GENERAL :

Heater : Voltage	6.3	a.c. or d.c. volts
Current	0.6	amp.
Direct Inter-electrode Capacitances (Approx.)		
Modulator to All Other Electrodes	10.5 μ f.	
Anode 1 to All Other Electrodes	6 μ f.	
Cathode to All Other Electrodes	9 μ f.	
Screen :		
Fluorescence	Blue.	
Afterglow	Yellow.	
Persistence of Afterglow	Long.	
Focusing Method	Magnetic.	
Deflection Method	Magnetic.	
Deflection Angle (Approx.)	53°	
Overall Length	280 $\pm$ 6 mm.	
Greatest Diameter of Bulb	125.5 $\pm$ 2 mm.	
Minimum Useful Screen Diameter	108 mm.	
Mounting Position	Any.	
Anode Cap	Recessed Small Ball.	
Base	International Octal.	

- Pin 1—No connection.
 Pin 2—Heater.
 Pin 3—Anode 1.
 Pin 4—No connection.



- Pin 5—Modulator.
 Pin 6—No connection.
 Pin 7—Cathode.
 Pin 8—Heater.
 Cap—Final Anode.

Maximum Ratings :

Final Anode Voltage	800 max. volts.
Anode 1 Voltage	700 max. volts.
Modulator Voltage :	
Negative bias value	125 max. volts.
Positive bias value	0 max. volts.
Peak Heater-Cathode Voltage :	
Heater negative with respect to cathode	125 max. volts.
Heater positive with respect to cathode	125 max. volts.

Typical Operation :

Anode Voltage	4000	7000 volts.
Anode 1 Voltage	250	250 volts.
Modulator Voltage for cut-off	-25 to -70	-25 to -70 volts.
Focusing-Coil current—See Note 3	420	520 A.T.
Spot Position	See Note 4	

Note 3. Focusing Coil, positioned with centre line of air gap approximately 70 mm. from reference line (see Outline Drawing).

Note 4. The centre of the undeflected unfocused spot will fall within a circle having 9 mm. radius concentric with the centre of the tube face.

