




Obsolete Type

For Information Only

TYPE **5Y4G**


(OCTAL BASE)

FULL WAVE RECTIFIER



CHARACTERISTICS

Filament Voltage	...	...	...	...	...	5.0 volts
Filament Current	...	...	...	...	...	2.0 amp.
Peak Inverse Voltage	...	...	...	...	...	1,400 volts max.
Peak Current per Anode	...	...	...	...	...	375 mA max.
R.M.S. Input per Anode	...	...	...	...	...	350 volts max.
Supply Impedance per Anode...	...	...	...	...	...	50 ohms min.
Rectified Current	...	...	...	...	...	125 mA max.
Reservoir Condenser	...	...	...	...	...	32 μ F max.




Replacement Type

TYPE **5Z3**

(U.X. BASE)

FULL WAVE RECTIFIER



CHARACTERISTICS

Filament Voltage	...	...	...	...	...	5.0 volts
Filament Current	...	...	...	...	...	3.0 amp.
Peak Inverse Voltage	...	...	...	...	...	1,550 volts max.
Peak Current per Anode	...	...	...	...	...	675 mA max.
R.M.S. Input per Anode	...	...	...	...	...	450 volts max.
Supply Impedance per Anode...	...	...	...	...	...	75 ohms min.
Rectified Current	...	...	...	...	...	225 mA max.
Reservoir Condenser	...	...	...	...	...	32 μ F max.

For characteristic curves refer to type 5U4G.