



6012

6012

GAS THYRATRON

NEGATIVE-CONTROL TETRODE TYPE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

	Min.	Av.	Max.	
Voltage.	5.7	6.3	6.9	ac or dc volts
Current at 6.3 volts . . .	-	2.6	2.85	amp

Cathode:

Minimum heating time prior to tube conduction.	30	sec
--	----	-----

Maximum outage time without reheating. .	5	sec
--	---	-----

Direct Interelectrode Capacitances

(Approx.):^o

Grid No.1 to anode	0.23	μ f
------------------------------	------	---------

Grid No.1 to cathode, grid No.2, and heater	5.8	μ f
---	-----	---------

Anode to cathode, grid No.2, and heater	3.9	μ f
---	-----	---------

Ionization Time (Approx.):

For conditions: dc anode volts = 100, grid-No.2 volts = 0, grid-No.1 square-pulse volts = +50, and peak anode amperes during conduction = 5.	0.5	μ sec
--	-----	-----------

Deionization Time (Approx.) See Table I

Maximum Critical Grid-No.1 Current:

For conditions: ac anode-supply volts = 460 (rms), and average anode amperes = 0.5.	3	μ amp
---	---	-----------

Anode Voltage Drop (Approx.) 10 volts

Grid-No.1 Control Ratio (Approx.):

For conditions: grid-No.1 resistor (megohms) = 0, grid-No.2 resistor (megohms) = 0, and grid-No.2 volts = 0.	150	
--	-----	--

Grid-No.2 Control Ratio (Approx.):

For conditions: grid-No.1 resistor (megohms) = 0, grid-No.2 resistor (megohms) = 0, and grid-No.1 volts = 0.	650	
--	-----	--

Mechanical:

Mounting Position. Any

Maximum Overall Length 3-7/8" ←

Maximum Seated Length. 3-5/16" ←

Maximum Diameter 1-23/32"

Bulb T-12

Base Large-Wafer Octal 6-Pin ←

with External Barriers and Sleeve (JETEC No.B6-100)

^o Without external shield.

← Indicates a change.



6012


GAS THYRATRON

Basing Designation for BOTTOM VIEW 6C0

Pin 1 - Cathode

Pin 2 - Heater

Pin 3 - Grid No.1



Pin 5 - Anode

Pin 7 - Heater

Pin 8 - Grid No.2

RELAY AND GRID-CONTROLLED RECTIFIER SERVICE

*For anode-supply frequency of 60 cps***Maximum Ratings, Absolute Values:**

PEAK ANODE VOLTAGE:

Forward.	650 max.	volts
Inverse.	1300 max.	volts

GRID-No.2 (SHIELD-GRID) VOLTAGE:

Peak, before tube conduction	-100 max.	volts
Average [#] , during tube conduction	-10 max.	volts

GRID-No.1 (CONTROL-GRID) VOLTAGE:

Peak, before tube conduction	-200 max.	volts
Average [#] , during tube conduction	-10 max.	volts

CATHODE CURRENT:

Peak	5 max.	amp
Average [#]	0.5 max.	amp
Fault, for duration of 0.1 second max.	20 max.	amp

AVERAGE GRID-No.2 CURRENT[#] +0.05 max. ampAVERAGE GRID-No.1 CURRENT[#] +0.05 max. amp

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode.	100 max.	volts
Heater positive with respect to cathode.	25 max.	volts

AMBIENT-TEMPERATURE RANGE. -75 to +90 °C

Maximum Circuit Values:

Grid-No.1-Circuit Resistance 2 max. megohms

[#] Averaged over any interval of 30 seconds maximum.

→ Indicates a change.



6012

6012


GAS THYRATRON

TABLE I

 E_{cc1} = DC Grid-No.1 Supply Voltage (Volts) E_{cc2} = DC Grid-No.2 Supply Voltage (Volts) R_{g1} = Grid-No.1 Resistor (Megohms) R_{g2} = Grid-No.2 Resistor (Ohms)

DC Anode Volts	125		250		R_{g1}	E_{cc1}	R_{g2}^*	E_{cc2}
DC Anode Amperes	0.5	1.0	0.5	1.0				
DEIONIZATION TIME μsec (Approx.)	175	225	250	275	0.001	-13	1000	0
	350	375	450	475	0.1			
	650	700	1100	1200	2			
	100	125	100	125	0.001	-100	1000	0
	125	150	150	175	0.1			
	250	275	275	300	2			

* Series resistor between grid No.2 and cathode.



92CS-7635RI



6012


GAS THYRATRON

OPERATIONAL RANGE OF CRITICAL GRID-N^o1 VOLTAGE

GRID-N^o2 (SHIELD) VOLTS=0
 RANGES SHOWN ARE FOR TWO VALUES
 OF GRID-N^o1 RESISTOR, 0.1 MEG. AND
 2 MEG., AND TAKE INTO ACCOUNT INITIAL
 DIFFERENCES BETWEEN INDIVIDUAL
 TUBES AND SUBSEQUENT DIFFERENCES
 DURING TUBE LIFE. FOR HEATER-
 VOLTAGE RANGE OF 5.7 TO 6.9 VOLTS
 AND FOR AN AMBIENT TEMPERATURE
 RANGE OF FROM -75° TO +90°C.

RANGE FOR
2 MEGOHMS

RANGE FOR
0.1 MEGOHM






6012

6012

AVERAGE CONTROL CHARACTERISTICS





CHARACTERISTIC CURVES

