




PENTODE

DESCRIPTION

The GL-6137 is a remote-cutoff pentode designed for use as a high-gain radio-frequency or intermediate-frequency amplifier. The tube is specially designed to assure dependable life and reliable service under the exacting conditions encountered

in mobile and aircraft applications. Features include a high degree of mechanical strength and a heater-cathode construction designed to withstand many thousand cycles of intermittent operation.

TECHNICAL INFORMATION

GENERAL

Electrical Data

Cathode—Coated Unipotential	
Heater Voltage (A-c or D-c)	6.3 Volts
Heater Current	0.3 Ampere
Direct Interelectrode Capacitance*	
Grid No. 1 to Plate, maximum	0.003 uuf
Input	5.0 uuf
Output	6.5 uuf

Mechanical Data

- Mounting Position—Any
- Envelope—MT-8, Metal Shell
- Base—Small Wafer Octal 8-pin, B8-21



TECHNICAL INFORMATION (CONT'D)

MAXIMUM RATINGS

Electrical—Design Center Values

Plate Voltage.....	300 Volts
Screen Supply Voltage.....	300 Volts
Screen Voltage.....	125 Volts
Positive D-c Grid—No. 1 Voltage.....	0 Volt
Plate Dissipation.....	3.0 Watts
Screen Dissipation.....	0.4 Watt
Heater-cathode Voltage.....	90 Volts
Mechanical	
Peak Impact Acceleration in Any Direction.....	600 G

CHARACTERISTICS AND TYPICAL OPERATION


Class A₁ Amplifier

Plate Voltage.....	100	250 Volts
Suppressor Voltage Δ	0	0 Volt
Screen Voltage.....	100	100 Volts
Grid—No. 1 Voltage.....	-1	-3 Volts
Plate Resistance, approximate.....	0.12	0.8 Megohm
Transconductance.....	2350	2000 Micromhos
Plate Current.....	13	9.2 Milliamperes
Screen Current.....	4.0	2.6 Milliamperes
Grid—No. 1 Voltage, approximate for $G_m = 10$ Micromhos.....	-35	-35 Volts


* Measured with Pin 1 connected to Pin 5.

 Δ Pin 3 connected to Pin 5 at socket.

AVERAGE PLATE CHARACTERISTICS




AVERAGE CHARACTERISTICS



K-69087-72A507

1-9-52


AVERAGE CHARACTERISTICS



K-69087-72A506

1-9-52


AVERAGE CHARACTERISTICS



K-69087-72A509


1-9-52

OUTLINE



N-15119AZ

BASING DIAGRAM



PIN 1: SHELL
PIN 2: HEATER
PIN 3: GRID NO. 3
PIN 4: GRID NO. 1

PIN 5: CATHODE
PIN 6: GRID NO. 2
PIN 7: HEATER
PIN 8: PLATE

1-9-52

Tube Department

GENERAL ELECTRIC

Schenectady, N. Y.