


TUNG-SOL


PENTODE
MINIATURE TYPE

GLASS BULB

6-2

COATED UNIPOTENTIAL CATHODE

HEATER

 $6.3 \pm 10\%$ VOLTS 0.30 AMP.

BOTTOM VIEW

MINIATURE BUTTON
7 PIN BASE

THE 6186/6AG5WA IS A SHARP CUTOFF PENTODE IN THE 7 PIN MINIATURE CONSTRUCTION. IT IS DESIGNED FOR USE AS AN INTERMEDIATE FREQUENCY OR RF AMPLIFIER. THROUGH THE USE OF TWO CATHODE LEADS, ISOLATION OF INPUT AND OUTPUT CIRCUITS IS MADE FEASIBLE

RATINGS
AND NORMAL OPERATION

	MIL-E-1 SYMBOL	TEST CONDI- TIONS	ABS. MAX.	MIL-E-1 UNITS
HEATER VOLTAGE	Ef	6.3	$6.3 \pm 10\%$	v
PLATE VOLTAGE	Eb	250	330	vdc
GRID #1 VOLTAGE	Ec1	0		vdc
GRID #2 VOLTAGE	Ec2	150	250	vdc
CATHODE RESISTANCE	Rk	200		OHMS
GRID #2 DISSIPATION	Pg2		0.55	w
PLATE DISSIPATION	Pp		2.5	w
HEATER-CATHODE VOLTAGE	Ehk		100	v
BUBB TEMPERATURE			+165	°c
ALTITUDE				

NOTE 11

CHARACTERISTICS AND QUALITY CONTROL TESTS

TEST

QUALIFICATION
APPROVAL TESTSAQL
%MIL-E-1
SYMBOL

MAX.

MIL-E-1
UNITS

QUALIFICATION APPROVAL:

CARTON DROP:

(d) PACKAGE GROUP 1;

CARTON SIZE B;

VIBRATION (1):

Rp = 2000

Ep:

100

mVac

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

CHARACTERISTICS AND QUALITY CONTROL TESTS - cont'd.

TEST	AQL %	MIL-E-1 SYMBOL	MIN.	BOG.	MAX.	MIL-E-1 UNITS
ACCEPTANCE TESTS- GROUP A						
FATIGUE:						
NOTE 3	6.5					
SHOCK:						
HAMMER ANGLE=30°						
Ehk=100 Vdc, HEATER						
POSITIVE; Rg1=0.1Meg.	---					
POST SHOCK AND &						
FATIGUE TEST END						
POINTS						
VIBRATION (2):	---	Ep:	---	---	450	mVac
HEATER-CATHODE LEAKAGE:						
HEATER POSITIVE	---	lhk	---	---	30	μAdc
HEATER NEGATIVE	---	lhk:	---	---	30	μAdc
TRANSCONDUCTANCE (1):	---	Sm:	3500	---	---	μMHOS
GRID CURRENT (1):	---	lc1:	0	---	-0.2	μAdc
ACCEPTANCE TESTS- GROUP B						
GLASS STRAIN:	2.5	---	---	---	---	---
ACCEPTANCE TESTS- GROUP C						
CONTINUITY & SHORT:	0.4	---	---	---	---	---
ACCEPTANCE TESTS GROUP D - NOTE 6						
HEATER CURRENT	0.65	lf:	275	300	375	mA
HEATER-CATHODE LEAKAGE:						
Ehk=100 Vdc, HEATER POS.	0.65	lhk:	---	---	10	μAdc
Ehk=100 Vdc, HEATER NEG.					10	μAdc
GRID CURRENT (1):	0.65	lc1:	0	---	-0.1	μAdc
PLATE CURRENT (1):	0.65	lb:	5.2	---	8.8	mAAdc
SCREEN GRID CURRENT:	0.65	lc2:	1.3	---	2.7	mAAdc
TRANSCONDUCTANCE (1):	0.65	Sm:	4000	---	6000	μMHOS
ACCEPTANCE TESTS- GROUP E						
INSULATION OF						
ELECTRODES:						
Ef = 6.3 V						
E(g1-all)=100Vdc, g1 Neg.	2.5	{	Rg1-all: 100	---	---	MEG
E(p-all)=300Vdc, p Neg.			Rp-all: 100	---	---	MEG.
PLATE CURRENT (2):						
Rk=0; Ec1=-4.5 Vdc	2.5	lb:	5	---	---	μAdc
PLATE CURRENT (3):						
Rk=0; Ec1=-10Vdc	2.5	lb:	---	---	100	μAdc
TRANSCONDUCTANCE (2):						
Ef = 5.7 V.	2.5	ΔSm:	---	---	15	PERCENT

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

CHARACTERISTICS AND QUALITY CONTROL TESTS - cont'd.

TEST	AQL %	MIL-E-1 SYMBOL	MIN.	BEG.	MAX.	MIL-E-1 UNITS
ACCEPTANCE TESTS- GROUP E- cont'd.						
GRID CURRENT (2): Ef =7.0 V; Rg1= 0.1 Meg.	2.5	Ic1:	0	---	-0.2	μ Adc
RF NOISE: Ec1=-2Vdc; Eca1=15.0 mVac	2.5	---	---	---	3	mW
NOISE & MICROPHONICS: Ef=6.3Vac; Ehk=0; Ebb= Ecc2=300Vdc; Rg2=0.06 Meg; Rp=0.04 Meg; Rk= 200	2.5	---	---	---	50	mVac
ACCEPTANCE TESTS- GROUP F						
VIBRATION (2): Rp = 2000	6.5	Ep:	---	---	100	mVac
CAPACITANCE: NO SHIELD	6.5	Cgp:	---	---	0.03	pf
NO SHIELD		Cin:	5.2	---	7.8	pf
NO SHIELD		Cout:	1.3	---	2.3	pf
LOW PRESSURE VOLTAGE BREAKDOWN: NOTE 10	6.5		500	---	---	Vac
ACCEPTANCE LIFE TESTS:						
STABILITY LIFE TEST: INTERMITTENT LIFE TEST CONDITIONS:NOTE 7	---	---	---	---	---	---
STABILITY LIFE TEST END POINTS:						
TRANSCONDUCTANCE (1):	1.0	---	---	ΔS_m :	---	10 PERCENT
SURVIVAL RATE LIFE TEST: INTERMITTENT LIFE TEST CONDITIONS OR EQUIVALENT: NOTE 7	0.65	---	---	---	---	---
INTERMITTENT LIFE TEST: Ehk=100Vdc; HEATER POS; Rg1=1.0 Meg; MIN. BULB TEMP.=+165°C	---	---	---	---	---	---

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CHARACTERISTICS AND QUALITY CONTROL TESTS - cont'd.

TEST	AQL %	ALLOWABLE DEF. PER CHARACTER. 1st. SAMP.	COMB. SAMP.	MIL-E-1 SYMBOL	MIN.	MAX.	MIL-E-1 UNITS
ACCEPTANCE LIFE TESTS:- cont'd.							
INTERMITTENT LIFE TEST							
END POINTS (500 HOURS):							
INOPERATIVES	---	1	3		---	---	
HEATER CURRENT	---	1	3	If:	275	325	mA
HEATER CATHODE LEAKAGE:							
HEATER POSITIVE	---	1	3	lhk:	---	10	μ Adc
HEATER NEGATIVE	---	1	3	lhk:	---	10	μ Adc
GRID CURRENT (1)	---	1	3	lc1:	0	-0.1	μ Adc
TRANSCONDUCTANCE (1)	---	1	3	Sm:	3750	6000	μ MHOS
TRANSCONDUCTANCE (1)	---	---	---				
AVG. CHANGE:	---	---	---	AVG. Δ Sm:	---	15	PERCENT
TRANSCONDUCTANCE (2)	---	2	5	Δ Sm:	---	15	PERCENT
INSULATION OF ELECTRODES:							
(gi-all)	---	2	5	Rgi-all:	50	---	MEG.
(p-all)	---	2	5	Rp-all:	50	---	MEG.
INTERMITTENT LIFE TEST							
END POINTS (4000 HRS.)							
INOPERATIVES	---	2	5		---	---	
HEATER CURRENT:	---	2	5	If:	275	325	mA
HEATER CATHODE LEAKAGE:							
HEATER POSITIVE	---	2	5	lhk:	---	10	μ Adc
HEATER NEGATIVE	---	2	5	lhk:	---	10	μ Adc
GRID CURRENT (1)	---	2	5	lc1:	0	-0.1	μ Adc
TRANSCONDUCTANCE (1)	---	2	5	Sm:	3500	6000	μ MHOS

GENERAL NOTE:

GENERAL TUBE MARKING REQUIREMENTS AS CONTAINED IN SPECIFICATION MIL-E-1 AND INSPECTION INSTRUCTIONS FOR ELECTRON TUBES SHALL APPLY TO TUBES MANUFACTURED IN ACCORDANCE WITH THIS TEST SPECIFICATION SHEET EXCEPT THAT THE LAST 2 DIGITS OF THE YEAR OF MANUFACTURE SHALL BE SHOWN RATHER THAN THE SINGLE LAST DIGIT. ALSO EACH TUBE SHALL BE MARKED WITH A LOT IDENTIFICATION SYMBOL, LETTER OR FIGURE, SO THAT TUBES OF A GIVEN LOT MAY BE IDENTIFIED.

A LOT AS REFERENCED IN THIS SPECIFICATION SHALL BE AS SPECIFIED IN PARAGRAPH 5-3.1.3 INSPECTION INSTRUCTIONS FOR ELECTRON TUBES.

NOTES:

1. DIFFICULTY MAY BE ENCOUNTERED IF THIS TUBE IS OPERATED FOR LONG PERIODS OF TIME WITH VERY SMALL VALUES OF CATHODE CURRENT.
2. IF IT IS DESIRED TO CHECK QUALITY SUBSEQUENT TO LOT ACCEPTANCE, THE CONDITIONS AND ACCEPTANCE LIMITS SET FORTH IN THIS SPECIFICATION SHALL APPLY. WHEN 100% TESTING IS PERFORMED AND THE RESULTS INDICATE THAT THE PERCENTAGE OF DEFECTIVES IS EQUAL TO OR LESS THAN THE SPECIFIED AQL VALUES, THE LOT IS DEEMED AS COMPLYING WITH THE INTENT OF THE SPECIFICATION.
3. THIS TEST SHOULD BE CONDUCTED ON THE INITIAL PRODUCTION LOT AND THEREAFTER ON A LOT EVERY 30 DAYS APPROXIMATE. IN THE EVENT OF LOT FAILURE, THE LOT IS REJECTED AND SUCCEEDING LOT IS SUBJECTED TO THIS TEST. ONCE A LOT HAS PASSED, THE 30 DAY RULE SHALL APPLY. MIL-STD-105, SAMPLE SIZE CODE LETTER F, NORMAL AND TIGHTENED INSPECTION TABLES TO APPLY.

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

NOTES- cont'd.

- 4, REFERENCE MIL-STD-105, SAMPLE SIZE CODE LETTER E, NORMAL AND TIGHTENED INSPECTION TABLES TO APPLY.
- 5, REFERENCE MIL-STD-105, SAMPLE SIZE CODE LETTER I, NORMAL AND TIGHTENED INSPECTION TABLES TO APPLY.
- 6, THE AQL FOR THE COMBINED DEFECTIVES FOR ATTRIBUTES IN GROUP D SHALL BE ONE (1) PERCENT. A TUBE HAVING ONE (1) OR MORE DEFECTS SHALL BE COUNTED AS ONE (1) DEFECTIVE. MIL-STD-105, INSPECTION LEVEL 2 SHALL APPLY.
- 7, TUBES TO BE LIFE TESTED AT ROOM TEMPERATURE AMBIENT.
- 8, APPROVED ALTERNATE TEST - THE INSERTION OF A 1.0 MEG RESISTOR IN THE GRID CIRCUIT SHALL NOT CHANGE THE PLATE CURRENT MORE THAN 0.5 MADC.
- 9, THE CATHODE RESISTOR SHALL BE SHUNTED WITH A CAPACITIVE REACTANCE NOT EXCEEDING THREE (3) OHMS AT 60 CYCLES.
- 10, BREAKDOWN SHALL BE DEFINED AS THE VOLTAGE AT WHICH ARCING OCCURS BETWEEN ANODE BASE PIN AND ADJACENT PINS. PRESSURE = 55±5MM MERCURY; TEMPERATURE = 25±5°C; HUMIDITY = 0; VOLTAGE = 500VAC, 60 CYCLES, SINUSOIDAL WAVE FORM.
- 11, REFERENCE SPECIFICATION SHALL BE OF THE ISSUE IN EFFECT ON THE DATE OF INVITATION FOR BID.