

Designed to Meet Military Specifications and Critical Industrial Applications

RCA Type	Proto- type	Name	Description and/or Difference Between Type and Prototype			Special Tests and Controls										
						Shock	Fatigue	Vibration	Glass Strain	AF Noise, Microphonics	Stability	Inoperatives	High-Altitude	Life Test		
			Rating or Characteristic	Premium Type	Proto- Type									Heater-Cycling	Room Temp.	Elevated Bulb Temp.
6072	12AY7	Medium-Mu Twin Triode §	Heater Current, Amperes, for Heater Volts = 6.3 For renewal use only.	0.35	0.3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
6073	0A2	Voltage Regulator*	None	—	—	✓	✓	✓	—	✓	—	—	—	—	—	—
6073/ 0A2	0A2	Voltage Regulator*	Like 0A2, but intended for volt- age-regulator applications critical as to shock and vibration.	—	—	✓	✓	✓	✓	✓	—	—	—	—	—	—
6074	0B2	Voltage Regulator*	None	—	—	✓	✓	✓	—	✓	—	—	—	—	—	—
6074/ 0B2	0B2	Voltage Regulator*	Like 0B2 but intended for volt- age-regulator applications critical as to shock and vibration.	—	—	✓	✓	✓	✓	✓	—	—	—	—	—	—
6080-WA	6AS7-G	Low-Mu Twin Power Triode §	This type is designed to meet the indicated military specification.	—	—	✓	✓	✓	—	✓	✓	✓	✓	✓	✓	✓
6099	6J6	Medium-Mu Twin Triode*	Special Air Force application only. For other military uses, the 6101/ 6J6-WA is recommended.	—	—	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
6101	6J6	Medium-Mu Twin Triode*	Plate Dissip., Watts Plate Res., Ohms Transcon., μ mhos Peak H-K Volts	0.85 6300 6000 ± 180	1.5 7100 5300 ± 100	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	—
6101/ 6J6-WA	6J6	Medium-Mu Twin Triode*	This type is designed to meet the indicated military specification.	—	—	✓	✓	✓	✓	✓	✓	✓	✓	✓	—	✓
6111	—	Medium-Mu Twin Triode*	General-purpose amplifier. Also used as a combined oscillator and mixer tube in vhf applications.	—	—	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	—
6112	—	High-Mu Twin Triode*	Heater-Cathode Type. Low-level audio amplifier. Designed to meet indicated military specification.	—	—	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	—
6136	6AU6	Sharp-Cutoff Pentode*	Input Capacitance (μ mf) For high-frequency broad-band applications.	6.0	5.5	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	—
6186	6AG5	Sharp-Cutoff Pentode*	None RF Amplifier.	—	—	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
6186/ 6AG5-WA	6AG5	Sharp-Cutoff Pentode*	This type is designed to meet the indicated military specification.	—	—	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
6189/ 12AU7-WA	12AU7	Medium-Mu Twin Triode §	This type is designed to meet the indicated military specification.	—	—	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
6201	12AT7	High-Mu Twin Triode §	None	—	—	✓	✓	✓	—	✓	✓	✓	✓	✓	✓	—
6205	5840	Sharp-Cutoff Pentode*	Grid-No. 3 brought out to separate pin	Yes	No	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	—
6206	5899	Semiremote- Cutoff Pentode*	Grid-No. 2 Ma. Similar to 5899 but uses a sepa- rate terminal for grid No. 3.	2.2	2.0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
6626/ 0A2-WA	0A2	Voltage Regulator*	This type is designed to meet the indicated military specification.	—	—	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓


For key to terminal connections see page 30.

* 7-pin miniature type.

§ 9-pin miniature type.


* Large wafer octal 8-pin type with metal sleeve.

* Subminiature type with flexible leads.



6072

6189/12AU7-WA 6201




6073

6073/0A2 6074 6074/0B2



6080-WA



6099 6101

6101/6J6-WA

Designed to Meet Military Specifications and Critical Industrial Applications

Cathode		Maximum Dimensions Inches		Class of Service	Maximum Ratings				Operating Conditions and Characteristics								Type
					Plate Volts	Plate Dissipation Watts	Cathode Current Ma.	Grid-No. 2 Input Watts	Plate Supply Volts	Grid-No. 1 Volts(v) or Cathode Resistance Ohms	Grid-No. 2 Supply Volts	Plate Current Ma.	AC Plate Resistance Ohms	Trans-conductance Micro-mhos	Amplification Factor	Power Output Watts	
Volts	Amps.	Length	Diam.														
6.3 12.6	0.35 0.175	2 ³ / ₁₆	7 ⁷ / ₈	Class A ₁ Amplifier Each Unit	300	1.5	—	—	250	—4v	—	3.0	25000	1750	44	Grid Volts for Cut- off, —8	6072
Cold Cathode		2 ⁵ / ₈	3 ³ / ₄	Voltage Regulator	Ambient Temp., —55 to +90°C Approx. DC Starting Volts, 156 Min. DC Anode-Supply Volts, 185								Approx. DC Operating Volts, 151 Regulation Range, 5 to 30 Ma. Regulation Volts, 2				6073
Cold Cathode		2 ⁵ / ₈	3 ³ / ₄	Voltage Regulator	Ambient Temp., —55 to +90°C Approx. DC Starting Volts, 156 Min. DC Anode-Supply Volts, 185								Approx. DC Operating Volts, 151 Regulation Range, 5 to 30 Ma. Regulation Volts, 2				6073/ 0A2
Cold Cathode		2 ⁵ / ₈	3 ³ / ₄	Voltage Regulator	Ambient Temp., —55 to +90°C Approx. DC Starting Volts, 115 Min. DC Anode-Supply Volts, 133								Approx. DC Operating Volts, 108 Regulation Range, 5 to 30 Ma. Regulation Volts, 1				6074
Cold Cathode		2 ⁵ / ₈	3 ³ / ₄	Voltage Regulator	Ambient Temp., —55 to +90°C Approx. DC Starting Volts, 115 Min. DC Anode-Supply Volts, 133								Approx. DC Operating Volts, 108 Regulation Range, 5 to 30 Ma. Regulation Volts, 1				6074/ 0B2
6.3	2.5	4 ¹ / ₄	1.72	DC Amplifier	For data refer to MIL-E-1/510B specification ^A												6080-WA
6.3	0.45	2 ¹ / ₈	3 ³ / ₄	Class A ₁ Amplifier Each Unit	For government end use only												6099
6.3	0.45	2 ¹ / ₈	3 ³ / ₄	Class A ₁ Amplifier Each Unit	330	0.85	—	—	100	Cath. Res., 50 Ohms Common to Both Units	—	3.5	6300	6000	38	—	6101
6.3	0.45	2 ¹ / ₈	3 ³ / ₄	Class A ₁ Amplifier Each Unit	For data refer to MIL-E-1/243A specification ^A												6101/ 6J6-WA
6.3	0.3	1 ³ / ₈ †	0.4	Class A ₁ Amplifier Each Unit	165	1.1	Neg. DC Grid Volts, 55	—	100	220	—	8.5	4000	5000	20	Grid Volts for Cut- off, —9	6111
6.3	0.3	1 ³ / ₈ †	0.4	Class A ₁ Amplifier Each Unit	For data refer to MIL-E-1/190C specification ^A												6112
6.3	0.3	2 ¹ / ₈	3 ³ / ₄	Class A ₁ Amplifier	300	3.0	—	0.65	100 250	150 68	100 150	5 10.6	500000 1000000	3900 5200	Cutoff Volts, —4.2 Cutoff Volts, —6.5		6136
6.3	0.3	2 ¹ / ₈	3 ³ / ₄	Class A ₁ Amplifier	330	2.5	—	0.55	250	200	150	7.0	—	5000	—	—	6186
6.3	0.3	2 ¹ / ₈	3 ³ / ₄	Class A ₁ Amplifier	For data refer to MIL-E-1/244A specification ^A												6186/ 6AG5-WA
6.3 12.6	0.3 0.15	2 ³ / ₁₆	7 ⁷ / ₈	Class A ₁ Amplifier Each Unit	For data refer to MIL-E-1/246A specification ^A												6189/ 12AU7-WA
6.3 12.6	0.3 0.15	2 ³ / ₁₆	7 ⁷ / ₈	Class A ₁ Amplifier Each Unit	300	2.5	Neg. DC Grid Volts, 50	—	100 250	270 200	—	3.3 10	14300 10900	4000 5500	57 60	—	6201
6.3	0.15	1 ³ / ₈ †	0.4	Class A ₁ Amplifier	165	1.1	16.5	0.55	100	150	100	7.5	260000	5000	Cutoff Volts, —9		6205
6.3	0.15	1 ³ / ₈ †	0.4	Class A ₁ Amplifier	165	1.1	16.5	0.55	100	120	100	7.2	260000	4500	—	—	6206
Cold Cathode		2 ⁵ / ₈	3 ³ / ₄	Voltage Regulator	For data refer to MIL-E-1/939B specification ^A												6626/ 0A2-WA

^A A copy of this specification may be obtained from the Director of the Armed Services Electro-Standards Agency (ASESA) at Fort Monmouth, New Jersey.
^A A copy of this specification may be obtained from the Bureau of Ships, Department of the Navy, Washington 25, D. C.

† Excluding flexible leads.

