



TUNG-SOL**PENTODE**
MINIATURE TYPE

GLASS BULB
MINIATURE BUTTON
7 PIN BASE E7-1
OUTLINE DRAWING
JEDEC 5-2

FOR
VOLTAGE AMPLIFIER SERVICE
IN TV APPLICATIONS

ANY MOUNTING POSITION



BOTTOM VIEW
BASING DIAGRAM
JEDEC 7CC

THE 6485 IS A HIGH TRANSCONDUCTANCE, SHARP CUT-OFF PENTODE IN THE 7 PIN MINIATURE CONSTRUCTION. IT IS DESIGNED FOR USE AS A WIDE BAND OR IF AMPLIFIER. THE TUBE WILL MAINTAIN ITS EMISSION AND FREEDOM FROM EXCESSIVE CATHODE INTERFACE RESISTANCE EVEN AFTER LONG PERIODS OF OPERATION UNDER CUT-OFF CONDITIONS. OTHERWISE, THE 6485 IS IDENTICAL TO THE 6AH6.

DIRECT INTERELECTRODE CAPACITANCES

	WITHOUT SHIELD	WITH ^A SHIELD	
GRID 1 TO PLATE: (G1 TO P) (MAX.)	0.030	0.020	pf
INPUT: G1 to (H + K + G2 + G3)	10	10	pf
OUTPUT: P TO (H + K + G2 + G3)	2.0	3.6	pf

HEATER CHARACTERISTICS AND RATINGS

DESIGN CENTER VALUES - SEE EIA STANDARD RS-239

AVERAGE CHARACTERISTICS	6.3	VOLTS	450	MA.
-------------------------	-----	-------	-----	-----

MAXIMUM RATINGS

DESIGN CENTER VALUES - SEE EIA STANDARD RS-239

PLATE VOLTAGE	300	VOLTS
GRID 2 VOLTAGE	150	VOLTS
PLATE DISSIPATION ^B	3.2	WATTS
GRID 2 DISSIPATION	0.6	WATT
CATHODE CURRENT	25	MA.

^A USING JEDEC SHIELD 316 CONNECTED TO CATHODE.

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CHARACTERISTICS

	PENTODE CONNECTED	TRIODE CONNECTED	
PLATE VOLTAGE	300	150	VOLTS
GRID 2 VOLTAGE	150	D	VOLTS
CATHODE RESISTOR	160	160	OHMS
PLATE CURRENT	10	12.5	MA.
TRANSCONDUCTANCE	9000	11000	μ MHOS
AMPLIFICATION FACTOR		40	
PLATE RESISTANCE	0.5	.0036	MEGOHMS
GRID 2 CURRENT	2.5		MA.
GRID 1 VOLTAGE FOR $I_b = 10 \mu A$. (APPROX.)	-7	-7	VOLTS
TRANSCONDUCTANCE (GRID 3 - PLATE)	C		

^B AT MAXIMUM RATINGS, IT IS NECESSARY THAT AT LEAST ONE SURFACE OF THE SHIELD, IF USED BE BLACK-ENED.

^C GRID 3 HAS PRACTICALLY NO CONTROL CHARACTERISTICS AND IT IS NOT INTENDED TO BE USED AS A CONTROL ELECTRODE. ITS TRANSCONDUCTANCE TO THE PLATE APPROXIMATES 2 MICROMHOS AND THE μ IS 0.7 TO 1.0

^D GRID 2 AND GRID 3 TIED TO PLATE

INPUT COUPLING AND SYNC. POLARITY	OUTPUT VOLTS P P	VOLTAGE GAIN	MAX. WATTS DISSIPATION		CATHODE RESISTOR OHMS	CATHODE CURRENT		GRID RESISTOR OHMS
			SCREEN	PLATE		NO SIG. (MA.)	WITH SIG. (MA.)	
DC-	66	22	0.6	3.2	39	20	13	5000
DC+	100	25	0.4	3.2	270	8	15	5000
AC-	100	25	0.4	3.2	39	20	21	1 meg.
AC+	100	25	0.6	3.2	39	20	18	1 meg.

ALL DATA TAKEN WITH SCREEN VOLTAGE OF 150 AND PLATE LOAD OF

4000 OHMS WITH TYPICAL ON-THE-AIR TELEVISION SIGNALS AND

AVERAGE PRODUCTION TUBES

