



TUNG-SOLPENTODE
MINIATURE TYPERUGGEDIZED FOR MILITARY
AND INDUSTRIAL APPLICATIONSGLASS BULB
MINIATURE BUTTON
7 PIN BASE E7-1
OUTLINE DRAWING
JEDEC 5-1

COATED UNIPOTENTIAL CATHODE

ANY MOUNTING POSITION

BOTTOM VIEW
BASING DIAGRAM
JEDEC 7BD

THE 6968 IS A WIDE-BAND HIGH-FREQUENCY AMPLIFIER IN THE 7 PIN MINIATURE CONSTRUCTION. THE DESIGN OF THE HEATER CATHODE PERMITS INTERMITTENT OPERATION WITH LONG PERIODS OF CUTOFF IN ON-OFF CONTROL APPLICATIONS WITHOUT IMPAIRMENT TO EMISSION. THE ELECTRICAL CHARACTERISTICS OF THE 6968 ARE SIMILAR TO THOSE OF THE 6AK5.

DIRECT INTERELECTRODE CAPACITANCES

WITH SHIELD 316 CONNECTED TO CATHODE

GRID TO PLATE: G1 TO P, MAX.	0.02	pf
INPUT: G1 TO K+H+G2+G3+I.S.	4.0	pf
OUTPUT: P TO K+H+G2+G3+I.S.	2.85	pf

HEATER CHARACTERISTICS AND RATINGS

ABSOLUTE MAXIMUM VALUES - SEE EIA STANDARD RS-239

AVERAGE CHARACTERISTICS	6.3	VOLTS	175	MA.
HEATER SUPPLY LIMITS:				
VOLTAGE/OPERATION			6.3 ± 0.6	VOLTS
MAXIMUM HEATER-CATHODE VOLTAGE:				
HEATER NEGATIVE WITH RESPECT TO CATHODE			135	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE			135	VOLTS

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

MAXIMUM RATINGS

ABSOLUTE MAXIMUM VALUES - SEE EIA STANDARD RS-239

PLATE VOLTAGE	200	VOLTS
GRID 2 VOLTAGE	155	VOLTS
GRID 1 VOLTAGE, NEGATIVE, DC	50	VOLTS
GRID 1 VOLTAGE, POSITIVE, DC	0	VOLTS
PLATE DISSIPATION	1.65	WATTS
GRID 2 DISSIPATION	0.55	WATT
CATHODE CURRENT, DC	20	MA.
GRID 1 CURRENT, DC	1.0	MA.
GRID 1 CIRCUIT RESISTANCE	0.1	MEGOHM
BULB TEMPERATURE AT HOTTEST POINT	165	°C
ALTITUDE ^A	60000	FEET

^A INCREASE IN ALTITUDE OVER THIS VALUE MAY REQUIRE A DECREASE IN INSTANTANEOUS VOLTAGES (EF EXCEPTED)

CHARACTERISTIC RANGE VALUES FOR EQUIPMENT DESIGN

CLASS A AMPLIFIER

	MIN.	AVG.	MAX.	
PLATE VOLTAGE		120		VOLTS
GRID 2 (SCREEN) VOLTAGE		120		VOLTS
GRID 1 (CONTROL-GRID) VOLTAGE		-2.0		VOLTS
TRANSCONDUCTANCE (1)	3800	5000	6200	μ MHOS
PLATE CURRENT	5.0	7.5	11	MA.
GRID 2 CURRENT	0.8	2.5	4.0	MA.
GRID 1 VOLTAGE (APPROX.) FOR $I_b = 10 \mu A$.	-----	-8.5	-----	VOLTS
TRANSCONDUCTANCE PERCENTAGE CHANGE WITH $E_f = 5.7$ V.				
$\frac{\Delta G_m}{G_m (1)} \times 100$			15	PERCENT

CHARACTERISTICS WITH $E_f = 6.3$ VOLTS,
 $E_b = E_{c2} = 120$ VOLTS

PLATE CURRENT CUTOFF, $E_{c1} = -10$ V AND
 $R_L = 0.1$ MEG.

----- 200 μA

PLATE CURRENT CUTOFF, $E_{c1} = -5.5$ V
NEGATIVE GRID 1 CURRENT, $E_{c1} = -2.0$ V,
 $R_{g1} = 0.5$ MEG.

5.0 ----- 200 μA

0 ----- 0.1 μA

GRID 1 EMISSION CURRENT

$E_f = 7.5$ V, $E_{c1} = -45$ V, $R_{g1} = 0.1$ MEG.

----- -0.5 μA .

TRIODE CONNECTED (GRID 2 TIED TO PLATE)^B

PLATE VOLTAGE

----- 150 ----- VOLTS

MAXIMUM PLATE CURRENT ($E_{c1} = -15.0$ V)

----- 100 μA

MINIMUM PLATE CURRENT ($E_{c1} = -7.0$ V)

250 ----- μA .

^B MEASUREMENT OF CURRENT IN CATHODE CIRCUIT

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

SPECIAL TESTS AND RATINGS

VIBRATION NOISE OUTPUT VOLTAGE, RMS (MIL-E-1C 4.9.19.1)
SHOCK RATING
FATIGUE RATING

