

TUNG-SOL

DIODE PENTODE

MINIATURE TYPE


COATED UNIPOTENTIAL CATHODE

HEATER


6.3 VOLTS 0.45 AMP.

AC OR DC

ANY MOUNTING POSITION



GLASS BULB



BOTTOM VIEW
MINIATURE BUTTON
9 PIN BASE
905

THE 6AS8 IS A GENERAL-PURPOSE, MULTIUNIT TUBE USING THE 9 PIN MINIATURE CONSTRUCTION. IT CONTAINS A HIGH PERVEANCE DIODE AND A SHARP-CUTOFF PENTODE IN ONE ENVELOPE. IT IS INTENDED FOR DIVERSIFIED APPLICATIONS IN TELEVISION AND RADIO RECEIVERS.

DIRECT INTERELECTRODE CAPACITANCES — APPROX.

WITH NO EXTERNAL SHIELD

DIODE UNIT		
PLATE TO HEATER & CATHODE & INTERNAL SHIELD	3.0	pf
PENTODE UNIT		
GRID #1 TO PLATE (MAX.)	→ 0.03	pf
INPUT	7.0	pf
OUTPUT	2.4	pf
PENTODE GRID TO DIODE PLATE (MAX.)	0.005	pf
PENTODE PLATE TO DIODE CATHODE (MAX.)	0.15	pf
PENTODE PLATE TO DIODE PLATE (MAX.)	0.10	pf

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

CLASS A₁ AMPLIFIER

HEATER VOLTAGE		
MAXIMUM PEAK HEATER-CATHODE VOLTAGE:	6.3	VOLTS
HEATER NEGATIVE WITH RESPECT TO CATHODE	200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	200 ^A	VOLTS
MAXIMUM PLATE VOLTAGE	300	VOLTS
MAXIMUM GRID #3 VOLTAGE	0	VOLTS
MAXIMUM GRID #2 SUPPLY VOLTAGE	300	VOLTS
MAXIMUM GRID #2 VOLTAGE	SEE SECOND CURVE	
MAXIMUM GRID #1 VOLTAGE:	0	VOLTS
POSITIVE BIAS VALUE		
MAXIMUM PLATE DISSIPATION	2.5	WATTS
MAXIMUM GRID #2 INPUT	0.5	WATT
MAXIMUM GRID #1 CIRCUIT RESISTANCE:		
CATHODE BIAS OPERATION	1.0	MEGOHM
FIXED BIAS OPERATION	0.25	MEGOHM

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

RATINGS — CONT'D

INTERPRETED ACCORDING TO DESIGN MAXIMUM SYSTEM

DIODE UNIT



MAXIMUM PEAK HEATER-CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE	200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	200A	VOLTS
MAXIMUM PEAK INVERSE PLATE VOLTAGE	330	VOLTS
MAXIMUM PEAK PLATE CURRENT	50	MA.
MAXIMUM DC PLATE CURRENT	5	MA.

A THE DC COMPONENT MUST NOT EXCEED 100 VOLTS.

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

PLATE SUPPLY VOLTAGE	200	VOLTS
GRID #3	CONNECTED TO CATHODE AT SOCKET	
GRID #2 SUPPLY VOLTAGE	150	VOLTS
CATHODE BIAS RESISTOR	180	OHMS
PLATE RESISTANCE (APPROX.)	300 000	OHMS
TRANSCONDUCTANCE	6 200	μMHOS
GRID #1 BIAS (APPROX.) FOR $I_b = 10 \mu\text{AMP.}$	-8	VOLTS
PLATE CURRENT	9.5	MA.
GRID #2 CURRENT	3	MA.

→ INDICATES A CHANGE



PRINTED IN U. S. A.

