

NEW **NATIONAL UNION ELECTRON TUBE** DATA

N.U. 6AW7GT

DOUBLE DIODE TRIODE

MECHANICAL DATA:

Outline Drawing.....	9-16
Bulb.....	T-9
Base.....	B8-26 (Small wafer with metal sleeve)
Maximum Diameter.....	1-5/16"
Maximum Overall Length.....	3-7/16"
Maximum Seated Height.....	2-7/8"

PIN CONNECTIONS: RMA BASING DESIGNATION 8CQ

Pin #1 - Shell and cathode for triode and No. 2 Diode Plate
Pin #2 - Triode Grid
Pin #3 - No. 1 Diode Plate
Pin #4 - No. 2 Diode Plate
Pin #5 - Cathode for Diode Plate No. 1
Pin #6 - Triode Plate
Pin #7 - Heater
Pin #8 - Heater

Mounting Position..... Any

ELECTRICAL DATA:

Direct interelectrode capacitances (without shield)

Grid to Diode Plate No. 1	.300	μ f. maximum
Grid to Diode Plate No. 2	.100	μ f. maximum
Diode No. 1 to Diode No. 2.....	.250	μ f. maximum

Ratings

Heater Voltage (ac or dc).....	6.3	Volts
Maximum Triode Plate Voltage.....	300	Volts
Maximum Heater Cathode Voltage.....	90	Volts
Maximum Diode Plate Dissipation.....	0.5	Watt
Maximum continuous Diode Current (each diode)...	1.0	Ma.

Typical Operating Conditions and Characteristics

Heater Voltage.....	6.3	Volts
Heater Current.....	0.300	Ma.
Plate Voltage.....	100	Volts
Grid Voltage.....	0	
Plate Current.....	1.4	Ma.
Transconductance.....	1200	μ mhos.
Amplification Factor.....	80	
Average Diode Current with 3 volts applied (each diode)...	5.0	Ma.

from RMA release #709. Nov. 15, 1948

JUNE 1, 1948

Research Division

ORANGE **NATIONAL UNION RADIO CORPORATION** NEW JERSEY