


SOVTEK 6B4G

6B4G, direct heated triode with oxide cathode is used for low frequency power amplification in output stages of amplifiers.

Standard data		
Heater voltage (AC or DC)	6.3 v	
Plate voltage	250 v	
Grid voltage:		
under DC cathode power supply	- 42 v	
under AC cathode power supply	- 45 v	
Grid effective voltage	30 v	
Plate load resistance	2.5 kOhm	
General data		
Heater current	1 a	
Plate current	60 ma	
Transconductance	5.5 ma/v	
Amplification factor	- 2.2 μ	
Output power	>= 3.0 w	
Limiting values	min	max
Heater voltage	5.7 v	6.9 v
Plate voltage		450 v
Cathode current		100 ma
Plate dissipation power		15 w
Grid negative voltage		- 120 v
Envelope temperature		150° C

The tube can't be exploited at two or more limited conditions.

Max height - 140mm
 Max diameter - 55mm
 Max mass - 75g
 Base - octal



- Pin #1 - no pin
 2 - cathode
 3 - plate
 4 - free
 5 - grid
 6 - free
 7 - cathode
 8 - free

Differential resistance - not less than 600 Ohm, not more than 1000 Ohm.
 input capacitance = 7.5 uf max
 output capacitance = 5.5 uf max
 transfer capacitance = 16.5 uf max