



6BH6

6BH6

SHARP-CUTOFF PENTODE

7-PIN MINIATURE TYPE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage. 6.3 ac or dc volts

Current. 0.15 amp

Direct Interelectrode Capacitances:

	Without External Shield	With External Shield ⁰	
Grid No.1 to plate	0.0035 max.	0.0035 max.	μf
Grid No.1 to cathode, grid No.3 & internal shield, grid No.2, and heater	5.4	5.4	μf
Plate to cathode, grid No.3 & internal shield, grid No.2, and heater	4.4	4.4	μf


Characteristics, Class A₁ Amplifier:

Plate Voltage.	100	250	volts
Grid No.3 (Suppressor)	Connected to cathode at socket		
Grid-No.2 Voltage.	100	150	volts
Grid-No.1 Voltage.	-1	-1	volt
Plate Resistance (Approx.) . . .	0.7	1.4	megohm
Transconductance	3400	4600	μmhos
Plate Current.	3.6	7.4	ma
Grid-No.2 Current.	1.4	2.9	ma
Grid-No.1 Voltage (Approx.) for plate current of 10 μamp . . .	-5	-7.7	volts

Mechanical:

Mounting Position.	Any
Maximum Overall Length	2-1/8"
Maximum Seated Length.	1-7/8"
Length, Base Seat to Bulb Top (Excluding tip) 1-1/2" $\pm$ 3-3/32"	
Maximum Diameter	3/4"
Dimensional Outline.	See General Section
Bulb	T-5-1/2
Base	Small-Button Miniature 7-Pin (JETEC No.E7-1)
Basing Designation for BOTTOM VIEW	7CM

Pin 1 - Grid No.1
Pin 2 - Cathode
Pin 3 - Heater
Pin 4 - Heater
Pin 5 - Plate



Pin 6 - Grid No.2
Pin 7 - Grid No.3,
Internal
Shield

⁰ With external shield JETEC No.316 connected to cathode.

← Indicates a change.

SEPT. 1, 1955

TUBE DIVISION

DATA

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

6BH6



6BH6

SHARP-CUTOFF PENTODE

AMPLIFIER - Class A₁

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE.	300 max. volts
GRID-No.2 (SCREEN) SUPPLY VOLTAGE.	300 max. volts
→ GRID-No.2 VOLTAGE.	See Grid-No.2 Input Rating Chart at front of Receiving Tube Section
GRID-No.1 (CONTROL-GRID) VOLTAGE:	
Negative bias value.	50 max. volts
Positive bias value.	0 max. volts
PLATE DISSIPATION.	3 max. watts
→ GRID-No.2 INPUT:	
For grid-No.2 voltages up to 150 volts . .	0.5 max. watt
For grid-No.2 voltages between 150 and 300 volts.	See Grid-No.2 Input Rating Chart at front of Receiving Tube Section
PEAK HEATER-CATHODE VOLTAGE:	
Heater negative with respect to cathode. .	90 max. volts
Heater positive with respect to cathode. .	90 max. volts

→ Indicates a change.

SEPT. 1, 1955

DATA


TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY



6BH6

6BH6

AVERAGE PLATE CHARACTERISTICS



AUG. 23, 1947


TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-6892

6BH6



AVERAGE CHARACTERISTICS



AUG. 21. 1947

TUBE DEPARTMENT
 RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-6891




6BH6

6BH6

AVERAGE CHARACTERISTICS

 $E_f = 6.3$ VOLTS PLATE VOLTS ≈ 250 GRID - N $\circ$ 3 VOLTS = 0

CURVES		GRID - N $\circ$ 2 VOLTS
I_b —	I_{c2} —	
1	A	50
2	B	100
3	C	150



AUG. 22 1947


TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-6893

6BH6



6BH6

AVERAGE PLATE CHARACTERISTICS
TRIODE CONNECTION

DEC. 10, 1947

TUBE DEPARTMENT

92CM-6896


RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY



6BH6

6BH6

AVERAGE CHARACTERISTICS



AUG. 22 1947


TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-6893

6BH6



6BH6

AVERAGE PLATE CHARACTERISTICS
TRIODE CONNECTION

DEC. 10, 1947

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-6896