

CHARACTERISTICS AND TYPICAL OPERATION**Class A1 Amplifier (Each Section)**

Plate Voltage	150 Volts
Cathode Bias Resistor	220 Ohms
Plate Current	10 Ma
Transconductance	7200 μ mhos
Amplification Factor	36
Plate Resistance	5000 Ohms
Grid Voltage for $I_b = 10 \mu$ a (Section 2 only)	-7 Volts

Cascode Amplifier



Plate Supply Voltage	250 Volts
Plate Current	16 Ma
Grid Voltage	-1 Volt
Transconductance	10,000 μ mhos
E_{c1} for $g_m = 50 \mu$ mhos (Approx.)	-6 Volts

NOTES:

- (1) External shield No. 315.
- (2) Section 2 (Pins 1, 2, and 3) is intended as the input section of the cascode circuit.

Color Television Type
**AFC or DETECTOR (D)
IF/VIDEO/AGC AMPLIFIER (P)**
6BT8**5BT8****Double Diode and Sharp Cutoff Pentode**

Construction	Miniature T-6½
Base	Button 9 Pin, E9-1
Basing	9FE
Outline	6-2
Maximum Diameter	0.875 In.
Maximum Seated Height	1.938 In.
Maximum Overall Height	2.188 In.

**ELECTRICAL DATA****HEATER OPERATION**

Heater Voltage	5BT8 4.7	6BT8 6.3 Volts
Heater Current	600	450 Ma
Heater Warm-up Time	11	— Seconds
Maximum Heater-Cathode Voltage		
Heater Negative with Respect to Cathode		
Total DC and Peak		200 Volts
Heater Positive with Respect to Cathode		
DC		100 Volts
Total DC and Peak		200 Volts

DIRECT INTERELECTRODE CAPACITANCES (Unshielded)**Pentode Section**

Grid No. 1 to Plate (Max.)	0.04 Pf
Input	7.0 Pf
Output	2.3 Pf

Diode (Each Section)

Plate to (h + k)	1.3 Pf
Cathode to (h + p)	3.0 Pf

Coupling

Pentode Grid No. 1 to Diode Plate	0.005 Pf
Pentode Plate to Diode Plate	0.020 Pf

RATINGS (Design Center Rating System)

Plate Voltage (Max.)	300 Volts
Grid No. 2 Supply Voltage (Max.)	300 Volts
Grid No. 2 Voltage	See Rating Chart (Gen. Info. Sec.)
Positive Grid No. 1 Voltage (Max.)	0 Volt
Plate Dissipation (Max.)	2.0 Watts
Grid No. 2 Input (Max.)	0.5 Watt
Grid No. 1 Circuit Resistance	
Fixed Bias (Max.)	0.25 Megohm
Self Bias (Max.)	1.0 Megohm

CHARACTERISTICS AND TYPICAL OPERATION**Pentode**

Plate Voltage	200 Volts
---------------------	-----------