



**ELECTRONIC
INNOVATIONS**
IN ACTION

TUBES

—PRODUCT INFORMATION—

Page 1 5-66

6BZ3

Compactron Diode

FOR TV DAMPING DIODE APPLICATIONS

The 6BZ3 is a compactron containing a single heater-cathode type diode intended for service as the damping diode in the horizontal-deflection circuit of television receivers.

GENERAL

ELECTRICAL

Cathode - Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC* . . . 6.3±0.06 Volts

Heater Current† 1.2 Amperes

Direct Interelectrode Capacitances, approximate§

Cathode to Plate and Heater:

k to (p + h) 11 pf

Plate to Cathode and Heater:

p to (k + h) 8.5 pf

Heater to Cathode: (h to k) . . . 3.4 pf

MECHANICAL

Operating Position - Any

Envelope - T-9, Glass

Base - E12-70, Button 12-Pin

Outline Drawing - EIA 9-60

Maximum Diameter 1.188 Inches

Minimum Diameter 1.062 Inches

Maximum Over-all Length . . . 2.875 Inches

Maximum Seated Height. 2.500 Inches

Minimum Seated Height. 2.250 Inches


MAXIMUM RATINGS

Design-Maximum ratings are limiting values of operating and environmental conditions applicable to a bogey electron tube of a specified type as defined by its published data and should not be exceeded under the worst probable conditions.

The tube manufacturer chooses these values to provide acceptable serviceability of the tube, making allowance for the effects of changes in operating conditions due to variations in the characteristics of the tube under consideration.

The equipment manufacturer should design so that initially and throughout life no design-maximum value for the intended service is exceeded with a bogey tube under the worst probable operating conditions with respect to supply-voltage variation, equipment component variation, equipment control adjustment, load variation, signal variation, environmental conditions, and variations in the characteristics of all other electron devices in the equipment.

PHYSICAL DIMENSIONS




EIA 9-60

TERMINAL CONNECTIONS

- Pin 1 - Heater
- Pin 2 - No Connection
- Pin 3 - No Connection
- Pin 4 - Plate
- Pin 5 - Internal Connection - Do Not Use
- Pin 6 - Internal Connection - Do Not Use
- Pin 7 - Cathode
- Pin 8 - Internal Connection - Do Not Use
- Pin 9 - Internal Connection - Do Not Use
- Pin 10 - Plate
- Pin 11 - No Connection
- Pin 12 - Heater

BASING DIAGRAM



EIA 12FX

The tubes and arrangements disclosed herein may be covered by patents of General Electric Company or others. Neither the disclosure of any information herein nor the sale of tubes by General Electric Company conveys any license under patent claims covering combinations of tubes with other devices or elements. In the absence of an

express written agreement to the contrary, General Electric Company assumes no liability for patent infringement arising out of any use of the tubes with other devices or elements by any purchaser of tubes or others.

GENERAL ELECTRIC



MAXIMUM RATINGS (Cont'd)**TV DAMPER SERVICE†—DESIGN-MAXIMUM VALUES**

Peak Inverse Plate Voltage.	4500	Volts
Plate Dissipation.	6.5	Watts
Steady-State Peak Plate Current	1200	Milliamperes
DC Output Current.	200	Milliamperes
Heater-Cathode Voltage		
Heater Positive with Respect to Cathode		
DC Component	100	Volts
Total DC and Peak.	300	Volts
Heater Negative with Respect to Cathode		
DC Component	900	Volts
Total DC and Peak.	4500	Volts


AVERAGE CHARACTERISTICS

Tube Voltage Drop

Ib = 350 Milliamperes DC 21 Volts

NOTES

- * The equipment designer should design the equipment so that heater voltage is centered at the specified bogey value, with heater supply variations restricted to maintain heater voltage within the specified tolerance.
- † Heater current of a bogey tube at Ef = 6.3 volts.
- § Without external shield.
- ¶ For operation in a 525-line, 30-frame television system as described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations", Federal Communications Commission. The duty cycle of the voltage pulse must not exceed 15 percent of one scanning cycle.

**TUBE DEPARTMENT****GENERAL  ELECTRIC****Owensboro, Kentucky**