


TUNG-SOL

PENTODE

MINIATURE TYPE



GLASS BULB


COATED UNIPOTENTIAL CATHODE

HEATER

6.3 VOLTS 0.3 AMP.

AC OR DC

ANY MOUNTING POSITION



BOTTOM VIEW

MINIATURE BUTTON
7 PIN BASE

7CM

THE 6BZ6 IS A HIGH TRANSCONDUCTANCE, SEMI-REMOTE CUT-OFF, PENTODE AMPLIFIER. IT IS DESIGNED FOR SERVICE AS AN AUTOMATIC GAIN CONTROLLED IF AMPLIFIER IN 300 MA. SERIES HEATER OPERATED TELEVISION RECEIVERS. THERMAL CHARACTERISTICS OF THE HEATER ARE CONTROLLED SUCH THAT HEATER VOLTAGE SURGES DURING THE WARM-UP CYCLE ARE MINIMIZED PROVIDED IT IS USED WITH OTHER TYPES WHICH ARE SIMILARLY CONTROLLED. WITH THE EXCEPTION OF HEATER RATINGS, ITS CHARACTERISTICS ARE IDENTICAL TO THE 3BZ6.

DIRECT INTERELECTRODE CAPACITANCES ←

	WITH SHIELD ^A	WITHOUT SHIELD	
GRID TO PLATE: G_1 TO P (MAX.)	.015	.025	μf
INPUT: G_1 TO (H+K+ G_2 + G_3 +IS)	7.0	7.0	μf
OUTPUT: P TO (H+K+ G_2 + G_3 +IS)	3.0	2.0	μf

^A EXTERNAL SHIELD #316 CONNECTED TO CATHODE AT SOCKET.

RATINGS^B

INTERPRETED ACCORDING TO DESIGN CENTER VALUES

HEATER VOLTAGE	6.3±10% ←	VOLTS
MAXIMUM HEATER CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
TOTAL DC AND PEAK	200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE		
DC	100	VOLTS
TOTAL DC AND PEAK	200	VOLTS
MAXIMUM PLATE VOLTAGE	330 ←	VOLTS
MAXIMUM GRID #2 VOLTAGE	SEE RATING	CURVE
MAXIMUM PLATE DISSIPATION	2.3 ←	WATTS
MAXIMUM GRID #2 DISSIPATION	0.55 ←	WATT
MAXIMUM GRID #2 SUPPLY VOLTAGE	330 ←	VOLTS
MAXIMUM POSITIVE DC GRID #1 VOLTAGE*	0	VOLTS
		MEGOHM

^B DESIGN MAXIMUM RATINGS ARE THE LIMITING VALUES EXPRESSED WITH RESPECT TO BOGIE TUBES AT WHICH SATISFACTORY TUBE LIFE CAN BE EXPECTED TO OCCUR IN THE TYPES OF SERVICE FOR WHICH THE TUBE IS RATED. THEREFORE, THE EQUIPMENT DESIGNER MUST ESTABLISH THE CIRCUIT DESIGN SO THAT INITIALLY AND THROUGHOUT EQUIPMENT LIFE NO DESIGN MAXIMUM VALUE IS EXCEEDED WITH A BOGIE TUBE UNDER THE WORST PROBABLE OPERATING CONDITIONS WITH RESPECT TO SUPPLY-VOLTAGE VARIATION, EQUIPMENT COMPONENT VARIATION, EQUIPMENT CONTROL ADJUSTMENT, LOAD VARIATION, AND ENVIRONMENTAL CONDITIONS.

CONTINUED ON FOLLOWING PAGE

← INDICATES A CHANGE.

* INDICATES AN ADDITION.



TUNG-SOL

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS ←

CLASS A₁ AMPLIFIER

HEATER VOLTAGE	6.3±10%	VOLTS
HEATER CURRENT	0.3	AMP.
PLATE VOLTAGE	125	VOLTS
GRID #2 VOLTAGE	125	VOLTS
GRID #3 VOLTAGE	PIN #7 CONNECTED TO PIN #2 AT SOCKET	
CATHODE BIAS RESISTOR	56	OHMS
PLATE RESISTANCE (APPROX.)	0.26	MEGOHM
TRANSCONDUCTANCE	8 000	μMHOS
PLATE CURRENT	14	MA.
GRID #2 CURRENT	3.6	MA.
GRID #1 VOLTAGE (APPROX.) FOR $G_m = 50 \mu\text{MHOS}$	-19	VOLTS
TRANSCONDUCTANCE ($E_{c1} = -4.5 \text{ V.}, R_k = 0$)	700	μMHOS



6BZ6

