

R.F. PENTODE

6CB6

High slope pentode primarily intended for use as r.f. or i.f. amplifier.

HEATER

Suitable for series or parallel operation

V_h	6.3	V
I_h	300	mA

MOUNTING POSITION

Any

CAPACITANCES

	Shielded	Unshielded
C_{in}	6.5	6.5 pF
C_{out}	3.0	1.9 pF
C_{a-g1}	<0.01	<0.02 pF

CHARACTERISTICS

V_a	200	V
V_{g3}	0	V
V_{g2}	150	V
V_{g1}	-2.2	V
I_a	9.5	mA
I_{g2}	2.8	mA
r_a	600	k Ω
g_m	8.0	mA/V
$V_{g1}(I_a = 10\mu A)$	-8.0	V

LIMITING VALUES



$V_{a(b)} \text{ max.}$	550	V
$V_a \text{ max.}$	300	V
$p_a \text{ max.}$	2.0	W
$V_{g2(b)} \text{ max.}$	300	V
$V_{g2} \text{ max.}$	150	V
$p_{g2} \text{ max.}$	500	mW
$V_{h-k} \text{ max.}$	100	V
$V_{h-k(pk)} \text{ max.}$	200	V

6CB6

R.F. PENTODE

*High slope pentode primarily intended for
use as r.f. or i.f. amplifier.*

4694



B7G Base

