

Information Release

Tube & Component Division

File

ROGERS MAJESTIC ELECTRONICS LIMITED
TECHNICAL INFORMATION CENTRE

LEASIDE (TORONTO 17) ONTARIO

1254

ROGERS


6 CD 7

ELECTRON-RAY TUNING INDICATOR with triode unit and two indicating sectors of different sensitivity

PHYSICAL SPECIFICATIONS

Cathode Coated unipotential
Base Octal 8 pin
Bulb Tubular bulb; diameter 1 3/32" max.
Maximum overall length 3 19/32"
Maximum seated height 3 1/32"
Maximum diameter 1 3/32"
Basing connections-JETEC basing designation 8 EV

- Pin 1 - not connected
- Pin 2 - heater
- Pin 3 - plate No.1 deflection rod No.1
- Pin 4 - control grid
- Pin 5 - target
- Pin 6 - plate No.2 deflection rod No.2
- Pin 7 - heater
- Pin 8 - cathode



GENERAL ELECTRICAL DATA

Heater voltage 6.3 volts
Heater current 0.2 amp

MAXIMUM RATINGS (Design Center Values)

Plate No.1 voltage (cold condition) 550 volts
Plate No.1 voltage 300 volts
Plate No.2 voltage (cold condition) 550 volts
Plate No.2 voltage 300 volts
Target voltage (cold condition) 550 volts
Target voltage 300 volts
Grid current starting point. Grid voltage when grid current is 0.3 μ amp. -1.3 volts
Grid circuit resistance 3 megohms
Heater-cathode voltage 100 volts
External resistance between heater and cathode 20,000 ohms

6CD 7**ROGERS**

OPERATING CHARACTERISTICS






Plate and target supply voltage	100	200	250 volts
Series resistor of plate No.1	1.0	1.0	1.0 megohm
Series resistor of plate No.2	1.0	1.0	1.0 megohm
Target current	approx. 0.4	1.4	2.0 mamps
Triode grid voltage (for section No.1)			
for minimum shadow angle	-2.5	-4.2	-5 volts
for shadow angle of 180°	0	0	0 volt
(for section No.2)			
for minimum shadow angle	-8	-12.5	-16 volts
for shadow angle of 180°	0	0	0 volt

ROGERS


6CD7



2.2.1953

ROGERS

6CD7



6CD7

ROGERS

