


TUNG-SOL

TRIODE-PENTODE
MINIATURE TYPE

GLASS BULB


COATED UNIPOTENTIAL CATHODE

HEATER

6.3 VOLTS 0.75 AMP.

AC OR DC

ANY MOUNTING POSITION

BOTTOM VIEW
SMALL BUTTON
9 PIN BASE

90X

THE 6CX8 IS A SHARP-CUTOFF PENTODE AND A MEDIUM-MU TRIODE IN THE 9 PIN MINIATURE CONSTRUCTION. THE PENTODE SECTION IS INTENDED PRIMARILY FOR USE AS A VIDEO AMPLIFIER. THE TRIODE SECTION IS SUITABLE FOR A 4.5 MEGACYCLE SOUND IF AMPLIFIER, SWEEP OSCILLATOR, SYNC SEPARATOR, SYNC AMPLIFIER, OR SYNC CLIPPER. EXCEPT FOR HEATER RATINGS AND HEATER WARM-UP TIME, THE 6CX8 IS IDENTICAL TO THE 8CX8.

DIRECT INTERELECTRODE CAPACITANCES
WITHOUT EXTERNAL SHIELD

PENTODE SECTION:

GRID #1 TO PLATE	0.06	μf
INPUT	9.0	μf
OUTPUT	4.4	μf

TRIODE SECTION:

GRID TO PLATE	4.4	μf
INPUT	2.2	μf
OUTPUT	0.38	μf

PENTODE GRID #1 TO TRIODE PLATE (MAX.)	.005	μf
TRIODE GRID TO PENTODE PLATE (MAX.)	.018	μf
PENTODE PLATE TO TRIODE PLATE (MAX.)	0.17	μf

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

	PENTODE SECTION	TRIODE SECTION	
HEATER VOLTAGE	6.3 $\pm$ 10%	6.3 $\pm$ 10%	VOLTS
MAXIMUM PLATE VOLTAGE	330	330	VOLTS
MAXIMUM SCREEN-SUPPLY VOLTAGE	330	---	VOLTS
MAXIMUM SCREEN VOLTAGE	SEE RATING CHART		
MAXIMUM POSITIVE DC GRID #1 VOLTAGE	0	0	VOLTS
MAXIMUM PLATE DISSIPATION	5.0	2.0	WATTS
MAXIMUM SCREEN DISSIPATION	1.1	---	WATTS

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

RATINGS - CONT'D

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM



	PENTODE SECTION	TRIODE SECTION	
MAXIMUM HEATER-CATHODE VOLTAGE:			
HEATER POSITIVE WITH RESPECT TO CATHODE			
DC COMPONENT	100	100	VOLTS
TOTAL DC AND PEAK	200	200	VOLTS
HEATER NEGATIVE WITH RESPECT TO CATHODE			
TOTAL DC AND PEAK	200	200	VOLTS
MAXIMUM GRID #1 CIRCUIT RESISTANCE			
WITH FIXED BIAS	0.25	0.5	MEGOHMS
WITH CATHODE BIAS	1.0	1.0	MEGOHMS
HEATER WARM-UP TIME (APPROX.)*		11.0	SECONDS



TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS



CLASS A₁ AMPLIFIER



	PENTODE SECTION	TRIODE SECTION	
HEATER VOLTAGE	6.3±10%	6.3±10%	VOLTS
HEATER CURRENT	0.75	0.75	AMP.
PLATE VOLTAGE	40	150	VOLTS
SCREEN VOLTAGE	125	---	VOLTS
GRID #1 VOLTAGE	0 ^A	---	VOLTS
CATHODE-BIAS RESISTOR	---	68	OHMS
AMPLIFICATION FACTOR	---	40	
PLATE RESISTANCE (APPROX.)	---	70 000	OHMS
TRANSCONDUCTANCE	---	10 000	μMHOS
PLATE CURRENT	40	24	MA.
SCREEN CURRENT	15.5	5.2	MA.
GRID #1 VOLTAGE (APPROX.)			
I _b = 100μA.	---	-8.5	-5.0 VOLTS


DESIGN-MAXIMUM RATINGS ARE THE LIMITING VALUES EXPRESSED WITH RESPECT TO BOGIE TUBES AT WHICH SATISFACTORY TUBE LIFE CAN BE EXPECTED TO OCCUR. TO OBTAIN SATISFACTORY CIRCUIT PERFORMANCE, THEREFORE, THE EQUIPMENT DESIGNER MUST ESTABLISH THE CIRCUIT DESIGN SO THAT NO DESIGN-MAXIMUM VALUE IS EXCEEDED WITH A BOGIE TUBE UNDER THE WORST PROBABLE OPERATING CONDITIONS WITH RESPECT TO SUPPLY-VOLTAGE VARIATION, EQUIPMENT COMPONENT VARIATION, EQUIPMENT CONTROL ADJUSTMENT, LOAD VARIATION, AND ENVIRONMENTAL CONDITIONS.











PRINTED IN U. S. A.

