


TUNG-SOL

TRIPLE TRIODE

GLASS BULB
9-62


COATED UNIPOTENTIAL CATHODE

HEATER

6.3±10% VOLTS 0.45 AMP.

AC OR DC

ANY MOUNTING POSITION



BOTTOM VIEW

BUTTON
12 PIN BASE
12BQ

THE 6D10 IS A COMPACTRON, CONTAINING THREE HIGH-MU TRIODES WITH SEPARATE PIN CONNECTIONS FOR ALL THREE CATHODES, GRIDS, AND PLATES IN A COMPACT T-9 GLASS ENVELOPE. IT IS ESPECIALLY DESIGNED FOR USE AS AN OSCILLATOR-MIXER, GROUNDED-GRID AMPLIFIER, AND AUTOMATIC FREQUENCY CONTROL SERVICE.

DIRECT INTERELECTRODE CAPACITANCES

WITHOUT EXTERNAL SHIELD

GRID TO PLATE (EACH SECTION)	1.5	pf
INPUT (EACH SECTION)	2.2	pf
OUTPUT (EACH SECTION)	0.5	pf

RATINGS

INTERPRETED ACCORDING TO DESIGN MAXIMUM SYSTEM
EACH SECTION

MAXIMUM PLATE VOLTAGE	330	VOLTS
MAXIMUM POSITIVE DC GRID VOLTAGE	0	VOLTS
MAXIMUM NEGATIVE DC GRID VOLTAGE	50	VOLTS
MAXIMUM PLATE DISSIPATION, EACH PLATE	2.0	WATTS
MAXIMUM TOTAL PLATE DISSIPATION, ALL PLATES	6.0	WATTS
MAXIMUM HEATER-CATHODE VOLTAGE:		
HEATER POSITIVE WITH RESPECT TO CATHODE		
DC COMPONENT	100	VOLTS
TOTAL DC AND PEAK	200	VOLTS
HEATER NEGATIVE WITH RESPECT TO CATHODE		
TOTAL DC AND PEAK	200	VOLTS

DESIGN-MAXIMUM RATINGS ARE LIMITING VALUES OF OPERATING AND ENVIRONMENTAL CONDITIONS APPLICABLE TO A ROGEY ELECTRON DEVICE OF A SPECIFIED TYPE AS DEFINED BY ITS PUBLISHED DATA, AND SHOULD NOT BE EXCEEDED UNDER THE WORST PROBABLE CONDITIONS. THE DEVICE MANUFACTURER CHOOSES THESE VALUES TO PROVIDE ACCEPTABLE SERVICEABILITY OF THE DEVICE, TAKING RESPONSIBILITY FOR THE EFFECTS OF CHANGES IN OPERATING CONDITIONS DUE TO VARIATIONS IN DEVICE CHARACTERISTICS. THE EQUIPMENT MANUFACTURER SHOULD DESIGN SO THAT INITIALLY AND THROUGHOUT LIFE NO DESIGN-MAXIMUM VALUE FOR THE INTENDED SERVICE IS EXCEEDED WITH A ROGEY DEVICE UNDER THE WORST PROBABLE OPERATING CONDITIONS WITH RESPECT TO SUPPLY-VOLTAGE VARIATION, EQUIPMENT COMPONENT VARIATION, EQUIPMENT CONTROL ADJUSTMENT, LOAD VARIATION, SIGNAL VARIATION, AND ENVIRONMENTAL CONDITIONS.

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

AVERAGE CHARACTERISTICS — EACH SECTION

PLATE VOLTAGE	125	VOLTS
GRID VOLTAGE	-1.0	VOLTS
AMPLIFICATION FACTOR	57	
PLATE RESISTANCE (APPROX.)	13 600	OHMS
TRANSCONDUCTANCE	4 200	μ MHOS
PLATE CURRENT	4.2	MA.
GRID VOLTAGE (APPROX.)		
$I_b = 20 \mu$ AMPERES	-4	VOLTS