


TUNG-SOL

PENTODE

MINIATURE TYPE



GLASS BULB


COATED UNIPOTENTIAL CATHODE

HEATER

6.3 VOLTS 0.3 AMP.

AC OR DC

ANY MOUNTING POSITION



BOTTOM VIEW

MINIATURE BUTTON
7 PIN BASE

TCM

THE 6DE6 IS A SHARP-CUTOFF PENTODE USING THE 7 PIN MINIATURE CONSTRUCTION. IT IS DESIGNED FOR USE IN 40 MAGACYCLE GAIN-CONTROLLED VIDEO IF STAGES.

DIRECT INTERELECTRODE CAPACITANCES ←

	WITH SHIELD ^A	WITHOUT SHIELD	
GRID TO PLATE: (G ₁ TO P) (MAX.)	.015	.025	μmf
INPUT: G ₁ TO (H+K+G ₂ +G ₃ +i.s.)	6.5	6.5	μmf
OUTPUT: P TO (H+K+G ₂ +G ₃ +i.s.)	3.0	2.0	μmf

^A EXTERNAL SHIELD #316 CONNECTED TO PIN #2.

RATINGS^B ←

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

CLASS A₁ AMPLIFIER

HEATER VOLTAGE	6.3±10%	VOLTS
MAXIMUM HEATER CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
TOTAL DC AND PEAK	200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE		
DC	100	VOLTS
TOTAL DC AND PEAK	200	VOLTS
MAXIMUM PLATE VOLTAGE	330	VOLTS
MAXIMUM GRID #2 SUPPLY VOLTAGE	330	VOLTS
MAXIMUM GRID #2 VOLTAGE		SEE CURVE
MAXIMUM PLATE DISSIPATION	2.3	WATTS
MAXIMUM GRID #2 DISSIPATION	0.55	WATT
MAXIMUM POSITIVE DC GRID #1 VOLTAGE	0	VOLTS

^B DESIGN MAXIMUM RATINGS ARE THE LIMITING VALUES EXPRESSED WITH RESPECT TO BOGIE TUBES AT WHICH SATISFACTORY TUBE LIFE CAN BE EXPECTED TO OCCUR IN THE TYPES OF SERVICE FOR WHICH THE TUBE IS RATED. THEREFORE, THE EQUIPMENT DESIGNER MUST ESTABLISH THE CIRCUIT DESIGN SO THAT INITIALLY AND THROUGHOUT EQUIPMENT LIFE NO DESIGN MAXIMUM VALUE IS EXCEEDED WITH A BOGIE TUBE UNDER THE WORST PROBABLE OPERATING CONDITIONS WITH RESPECT TO SUPPLY-VOLTAGE VARIATION, EQUIPMENT COMPONENT VARIATION, EQUIPMENT CONTROL ADJUSTMENT, LOAD VARIATION, AND ENVIRONMENTAL CONDITIONS.

→ INDICATES A CHANGE.

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS ←

CLASS A₁ AMPLIFIER

HEATER VOLTAGE	6.3	VOLTS
HEATER CURRENT	0.3	AMP.
PLATE VOLTAGE	125	VOLTS
GRID #3 VOLTAGE	PIN 7 CONNECTED TO PIN 2 AT SOCKET	
GRID #2 VOLTAGE	125	VOLTS
CATHODE BIAS RESISTOR	56	OHMS
PLATE RESISTANCE (APPROX.)	0.25	MEGOHM
TRANSCONDUCTANCE	8 000	μMHOS
GRID #1 VOLTAGE (APPROX.) FOR I _b = 20 μA	-9	VOLTS
TRANSCONDUCTANCE (E _{c1} = -5.5V., R _k = 0)	700	μMHOS
PLATE CURRENT	15.5	MA.
GRID #2 CURRENT	4.2	MA.

→ INDICATES A CHANGE.

