

Heater Voltage (ac/dc)	6DT8	12DT8	volts
Heater Current	6.3	12.6	ampere
Heater-Cathode Voltage:	0.3	0.15	
Peak value	±200 max	±200 max	volts
Average value	100 max	100 max	volts

Direct Interelectrode Capacitances (Approx., Each Unit Except as


Noted:

Grid to Plate	1.6*	pF
Grid to Cathode, Heater, and Internal Shield	2.7*	pF
Plate to Cathode, Heater, and Internal Shield	1.6*	pF
Heater to Cathode	3*	pF
Cathode to Grid, Heater, and Internal Shield (Unit No.2)	5.3†	pF
Plate to Grid, Heater, and Internal Shield (Unit No.2)	2.8†	pF

† With external shield connected to grid of unit under test.

* With external shield connected to ground.

* With external shield connected to cathode of unit under test.



INDEX = LARGE LUG
• = SHORT PIN

12EA

MEDIUM-MU TRIODE

6DV4

2DV4

Nuvistor type used at frequencies up to 1000 MHz in uhf oscillator stages of color and black-and-white television receivers. Outlines section, 1; requires nuvistor socket. Type 2DV4 is identical with type 6DV4 except for heater ratings.

Heater Voltage (ac/dc)	2DV4	6DV4	volts
Heater Current	2.1	6.3	ampere
Heater Warm-up Time (Average)	0.45	0.135	seconds
Peak Heater-Cathode Voltage	8	—	volts
	±100 max	±100 max	

Direct Interelectrode Capacitance (Approx.):

Grid to Plate	1.8	pF
Grid to Cathode, Heater, and Shell	4.4	pF
Plate to Cathode, Heater, and Shell	1.9	pF
Plate to Cathode	0.25	pF
Heater to Cathode	1.4	pF
Grid to Cathode	3.7	pF

Class A₁ Amplifier

MAXIMUM RATINGS (Design-Maximum Values)

Plate Supply Voltage	300	volts
Plate Voltage	125	volts
Grid Voltage:		
Negative-bias value	55	volts
Peak positive value	2	volts
Plate Dissipation	1	watt
Cathode Current	15	mA

CHARACTERISTICS

Plate Supply Voltage	75	volts
Cathode-Bias Resistor	100	ohms
Amplification Factor	35	
Plate Resistance (Approx.)	3100	ohms
Transconductance	11500	μmhos
Plate Current	10.5	mA
Grid Voltage (Approx.) for plate current of 10 μA	—7	volts

TYPICAL OPERATION AS OSCILLATOR AT 950 MHz

Plate Voltage	60	volts
Grid Voltage	—2	volts
Grid Resistor	5600	ohms
Plate Current	8	mA
Grid Current	350	μA