


TUNG-SOL


REMOTE-CUTOFF PENTODE

MINIATURE TYPE



UNIPOTENTIAL CATHODE

HIGH GM, SMALL SIGNAL
RF & IF AMPLIFIER
WITH GAIN CONTROL



THE 6EH7 IS A REMOTE-CUTOFF PENTODE IN THE 9 PIN MINIATURE CONSTRUCTION. IT FEATURES VERY HIGH GM WITH A REMOTE CUTOFF AND IS DESIGNED FOR FREQUENCIES INTO THE VHF RANGE. ITS CHIEF APPLICATION IS IN THE IF AMPLIFIER STAGES OF TELEVISION RECEIVERS.

DIRECT INTERELECTRODE CAPACITANCES

WITHOUT EXTERNAL SHIELD

GRID #1 TO PLATE: (G1 TO P) MAX.	0.0055	pf
INPUT: G1 TO (H+G2+G3+K+1S)	9.5	pf
OUTPUT: P TO (H+G2+G3+K+1S)	2.8	pf

HEATER CHARACTERISTICS AND RATINGS

DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239

AVERAGE CHARACTERISTICS	6.3 VOLTS	300	MA
HEATER SUPPLY LIMITS:			
VOLTAGE OPERATION	6.3±0.6	VOLTS	
CURRENT OPERATION	300±20	MA.	
MAXIMUM HEATER-CATHODE VOLTAGE	165	VOLTS	

MAXIMUM RATINGS

DESIGN CENTER VALUES - SEE EIA STANDARD RS-239

PLATE VOLTAGE	250	VOLTS
PLATE DISSIPATION	2.5	WATTS
GRID #2 VOLTAGE	250	VOLTS
GRID #2 DISSIPATION	0.65	WATTS
CATHODE CURRENT	20	MA
GRID #1 CIRCUIT RESISTANCE	1	MEGOHM

CONTINUED ON FOLLOWING PAGE

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CHARACTERISTICS

PLATE VOLTAGE	200	200	VOLTS
GRID #3 VOLTAGE	0	0	VOLTS
GRID #2 VOLTAGE (SUPPLY)	90	200	VOLTS
GRID #2 SERIES RESISTOR	0	24	KILOHMS
GRID #1 VOLTAGE	-2	-2	VOLTS
PLATE CURRENT	12	---	MA.
GRID #2 CURRENT	4.5	---	MA.
TRANSCONDUCTANCE	12500	12500	μ MHOS
PLATE RESISTANCE	0.5	---	MEGOHMS
GRID #1 IMPEDANCE AT 40 MC	13	---	KILOHMS
GRID #1 CUTOFF: $E_{c1} = -6.5$		1250	μ MHOS
$E_{c1} = -9.5$		625	μ MHOS
$E_{c1} = -19.5$		125	μ MHOS
GRID #1 VOLTAGE FOR A CROSS-MODULATION FACTOR OF 10:			
$E_{c1} = -6.5$		100	MV.
$E_{c1} = -9.5$		160	MV.
$E_{c1} = -19.5$		450	MV.

