

Dual Triode

With High-Mu Unit and Low-Mu Unit

GENERAL DATA

Electrical:

Heater, for Unipotential Cathodes:

Voltage (AC or DC) $6.3 \pm 10\%$ volts

Current at 6.3 volts. 0.925 amp

Direct Interelectrode Capacitances (Approx.):[▲]

	Unit No. 1	Unit No. 2	
Grid to plate	4.8	10	μf
Grid to cathode and heater. . .	2.2	7	μf
Plate to cathode and heater . .	0.6	1.8	μf

Characteristics, Class A₁ Amplifier:

	Unit No. 1	Unit No. 2	
Plate Voltage	250	150	volts
Grid Voltage.	-3	-20	volts
Amplification Factor.	68	5.4	
Plate Resistance (Approx.). . .	40000	750	ohms
Transconductance.	1600	7200	μmhos
Plate Current	1.4	50	ma
Plate Current for plate volts =			
60 and grid volts = 0	-	95	ma
Plate Current for grid volts = -28	-	10	ma
Grid Voltage (Approx.) for plate			
$\mu_a = 10$	-5.5	-	volts
Grid Voltage (Approx.) for plate			
$\mu_a = 100$	-	-45	volts

Mechanical:

Operating Position. Any

Maximum Overall Length. 3"

Maximum Seated Length 2-7/16"

Maximum Diameter 1-9/32"

Bulb T9

Base Short Intermediate-Shell Octal 8-Pin

with External Barriers (JEDEC Group 1, B8-58)

Basing Designation for BOTTOM VIEW. 8BD

Pin 1-Grid of

Unit No. 2

Pin 2-Plate of


Unit No. 2

Pin 3-Cathode of

Unit No. 2

Pin 4-Grid of

Unit No. 1



Pin 5-Plate of

Unit No. 1

Pin 6-Cathode of

Unit No. 1

Pin 7-Heater

Pin 8-Heater

VERTICAL-DEFLECTION OSCILLATOR

Values are for Unit No. 1

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system[•]

DC PLATE VOLTAGE. 330 max. volts



PEAK NEGATIVE-PULSE GRID VOLTAGE.	400	max.	volts
CATHODE CURRENT:			
Peak.	77	max.	ma
Average	22	max.	ma
PLATE DISSIPATION	1.5	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode.	200	max.	volts
Heater positive with respect to cathode.	200*	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:

For grid-resistor-bias or cathode-bias operation.	2.2	max.	megohms
---	-----	------	---------

VERTICAL-DEFLECTION AMPLIFIER

Values are for Unit No. 2

Maximum Ratings, Design-Maximum Values:

*For operation in a 525-line, 30-frame system**

DC PLATE VOLTAGE.	330	max.	volts
PEAK POSITIVE-PULSE PLATE VOLTAGE†. . . .	1500	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE.	250	max.	volts
CATHODE CURRENT:			
Peak.	175	max.	ma
Average	50	max.	ma
PLATE DISSIPATION	10	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode.	200	max.	volts
Heater positive with respect to cathode.	200*	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:

For grid-resistor-bias or cathode-bias operation.	2.2	max.	megohms
---	-----	------	---------

▲ Without external shield.


● As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.

* The dc component must not exceed 100 volts.

† This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one vertical scanning cycle. In a 525-line, 30-frame system, 15 per cent of one vertical scanning cycle is 2.5 milliseconds.


OPERATING CONSIDERATIONS

The *bulb* becomes hot during operation. To insure adequate cooling, therefore, it is essential that free circulation of air be provided.



6EM7


AVERAGE PLATE CHARACTERISTICS Unit No.1



92CM-9912



AVERAGE CHARACTERISTICS Unit No.1




92CM-9915



6EM7

AVERAGE PLATE CHARACTERISTICS Unit No. 2



92CM-10466



Dual Triode

With High-Mu Unit and Low-Mu Unit

GENERAL DATA

Electrical:

Heater, for Unipotential Cathodes:

Voltage (AC or DC) 6.3 $\pm$ 10% volts

Current at 6.3 volts. 0.925 amp

Direct Interelectrode Capacitances (Approx.):^a

	Unit No.1	Unit No.2	
Grid to plate	4.8	10	μ f
Grid to cathode and heater. . .	2.2	7	μ f
Plate to cathode and heater . .	0.6	1.8	μ f

Characteristics, Class A₁ Amplifier:

	Unit No.1	Unit No.2	
Plate Voltage	250	150	volts
Grid Voltage.	-3	-20	volts
Amplification Factor.	68	5.4	
Plate Resistance (Approx.). . .	40000	750	ohms
Transconductance.	1600	7200	μ hos
Plate Current	1.4	50	ma
Plate Current for plate volts =			
60 and grid volts = 0	-	95	ma
Plate Current for grid volts = -28 .	-	10	ma
Grid Voltage (Approx.) for plate			
μ a = 10	-5.5	-	volts
Grid Voltage (Approx.) for plate			
μ a = 100.	-	-45	volts

Mechanical:

Operating Position. Any

Maximum Overall Length. 2-7/8" $\leftarrow$

Maximum Seated Length 2-5/16" $\leftarrow$

Maximum Diameter. 1-9/32"

Bulb. T9

Base. Short Intermediate-Shell Octal 8-Pin
with External Barriers (JEDEC Group 1, B8-58)


Basing Designation for BOTTOM VIEW. 8BD

Pin 1-Grid of
Unit No.2

Pin 2-Plate of
Unit No.2

Pin 3-Cathode of
Unit No.2

Pin 4-Grid of
Unit No.1



Pin 5-Plate of
Unit No.1

Pin 6-Cathode of
Unit No.1

Pin 7-Heater

Pin 8-Heater

$\leftarrow$ Indicates a change.



VERTICAL-DEFLECTION OSCILLATOR

Values are for Unit No.1

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^b

DC PLATE VOLTAGE.	330	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE.	400	max.	volts
CATHODE CURRENT:			
Peak.	77	max.	ma
Average	22	max.	ma
PLATE DISSIPATION	1.5	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode. .	200	max.	volts
Heater positive with respect to cathode. .	200 ^c	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:

For grid-resistor-bias or cathode-bias operation. 2.2 max. megohms

VERTICAL-DEFLECTION AMPLIFIER

Values are for Unit No.2

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^b

DC PLATE VOLTAGE.	330	max.	volts
PEAK POSITIVE-PULSE PLATE VOLTAGE ^d	1500	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE.	250	max.	volts
CATHODE CURRENT:			
Peak.	175	max.	ma
Average	50	max.	ma
PLATE DISSIPATION	10	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode. .	200	max.	volts
Heater positive with respect to cathode. .	200 ^c	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:

For grid-resistor-bias or cathode-bias operation. 2.2 max. megohms

^a without external shield.

^b As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.


^c The dc component must not exceed 100 volts.

^d This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one vertical scanning cycle. In a 525-line, 30-frame system, 15 per cent of one vertical scanning cycle is 2.5 milliseconds.

OPERATING CONSIDERATIONS

The bulb becomes hot during operation. To insure adequate cooling, therefore, it is essential that free circulation of air be provided.






92CS-10880



6EM7


AVERAGE PLATE CHARACTERISTICS Unit No.1



92CM-9912



AVERAGE CHARACTERISTICS Unit No.1




92CM-9915RI



6EM7

AVERAGE PLATE CHARACTERISTICS Unit No.2




92CM-10466



AVERAGE CHARACTERISTICS

Unit No. 2



92CM-10467

