

6F17

MINIATURE PULSE & R.F. BEAM TETRODE

Indirectly heated—for parallel operation

RATING

Heater Voltage (volts)	V _h	6.3
Heater Current (amps)	I _h	0.3
Maximum Anode Voltage (volts)	V _{a(max)}	600
Maximum Screen Voltage (volts)	V _{g2(max)}	600
Mutual Conductance (mA/V)	G _m	8.3
Maximum Anode Dissipation (watts)	P _a	‡ 3.5
Maximum Screen Dissipation (watts)	P _{g2}	0.7

- Tested under pulse conditions and taken at V_a = V_{g2} = 250v; V_{g1} = -6.25v; I_a = 64mA.

- ‡ If used in a can at maximum rating the can must be matt black both internally and externally.

INTER-ELECTRODE CAPACITANCES

		q	l
Anode/Control Grid (μF) C _{a-g1}	.03	.033	.05
Anode/Earth (μF) C _{out}	6.0	7.1	5.9
Control Grid/Earth (μF) C _{in}	6.6	7.6	7.5

- || Inter-electrode capacitance with holder capacitance balanced out, but with cylindrical screen.

- q Total capacitance including Benjamin B7G holder type 75/828 and cylindrical screen type 75/832.

- l Total capacitance including Benjamin B7G holder type 75/663R without cylindrical screen.

DIMENSIONS


Maximum Overall Length (mm)	54
Maximum Diameter (mm)	19
Maximum Seated Height (mm)	47.5
Approximate Nett Weight (ozs)	1
Approximate Packed Weight (ozs)	2

MOUNTING POSITION - Unrestricted.

6F17

MINIATURE PULSE & R. F. BEAM TETRODE

Indirectly heated—for parallel operation

BULB ClearBASE B7G

Viewed from free end of pins

CONNEXIONS

Pin 1	Control Grid	g1
Pin 2	Cathode	k
Pin 3	Heater	h
Pin 4	Heater	h
Pin 5	Anode	a
Pin 6	Beam Plates	
Pin 7	Screen Grid	g2


6F17

MINIATURE PULSE & R. F. BEAM TETRODE

Indirectly heated—for parallel operation

AVERAGE CHARACTERISTIC CURVES

*These curves were taken with a short duration pulse
having a 400 μ s on period*



6F17

MINIATURE PULSE & R. F. BEAM TETRODE

Indirectly heated—for parallel operation

AVERAGE CHARACTERISTIC CURVES

These curves were taken with a short duration pulse
having a 400:1 off to on period at $V_{g2} = 280$

