

CHARACTERISTICS

	Triode Unit	Pentode Unit	
Plate Voltage	100	125	volts
Grid-No.2 Voltage	—	90	volts
Grid-No.1 Voltage	—	—1	volt
Grid-No.1-Circuit Resistance	0.1	0.1	megohm
Amplification Factor	40	—	
Plate Resistance	—	4700	ohms
Transconductance	8700	8500	μmhos
Plate Current	12.5	8.5	mA
Grid-No.2 Current	—	2.8	mA
Grid-No.1 Voltage for plate current of 20 μA	—6	—2.5	volts

MAXIMUM CIRCUIT VALUES


	Triode Unit	Pentode Unit	
Grid-No.1-Circuit Resistance:	0.5	0.25	megohm
For fixed-bias operation	1	0.5	megohm
For cathode-bias operation			

6GY5

16GY5, 21GY5

BEAM POWER TUBE

Duodecar type used as horizontal-deflection amplifier in television receivers. Outlines section, 16A; requires duodecar 12-contact socket. Types 16GY5 and 21GY5 are identical with type 6GY5 except for heater ratings.

**12DR**

	6GY5	16GY5	21GY5	
Heater Voltage (ac/dc)	6.3	15.8	21	volts
Heater Current	1.5	0.6	0.45	amperes
Heater Warm-up Time (Average)	—	11	11	seconds
Heater-Cathode Voltage:				
Peak value	±200 max	±200 max	±200 max	volts
Average value	100 max	100 max	100 max	volts

Class A₁ Amplifier**CHARACTERISTICS**

	Pentode Connection	Triode† Connection	
Plate Voltage	5000	60	130
Grid-No.2 (Screen-Grid) Voltage	130	130	130
Grid-No.1 (Control-Grid) Voltage	—	0	—20
Amplification Factor	—	—	4.7
Plate Resistance (Approx.)	—	—	11000
Transconductance	—	—	9100
Plate Current	—	410**	50
Grid-No.2 Current	—	24**	1.75
Grid-No.1 Voltage (Approx.) for plate current of 1 μA	—66	—	—33

** This value can be measured by a method involving a recurrent waveform such that the maximum ratings of the tube will not be exceeded.

† Grid No.2 tied to plate.

Horizontal-Deflection Amplifier

For operation in a 525-line, 30-frame system

MAXIMUM RATINGS (Design-Maximum Values)

DC Plate Supply Voltage	770	volts
Peak Positive-Pulse Plate Voltage#	6500	volts
Peak Negative-Pulse Plate Voltage	1500	volts
DC Grid-No.2 Voltage	220	volts
DC Grid-No.1 Voltage	—55	volts
Peak Negative-Pulse Grid-No.1 Voltage	330	volts
Peak Cathode Current	800	mA
Average Cathode Current	230	mA
Plate Dissipation††	18	watts
Grid-No.2 Input	3.5	watts
Bulb Temperature (At hottest point)	220	°C

MAXIMUM CIRCUIT VALUE

Grid-No.1-Circuit Resistance	1	megohm
------------------------------	---	--------

Pulse duration must not exceed 15% of a horizontal scanning cycle (10 microseconds).

†† A bias resistor or other means is required to protect the tube in absence of excitation.