

Tube type 6H7S
A Power Pentode and High-Mu Triode

Heater volts A.C. or D.C.	6.3 volts
Heater Current	0.5 ampere

POWER PENTODE SECTION

Plate voltage (P ₂)	250 volts
Screen voltage (G ₂₂)	250 volts
Suppressor voltage (G ₃₂)	Internal connec to cathode
Control Grid voltage (G ₁₂)	-18.0 volts
Plate current	32 milliamperes
Screen current	6 milliamperes
Plate resistance	70000 ohms
Amplification Factor	150 approximately
Transconductance	2.2 milliamperes per volt
Load Resistance	7600 ohms
Power Output (10% harmonic distortion)	3.4 watts

TRIODE AMPLIFIER SECTION

Plate Voltage (P ₁)	250 volts
Control Grid voltage (G ₁₁)	-1.5 volts
Amplification Factor	100
Plate resistance	0.33 megohms
Transconductance	0.3 milliamperes per volt
Overall Length	4-1/2 to 4-3/4"
Maximum Diameter	1-9/16"
Bulb	ST-12
Cap	Small Metal
Base	Small 7-pin

Pin Arrangement:

Pin 1 - Heater	Pin 5 - Triode Plate (P ₁)
Pin 2 - Pentode Plate (P ₂)	Pin 6 - Cathode and Suppressor (G ₃₂)
Pin 3 - Screen Grid (G ₂₂)	Pin 7 - Heater
Pin 4 - Control Grid (G ₁₂)	Cap - Control Grid (G ₁₁)

Note 1: The full spray shield is grounded to the chassis by means of a clip.

Note 2: Triode plate voltage is applied through a 0.5 megohm resistor.

From RMA release #8, August 21, 1934
Tube type: 6H7S
registered by Rogers Radio Tubes, Ltd., Toronto, Canada