

RCA-6HG5

BEAM POWER TUBE

7-Pin Miniature Type

Plate Dissipation: 12 Watts

Controlled Cathode Warm-up Time

RCA-6HG5 is a beam power tube of the 7-pin miniature type for use in the audio output stages of television receivers. This tube features a controlled cathode warm-up time of 14 seconds minimum to delay the flow of cathode current during receiver warm up. As a result, extraneous sound is minimized until high voltage is developed and the picture appears.

The 6HG5 has a plate dissipation of 12 watts and can provide a relatively high power output at low plate current. In addition, this type utilizes the RCA "Dark Heater" for long life and dependable performance.

Maximum Seated Length. 2-3/8"
Length, Base Seat to Bulb Top (Excluding Tip) . . 2" ± 3/32"
Diameter 0.650" to 0.750"
Bulb T5-1/2
Base . . . Small-Button Miniature 7-Pin (JEDEC No.E7-1)
Basing Designation for BOTTOM VIEW 7BZ

AMPLIFIER - Class A₁

Maximum Ratings, *Design-Maximum Values:*

Plate Voltage.	275 max.	volts
Grid-No.2 (Screen-Grid) Voltage. . .	275 max.	volts
Grid-No.2 Input.	2 max.	watts
Plate Dissipation.	12 max.	watts
Bulb Temperature (At hottest point on bulb surface)	250 max.	°C

GENERAL DATA

Electrical:

Heater Characteristics and Ratings:

Voltage (AC or DC) 6.3 ± 0.6 volts
Current. 0.45 amp

Peak heater-cathode voltage:

Heater negative with
respect to cathode 200 max. volts
Heater positive with
respect to cathode 200^a max. volts

Minimum Cathode Warm-up Time:^b

Heater volts = 6.3, plate
and grid-No.2 volts = 250,
and cathode resistor (ohms)
= 680. 14 sec

Direct Interelectrode Capacitances (Approx.):

Grid No.1 to plate	0.4	pf
Grid No.1 to cathode & grid No.3, grid No.2, and heater.	8	pf
Plate to cathode & grid No.3, grid No.2, and heater.	8.5	pf

Mechanical:

Operating Position Any
Maximum Overall Length 2-5/8"

Typical Operation and Characteristics:

Plate Voltage.	180	250	volts
Grid-No.2 Voltage.	180	250	volts
Grid-No.1 (Control-Grid) Voltage	-8.5	-12.5	volts
Peak AF Grid-No.1 Voltage. . . .	8.5	12.5	volts
Zero-Signal Plate Current. . . .	29	45	ma
Max.-Signal Plate Current. . . .	30	47	ma
Zero-Signal Grid-No.2 Current. .	3	4.5	ma
Max.-Signal Grid-No.2 Current. .	4	7	ma
Plate Resistance (Approx.) . . .	58000	52000	ohms
Transconductance	3700	4100	μmhos
Load Resistance.	5500	5000	ohms
Total Harmonic Distortion. . . .	8	8	%
Max.-Signal Power Output	2	4.5	watts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

For fixed-bias operation	0.1 max.	megohm
For cathode-bias operation . . .	0.5 max.	megohm


^a The dc component must not exceed 100 volts.

^b The time interval between the instant all electrode voltages are applied and the instant a current of one milliampere flows in the plate circuit of the 6HG5.


Information furnished by RCA is believed to be accurate and reliable. However, no responsibility is assumed by RCA for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of RCA.




AVERAGE CHARACTERISTICS



OPERATION CHARACTERISTICS




DIMENSIONAL OUTLINE



Dimensions in Inches

TERMINAL DIAGRAM

Bottom View



- Pin 1—Grid No. 1
- Pin 2—Cathode,
Grid No. 3
- Pin 3—Heater
- Pin 4—Heater
- Pin 5—Plate
- Pin 6—Grid No. 2
- Pin 7—Grid No. 1

* Measured from base seat to bulb-top line as determined by ring gauge of 7/16 inside diameter.

** Applies in zone starting 0.375 from base seat.